

SOUNDERS

- Industry compatible
- Competitively priced
- Sound output to 95dB

MECHANICAL BUZZERS



ORDERING INFORMATION

| Ordering Code | Rated Voltage (V) | Operation Voltage (V) | Rated Current (mA) | Sound Output at 10cm (dB) | Resonate Frequency (Hz) | Tone | Operating Temp (°C) | Weight | Size |
|---------------|-------------------|-----------------------|--------------------|---------------------------|-------------------------|--------|---------------------|--------|---------------------|
| HJ50-110V/P | 110 | 70.0 - 150.0 | ≤30 | ≥75 | - | - | -25 ~ +110 | 20 | 30 x 23 x H8.5 |
| FCE28-2S3120 | 12 | 9.0 - 15.0 | ≤40 | ≥95 | 2700 - 3200 | Single | -20 ~ +70 | 10 | ø28 x H20 |
| FCE28-2P3120 | 12 | 8.0 - 15.0 | ≤15 | ≥85 | 2700 - 3200 | Pulse | -20 ~ +70 | 10 | ø28 x H20 |
| CMB-06 | 6 | 3.0 - 8.0 | ≤23 | ≥82 | 300 - 500 | - | -40 ~ +85 | 10 | 22.5 x 16.0 x H14.5 |
| BMB-12 | 12 | 8.0 - 16.0 | ≤35 | ≥95 | 300 - 500 | - | -40 ~ +70 | 17 | 26.0 x 26.0 x H19.7 |
| NMB-06 | 6 | 4.0 - 8.0 | ≤35 | ≥95 | 300 - 500 | - | -40 ~ +70 | 17 | 26.0 x 26.0 x H19.6 |

SOUNDERS

- Industry compatible
- Competitively priced
- Sound output to 95dB

DYNAMIC TRANSDUCERS



ORDERING INFORMATION

| Ordering Code | Rated Imp (Ω) | Rate (Max) Power (W) | Sound Output at 10cm (dB) 1.5KHz | Resonate Frequency (kHz) | Rated Frequency Range (Hz) | Operating Temp (°C) | Weight | Size |
|---------------|---------------|----------------------|----------------------------------|--------------------------|----------------------------|---------------------|--------|-------------|
| XD41 | 8±15% | 0.15 (0.2) | 1000±20% | 700 - 5000 | ≥81 | -20 ~ +60 | 10 | ø30 x H12.6 |
| XD3108 | 8±20% | 0.15 (0.2) | 1100±150 | 700 - 4000 | ≥83 | -20 ~ +60 | 11 | ø31.7 x H15 |