

LIGHT SOURCE

CALIBRATED LAMP LIGHT SOURCE SERIES

L7810, L7810-02 (Xenon Lamp)
L7820, L7820-02 (Deuterium Lamp)

Easy to reproduce highly stable light!!





Left: Lamp Housing
Right: Power Supply

TLSOF0151



Left: Lamp Housing
Right: Power Supply

TLSOF0159



These light sources deliver the extremely high levels of "stability" and "repeatability" essential to calibrated light sources. These are available as an optimal set including a lamp, lamp housing and power supply, so that anyone can easily reproduce a highly stable light output.

The L7810-02 xenon lamp light source is calibrated over a wide spectral range from 200 nm to 800 nm, while the L7820-02 deuterium lamp light source is calibrated in the UV range from 200 nm to 400 nm.

Since we are certified as an ASNITE-Calibration laboratory, we are capable of calibrating spectral irradiance over a wide range from 200 nm to 800 nm (L7810-02).

The spectral range at wavelengths shorter than 250 nm is calibrated based on the ASNITE calibration system (Accreditation System of National Institute of Technology and Evaluation), while the spectral range at wavelengths longer than 250 nm is calibrated based on the JCSS (Japan Calibration Service System).

As of August 2009, Hamamatsu Photonics is the only company certified as an ASNITE-Calibration laboratory in the "Light" field.

Manufactured upon receiving your order.

APPLICATIONS

- Light level control of light source
- Sensitivity control of optical sensor
- Light intensity measurement and studies of photoreactions (Light resistance, light curing, etc.)
- Quality control of photometric equipment (Medical analysis equipment, semiconductor inspection systems, imaging devices, etc)


HAMAMATSU

SPECIFICATIONS


| Type No. | L7810 | | L7810-02 | | L7820 | L7820-02 | |
|---|---|------------------------------------|----------|-----------------------------------|-------------------------|------------------------------------|-----------------------------------|
| Lamp | Xenon lamp | | | | Deuterium lamp | | |
| Input Wattage | 150 W | | | | 30 W | | |
| Spectral Distribution | 185 nm to 2000 nm | | | | 185 nm to 400 nm | | |
| Calibrated Range ① | ASNITE Calibration | — | | 200 nm to 245 nm (5 nm intervals) | | — | 200 nm to 245 nm (5 nm intervals) |
| | JCSS | 250 nm to 800 nm (10 nm intervals) | | | | 250 nm to 400 nm (10 nm intervals) | |
| Type of Calibration | Spectral irradiance | | | | | | |
| Calibration Unit | $\mu\text{W}\cdot\text{cm}^{-2}\cdot\text{nm}^{-1}$ | | | | | | |
| Output Window Material (Lamp Housing) | Synthetic quartz | | | | | | |
| Output Window Diameter | $\phi 28$ mm | | | $\phi 25$ mm | | | |
| Optical Axis Height | 140 mm (150 mm including plastic feet) | | | | | | |
| Warm-up Time | 10 minutes or more | | | | | | |
| Timer | Hour display (power supply) | | | Hour display (lamp housing) | | | |
| Input Voltage (AC) | 100 V to 240 V, 50 Hz / 60 Hz | | | | | | |
| Power Consumption | 350 VA | | | 90 VA | | | |
| Cooling (Lamp Housing, Power Supply) | Forced air cooling | | | | | | |
| Ambient Operating Temperature | 0 °C to +40 °C | | | | | | |
| Operating Range During Calibration | Temperature | +23 °C to +27 °C | | | | | |
| | Humidity | 20 % to 70 % (no condensation) | | | | | |
| Dimensions (excluding projecting parts) (W × H × D) | Lamp Housing | 100 mm × 280 mm × 100 mm | | | | | |
| | Power Supply | 144 mm × 90 mm × 282 mm | | | 117 mm × 90 mm × 200 mm | | |
| | Carrying Case ② | 480 mm × 380 mm × 205 mm | | | | | |
| Weight | Lamp Housing | Approx. 2.9 kg | | | Approx. 2.2 kg | | |
| | Power Supply | Approx. 3.2 kg | | | Approx. 2.2 kg | | |
| | Total Weight ③ | Approx. 11 kg | | | Approx. 9.5 kg | | |
| Recalibration Interval ④ | 100 hours in operation | | | | | | |
| Guaranteed Lamp Service Life ⑤ | 500 hours | | | | | | |

- NOTE:** ① Spectral irradiance is measured at a point 50 cm away from the reference plane of the lamp housing.
 ② Carrying case specially designed to contain one set of calibrated lamp light source and accessories.
 ③ Total weight including a set of calibration lamp light source and carrying case.
 ④ This is a general guide for recalibration to maintain calibration reliability. Please contact our sales office for recalibration fee.
 ⑤ This is the total amount of time that the lamp can be recalibrated to serve as a calibrated light source.

COMPARISON OF SPECTRAL IRRADIANCE (Reference Data)



LIGHT INTENSITY DRIFT (Typ.)



This is the logo mark for the Accreditation System of National Institute of Technology and Evaluation (ASNITE), an independent administrative agency in Japan. NITE independently implements calibration standards based on international standards.

In spectral regions not covered by the range specified by JCSS, NITE carries out accreditation to make calibration using international and foreign national standards. The Product Management Dept. of Hamamatsu Photonics K. K. was accredited as an ASNITE calibration company in the "Light" field on May 7, 2004 and is entitled to issue calibration certificates bearing the ASNITE logo mark (ASNITE accreditation symbol).




This is the logo mark for the traceability system approved by the Japan Calibration Service System (JCSS) based on the Measurement Law.

The Product Management Dept. of Hamamatsu Photonics K. K. was accredited as a calibration company in the "Light" field on May 21, 1999, and then became a registered company on August 4, 2009 according to the legal revisions. And is entitled to issue calibration certificates bearing the JCSS logo mark (JCSS accreditation symbol). Those calibration certificates assure the traceability to National Measurement Standards and can be used, for example, as a traceability certificate for ISO9000 series.

DIMENSIONAL OUTLINES (Unit: mm)


L7810, L7810-02 (Xenon Lamp)

LAMP HOUSING



TLSOA0066EC

POWER SUPPLY




* For cable to connect lamp housing with power supply, length: 2 m

TLSOA0090EB

DIMENSIONAL OUTLINES (Unit: mm)


L7820, L7820-02 (Deuterium Lamp)

LAMP HOUSING



TLSOA0072ED

POWER SUPPLY



* For cable to connect lamp housing with power supply, length: 1.8 m

TLSOA0091EB

WARRANTY

This device is guaranteed for one year after delivery date from us. The warranty extends only to replacement of the products. The warranty does not cover damage due to misuse of natural calamity.

Subject to local technical requirements and regulations, availability of products included in this promotional material may vary. Please consult with our sales office. Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2009 Hamamatsu Photonics K.K.

HAMAMATSU

WEB SITE www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Electron Tube Division

314-5, Shimokanzo, Iwata City, Shizuoka Pref., 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P. O. Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: usa@hamamatsu.com

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658 E-mail: info@hamamatsu.de

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: infos@hamamatsu.fr

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road Welwyn Garden City Hertfordshire AL7 1BW, United Kingdom, Telephone: 44-(0)1707-294888, Fax: 44(0)1707-325777 E-mail: info@hamamatsu.co.uk

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171-41 SOLNA, Sweden, Telephone: (46)8-509-031-00, Fax: (46)8-509-031-01 E-mail: info@hamamatsu.se

Italy: Hamamatsu Photonics Italia: S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39)02-935 81 733, Fax: (39)02-935 81 741 E-mail: info@hamamatsu.it

TLSO1054E04
 OCT. 2009 IP