

RGF1A - RGF1M

SURFACE MOUNT FAST RECOVERY RECTIFIERS


PRV : 50 - 1000 Volts
Io : 1.0 Ampere

FEATURES :

- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop
- * Fast switching for high efficiency
- * **Pb / RoHS Free**

MECHANICAL DATA :

- * Case : SMA Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Lead Formed for Surface Mount
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.21 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specific.
Single phase, half wave, 60 Hz, resistive or inductive load
For capacitive load, derate current by 20%

RATING	SYMBOL	RGF1A	RGF1B	RGF1D	RGF1G	RGF1J	RGF1K	RGF1M	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	V
Maximum Average Forward Current $T_L = 125\text{ }^\circ\text{C}$	IF(AV)	1.0							A
Peak Forward Surge Current, 8.3ms Single half sine wave Superimposed on rated load (JEDEC Method)	IFSM	30							A
Maximum Peak Forward Voltage at $I_F = 1.0\text{ A}$	VF	1.3							V
Maximum DC Reverse Current $T_a = 25\text{ }^\circ\text{C}$ at Rated DC Blocking Voltage $T_a = 125\text{ }^\circ\text{C}$	IR	5							μA
	IR(H)	100							
Maximum Reverse Recovery Time (Note 1)	Trr	150				250	500		ns
Total Capacitance (Note 2)	CT	8.5							pf
Junction Temperature Range	TJ	- 65 to + 175							$^\circ\text{C}$
Storage Temperature Range	TSTG	- 65 to + 175							$^\circ\text{C}$

Notes :

- (1) Reverse Recovery Test Conditions : $I_F = 0.5\text{ A}$, $I_R = 1.0\text{ A}$, $I_{rr} = 0.25\text{ A}$.
- (2) Measured at 1.0 MHz and applied reverse voltage of 4.0V

RATING AND CHARACTERISTIC CURVES (RGF1A - RGF1M)

FIG.1 - FORWARD CURRENT DERATING CURRENT




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG.4 - TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG.5 - TYPICAL JUNCTION CAPACITANCE PER LEG

