

≧≧ JUNCTION FET ≦≦

Type No.	V _{GDS} (V)	I _G (mA)	P _D (mW)	I _{DSS}			Y _{fs} TYP. (MIN.)		C _{rss} TYP.			NF MAX.					
				V _{DS} (V)	I _{DSS} (mA)	V _{GS} (V)	V _{DS} (V)	V _{GS} (V)	(mS)	(pF)	V _{DS} (V)	F (MHz)	V _{DS} (V)	ID (mA)	f (Hz)	R _g (KΩ)	
N-Channel																	
P-Channel																	
2SK30ATM	-50	10	100	10	0.3~6.5	0	(1.2)	10	0	2.6	-10	1	5	15	IDSS	120	100
2SK117	-50	10	300	10	0.8~14	0	15	10	0	3	-10	1	2	10	0.5	1K	1
2SK170	-40	10	400	10	2.6~20	0	22	10	0	6	-10	1	2	10	1	1K	1
2SK246	-50	10	300	10	1.2~14	0	(1.5)	10	0	2.5	-10	1	-	-	-	-	-
2SK362	-50	10	300	10	1.2~14	0	19	10	0	3	-10	1	-	-	-	-	-
2SK363	-40	10	400	10	5~30	0	60	10	0	15	-10	1	-	-	-	-	-
2SK364	-40	10	400	10	2.6~20	0	28	10	0	6	-10	1	-	-	-	-	-
2SK369	-40	10	400	10	5~30	0	60	10	0	15	-10	1	2	10	5	1K	0.1
2SK373	-100	10	400	10	0.6~6.5	0	4.6	10	0	3	-10	1	-	-	-	-	-
2SJ74	25	-10	400	-10	-2.6~-20	0	22	-10	0	32	10	1	2	-10	-1	1K	1
2SJ103	50	-10	300	-10	-1.2~-14	0	4.0	-10	0	3.6	10	1	-	-	-	-	-
2SJ104	25	-10	400	-10	-2.6~-20	0	30	-10	0	32	10	1	-	-	-	-	-
2SJ110	25	-10	400	-10	-5~-30	0	60	-10	0	55	10	1	-	-	-	-	-
2SJ111	25	-10	400	-10	-5~-30	0	60	-10	0	55	10	1	2	-10	-5	1K	0.1

Application

- General Purpose
- High |Y_{fs}| Low Noise
- High |Y_{fs}| Low Noise
- Analog SW & General Purpose
- "
- "
- (NEW)
- (NEW)
- (NEW)
- (NEW)
- (NEW)
- (NEW)
- High |Y_{fs}| Low Noise
- High Voltage, Constant Current & Analog SW
- High |Y_{fs}| Low Noise
- Analog SW & General Purpose
- (NEW)
- (NEW)
- (NEW)
- (NEW)
- High |Y_{fs}| Low Noise