



NOTE:

1. DISPLAY TYPE: STN-Y/G-POSITIVE-TRANSFLECTIVE
2. DRIVE METHOD: 1/32 DUTY, 1/5 BIAS, 7.5V Vop(typ.), 5V VDD
3. VIEWING DIR.: 6:00
4. OP. TEMP.: $-20^{\circ}C \sim 70^{\circ}C$
5. ST. TEMP.: $-40^{\circ}C \sim 80^{\circ}C$
7. BACKLIGHT: LED(Y/G), $V_f = 5.0V$, $I_f < 150mA$ $500CD/m^2$
Wavelength $570 \pm 2.5nm$
8. DRIVER IC: NUU6450(OR EQUAL)
9. 提供和FC0配套使用的下接触的18PIN插座一个

TOLERANCE	
>0~6	± 0.10
>6~80	± 0.20
>80~240	± 0.30
>240~400	± 0.50
// L ϕ	± 0.10

HTDISPLAY
HTDISPLAY CO., LTD.

DRAWING No. : HG1223206C-YF62L-VB
DRAWING TITLE: LCD MODULE
FILE NO.: 8

DESIGN	LI JINTANG	06.06.23	STANDARD	REV. : A	SCALE : -
CHECKED			TECHNOLOGY	PROJECTION:	UNIT : MM
APPROVED			Q.A		SHEET : 1/2

REV.	CHANGE CONTENT	BY	DATE
B	增加泡棉、更改电极焊位置及接口	LJT	05.08.19