



BNC ANGLE CABLE PLUGS

| Cable RG-/U | Cable Attachment | | Dimensions, inches (millimeters) | | | | Notes | | | Military Number | Amphenol Number | Fig. |
|----------------------------|------------------|--------|----------------------------------|------------|-----------|------------|-------|-----|------|--------------------|--------------------|------|
| | Outer | Inner | a | b | c • | d | CAI | Pt. | Ins. | | | |
| 55, 58, 141, 142, 223, 400 | Clamp | Solder | 1.68(42.7)■ | .562(14.3) | .214(5.5) | 1.09(27.8) | C25 | P1 | D1 | UG-913/U | 31-204* | 2 |
| 55, 142, 223, 400 | Crimp | Crimp | 1.59(30.2)■ | .562(14.3) | .220(5.6) | 1.19(40.5) | C26a | P15 | D1 | — | 31-334* | 1 ▲ |
| 58, 141 | Crimp | Crimp | 1.59(40.5)■ | .562(14.3) | .206(5.2) | 1.19(30.2) | C26a | P15 | D1 | — | 31-335* | 1 |
| | Crimp | Crimp | 1.66(42.2)■ | .571(14.5) | .210(5.3) | 1.07(27.2) | C26a | P7 | D23 | — | 31-335-RFX | 1 |
| 58, 141, 142, 400 | Clamp | Solder | 1.00(25.4)■ | .562(14.3) | .212(5.4) | 1.25(31.8) | C25 | P1 | D1 | (Cubic Body) | 8525* | 3 |
| 59, 62, 71, 140, 210 | Clamp | Solder | 1.00(25.4) | .562(14.3) | .259(6.6) | 1.25(31.8) | C25 | P1 | D1 | — | 8575* | 3 ▲ |
| | Clamp | Solder | 1.25(31.6) | .562(14.3) | .259(6.6) | 1.03(26.2) | C25 | P1 | D6 | — | 31-850* | 3 ▲ |
| 59, 62, 140, 210 | Crimp | Crimp | 1.59(40.5)■ | .562(14.3) | .259(6.6) | 1.19(30.2) | C26a | P15 | D1 | — | 31-336 | 1 |
| | Crimp | Crimp | 1.66(42.2)■ | .571(14.5) | .260(6.6) | 1.07(27.2) | C26a | P7 | D23 | — | 31-336-RFX | 1 |
| 174, 179, 187, 188 | Clamp | Solder | 1.25(31.6) | .562(14.3) | .115(2.9) | 1.00(25.4) | C25 | P1 | D1 | (Cubic Body) | 33275* | 3 ▲ |
| 174, 188, 316 | Crimp | Crimp | 1.19(30.2)■ | .562(14.3) | .115(2.9) | 1.59(40.5) | C26a | P15 | D1 | — | 31-316* | 1 |
| 58, 141 | Crimp | Solder | .862(21.9) | .571(14.5) | .214(5.5) | 1.07(27.2) | C26a | P7 | D23 | (Cubic Body) | 31-5911-RFX | 4 |
| 59 | Crimp | Solder | .862(21.9) | .571(14.5) | .259(6.6) | 1.07(27.2) | C26a | P7 | D23 | (Cubic Body) | 31-5914-RFX | 4 |
| 316 | Crimp | Solder | .862(21.9) | .571(14.5) | .115(2.9) | 1.09(27.8) | C26a | P7 | D23 | (Cubic Body) | 31-5991-RFX | 4 |
| 316 Die Cast | Crimp | Solder | .862(21.9) | .571(14.5) | .115(2.9) | 1.07(27.2) | C26a | P7 | D23 | (Cubic Body) | 31-316-RFX | 1 |

■ includes outer ferrule • accommodates cable diameter * recognized under the component program of U.L., Inc. ▲ distributor stocked