

256K CMOS Static RAM (32768x8) 28PIN 62256

型名	社名	温度範囲 (°C)	スイッチング特性											電源		入力 [*typ]			出力 [*typ]		備考
			TAAC max (ns)	TCAC max (ns)	TOE max (ns)	TOH min (ns)	TOD max (ns)	TPW min (ns)	TDS min (ns)	TDH min (ns)	TW min (ns)	TWR max (ns)	VDD or VCC (V)	IDD max (mA)	IDB STANDBY (1SB/1SB2) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/ I VOL max (V/mA)	VOH/ I VOH min (V/mA)	
HM62256LP/FP-15SL/LT	HITACHI	0~70	150	150	70	10	50	90	60	0	0	4.5~5.5	70		3/0.5	0.8	2.2	6	0.4/2.1	2.4/1.0	8
HM62256LP/FP-10	HITACHI	0~70	100		50	10	35	75	40	0	0	4.5~5.5	70		3/-	0.8	2.2	6	0.4/2.1	2.4/1	8
HM62256LP/FP-12	HITACHI	0~70	120		60	10	40	90	50	0	0	4.5~5.5	70		3/-	0.8	2.2	6	0.4/2.1	2.4/1	8
HM62256LP/FP-15	HITACHI	0~70	150		70	10	50	110	60	0	0	4.5~5.5	70		3/-	0.8	2.2	6	0.4/2.1	2.4/1	8
HM62256LP/FP-8	HITACHI	0~70	85		45	5	30	70	40	0	0	4.5~5.5	70		3/-	0.8	2.2	6	0.4/2.1	2.4/1	8
HM62256P-10	HITACHI	0~70	100		50	10	35	75	40	0	0	4.5~5.5	70		3/-	0.8	2.2	5	1/-	2.4/-	8
HM62256P-12	HITACHI	0~70	120		60	10	40	90	50	0	0	4.5~5.5	70		3/-	0.8	2.2	5	1/-	2.4/-	8
HM62256P-15	HITACHI	0~70	150		70	10	50	110	60	0	0	4.5~5.5	70		3/-	0.8	2.2	5	1/-	2.4/-	8
HM62256P-8	HITACHI	0~70	85		45	5	30	70	40	0	0	4.5~5.5	70		3/-	0.8	2.2	5	1/-	2.4/-	8
HM62832HLP/JP-25	HITACHI	0~70	25	25	12	5	12	15	12	0	0	4.5~5.5	120		30/1	0.8	2.2	6	0.4/8	2.4/4	10
HM62832HLP/JP-15	HITACHI	0~70	15	15	8	3	7	10	8	0	0	4.5~5.5	170		60/1	0.8	2.2	6	0.4/8	2.4/4	10
HM62832HLP/JP-15	HITACHI	0~70	15	15	8	3	7	10	8	0	0	4.5~5.5	170		60/2.0	0.8	2.2	6	0.4/8	2.4/4	10
HM62832HLP/JP-20	HITACHI	0~70	20	20	10	3	10	12	10	0	0	4.5~5.5	150		50/2.0	0.8	2.2	6	0.4/8	2.4/4	10
HM66202-12	HITACHI	0~70	120		60	10	40	70	50	0	0	4.5~5.5	90		12/-	0.8	2.2	40	0.4/2.1	2.4/1	40
HM66202-15	HITACHI	0~70	150		70	15	50	90	60	0	0	4.5~5.5	90		12/-	0.8	2.2	40	0.4/2.1	2.4/1	40
HM66202-20	HITACHI	0~70	200		100	15	60	100	70	0	0	4.5~5.5	90		12/-	0.8	2.2	40	0.4/2.1	2.4/1	40
HM66202L-12	HITACHI	0~70	120		60	10	40	70	50	0	0	4.5~5.5	90		12/-	0.8	2.2	40	0.4/2.1	2.4/1	40
HM66202L-15	HITACHI	0~70	150		70	15	50	90	60	0	0	4.5~5.5	90		12/-	0.8	2.2	40	0.4/2.1	2.4/1	40
HM66202L-20	HITACHI	0~70	200		100	15	60	100	70	0	0	4.5~5.5	90		12/-	0.8	2.2	40	0.4/2.1	2.4/1	40
HY62C256-10	HYUNDAI	0~70	100	100	50	10	35	70	40	0	0	4.5~5.5	70		3/1.0	0.8	2.2	8	0.4/4	2.4/1.0	10
HY62C256-12	HYUNDAI	0~70	120	120	60	10	40	70	50	0	0	4.5~5.5	70		3/1.0	0.8	2.2	8	0.4/4	2.4/1.0	10
HY62C256-15	HYUNDAI	0~70	150	150	70	10	50	90	60	0	0	4.5~5.5	70		3/1.0	0.8	2.2	8	0.4/4	2.4/1.0	10
HY62C256L-10	HYUNDAI	0~70	100	100	50	10	35	70	40	0	0	4.5~5.5	70		3/1.0	0.8	2.2	8	0.4/4	2.4/1.0	10
HY62C256L-12	HYUNDAI	0~70	120	120	60	10	40	70	50	0	0	4.5~5.5	70		3/1.0	0.8	2.2	8	0.4/4	2.4/1.0	10
HY62C256L-15	HYUNDAI	0~70	150	150	70	10	50	90	60	0	0	4.5~5.5	70		3/1.0	0.8	2.2	8	0.4/4	2.4/1.0	10
HY63C256-35	HYUNDAI	0~70	35	35	25	5	20	25	20	5	5	4.5~5.5	100		15/2	0.8	2.2	8	0.4/4	2.4/1.0	10
HY63C256-45	HYUNDAI	0~70	45	45	30	5	25	35	25	5	5	4.5~5.5	95		15/2	0.8	2.2	8	0.4/4	2.4/1.0	10
HY63C256-55	HYUNDAI	0~70	55	55	35	5	25	40	25	5	5	4.5~5.5	85		15/2	0.8	2.2	8	0.4/4	2.4/1.0	10
HY63C256L-35	HYUNDAI	0~70	35	35	25	5	20	25	20	5	5	4.5~5.5	90		15/0.1	0.8	2.2	8	0.4/4	2.4/1.0	10
HY63C256L-45	HYUNDAI	0~70	45	45	30	5	25	35	25	5	5	4.5~5.5	85		15/0.1	0.8	2.2	8	0.4/4	2.4/1.0	10
HY63C256L-55	HYUNDAI	0~70	55	55	35	5	25	40	25	5	5	4.5~5.5	80		15/0.1	0.8	2.2	8	0.4/4	2.4/1.0	10
IDT71256L-35	IDT	0~70																			
IDT71256L-45	IDT	0~70																			
IDT71256L-55	IDT	0~70																			
IDT71256L-70	IDT	0~70																			
IDT71256L-85	IDT	0~70																			
IDT71256S-35	IDT	0~70																			
IDT71256S-45	IDT	0~70																			
IDT71256S-55	IDT	0~70																			
IDT71256S-70	IDT	0~70																			
IDT71256S-85	IDT	0~70																			
IDT71256S20	IDT	0~70	20	20	10	5	8	15	11	0	0	4.5~5.5	155		20/15	0.8	2.2	11	0.4/8	2.4/4	11