

**TECHNICAL DESCRIPTION**

**FEATURES**

- 2.0 - 2.3 GHz
- LOW LOSS
- HIGH ISOLATION
- EXCELLENT PHASE/AMPLITUDE BALANCE
- SURFACE MOUNT
- TAPE & REEL

**APPLICATIONS**

- WCDMA BASE STATION RF SUBSYSTEMS
- UMTS
- SATCOM




The Multi-Mix<sup>®</sup> QHD series provides a 3 dB coupler with low insertion loss, low VSWR, and high isolation. Accurate phase and amplitude balance make them ideal for applications involving IQ networks, power amplifiers, signal distribution and processing.

QHD quad hybrids are fusion bonded multilayer stripline assemblies. The fusion bonding process yields a homogeneous monolithic dielectric structure with reliability, ruggedness, and electrical performance that is superior to conventional adhesive bonding techniques.

**GENERAL SPECIFICATIONS**

FREQUENCY RANGE GHz		INSERTION LOSS (dB MAX)	AMPLITUDE BALANCE (dB MAX)	PHASE BALANCE	ISOLATION (dB MIN)
2.0 - 2.3		0.15	± 0.25	90 ± 2°	25
VSWR (MAX, ALL PORTS)	INPUT POWER (CW @ 1.2:1 LOAD VSWR)	SIZE (INCHES)	WEIGHT (OZ./GRAMS)	RF INTERFACE	OPERATING TEMPERATURE
1.15:1	100 W	0.56 x 0.20 x 0.075	0.02 / 0.6	Surface Mount	-55° - +85° C

**PACKAGE OUTLINE / TAPE & REEL ORIENTATION**







**THE MULTI-MIX MICROTECHNOLOGY<sup>®</sup> GROUP IS ISO 9001:2000 REGISTERED**




U.S. Patent 6,099,677 and other Patents Pending.

## TYPICAL PERFORMANCE



## MOUNTING CONFIGURATION



## TRUTH TABLE

	1	2	3	4
1	Input	Iso	-90°	0°
2	Iso	Input	0°	-90°
3	-90°	0°	Input	Iso
4	0°	-90°	Iso	Input