
Gloss finish duroplast






FEMALE	1031	22	30	12	M6 M8
Moulded thread	1032	28	35	18	M8 MIO
	1033	35	44	22	MIO MI2
	1034	45	60	25	MIO MI2
SELF FIX	1031/SF	22	30	12	6
Simple	1032/SF	28	35	18	8
knock-on assembly onto plain shaft	1033/SF	35	44	22	10 12
	1034/SF	45	60	25	12 16

Gloss finish duroplast






FEMALE	360	38	24	17	M6 M8 M10
Moulded thread	361	51 34		22	MIO MIZ
SELF FIX	360/SF	38	24	17	10
Simple knock-on assembly onto plain shaft	361/SF	51	34	22	12

Gloss finish duroplast






FEMALE Moulded

940 30 35 16

M6 M8 M10

Gloss finish duroplast





FEMALE

thread

Moulded thread

942 38 38 22

M6 M8 M10

TYPE

PATTERN










THREAD OR BORE

TO FIT SHAFT DIAMETER

8

Gloss finish duroplast







FEMALE	72	22 20		12	M5 M6	
Moulded thread	77	27	20	14	M6	
SELF FIX Simple knock- on assembly	77/SF	27	20	14	6	

Gloss finish duroplast








FEMALE

onto plain shaft

Aluminium insert	1008	35	34	20	M6	M8	
MALE	1008/M	35	34	20	M6	M8	12
Plated steel insert							

Matt finish reinforced thermoplastic






MALE	781/M	15	6	M4	M5 M6	10	15
Plated steel insert	782/M	25	13	M6	M8	. 10	15 20

Gloss finish duroplast








Gloss finish duroplast





MALE	1472/M	21	9	10	M5 M6	10 20
Plated steel insert						

PATTERN TYPE









LENGTH OF MALE THREAD