

# VTC-5760B Pulsed Coupled Cavity TWT

The VTC-5760B pulsed-coupled cavity TWT covers 5.4 GHz to 5.9 GHz with 50 kW peak output power, 2.5 % duty cycle. This device has a non-intercepting grid pulsed and single stage depressed collector to achieve 4.7 dB gain.

Custom configurations are also available. These variations in the performance and configuration include: cooling method (affects average power level), mechanical configuration, electrical and RF connections, & multiple stage depressed collector.

## Features

- 5.4 GHz to 5.9 GHz
- 50 kW PEAK OUTPUT POWER
- 2.5 % DUTY CYCLE
- NON-INTERCEPTING GRID PULSED
- 47 dB GAIN
- SINGLE STAGE DEPRESSED COLLECTOR
- FORCED LIQUID COOLED
- PPM FOCUSED
- COAXIAL INPUT, WR 187 WAVEGUIDE OUTPUT

## Typical Operating Parameters

PARAMETER	MIN	MAX	UNITS
Cathode Voltage	-34	-32	kV
Cathode Current	---	10	a
Heater Voltage	8	10	V
Heater Current	---	8	A
Collector Voltage	19	22	kV
Grid Bias Voltage	-550	-450	V
Grid Pulse Voltage	350	500	v
RF Drive Power	---	0.50	W
Pulse Width	---	100	μsec
Duty Cycle	---	2.5	%
Cooling Flow Rate	3.5	---	gpm
Pressure Drop	---	40	psig
Weight	---	45	lbs
Dimensions	---	6x6x40	inches

The values listed above represent specified limits for the product and are subject to change. The data should be used for basic information only. Formal, controlled specifications may be obtained from CPI for use in equipment design.

For additional information on CPI MPP products contact:

CPI MPP, Coupled Cavity TWT Operation - 3120 Hansen Way, Palo Alto, CA 94303-0750  
 Phone: 650-846-3073, Fax: 650-857-1708, Email: [marketing@mpp.cpii.com](mailto:marketing@mpp.cpii.com), [www.cpii.com/mpp](http://www.cpii.com/mpp)