
HB56U264EJ Series

2,097,152-word $\times$ 64-bit High Density Dynamic RAM Module

HITACHI

Preliminary

Description

The HB56U264EJ belongs to 8 Byte DIMM (Dual In-line Memory Module) family, and has been developed as an optimized main memory solution for 4 and 8 Byte processor applications.

The HB56U264EJ is a $2\text{M} \times 64$ dynamic RAM module, mounted 8 pieces of 16-Mbit DRAM (HM5117805BJ) sealed in SOJ package and 2 pieces of 16-bit BiCMOS line driver (74ABT16244) sealed in TSSOP package. The HB56U264EJ offers Extended Data Out (EDO) Page Mode as a high speed access mode.

An outline of the HB56U264EJ is 168-pin socket type package (dual lead out). Therefore, the HB56U264EJ makes high density mounting possible without surface mount technology. The HB56U264EJ provides common data inputs and outputs. Decoupling capacitors are mounted beneath each SOJ on the module board.

Features

- 168-pin socket type package (Dual lead out)
 - Lead pitch: 1.27 mm
- Single 5 V ($\pm 5\%$) supply
- High speed
 - Access time: $t_{\text{RAC}} = 60/70/80$ ns (max)
 - Access time: $t_{\text{CAC}} = 20/23/25$ ns (max)
- Low power dissipation
 - Active mode: 5.38/4.96/4.54 W (max)
 - Standby mode (TTL): 420 mW (max)
- Buffered input except $\overline{\text{RAS}}$ and DQ
- 4 byte interleave enabled, dual address input (A0/B0)
- EDO page mode capability
- 2,048 refresh cycles: 32 ms
- 2 variations of refresh
 - $\overline{\text{RAS}}$ -only refresh
 - $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh

Note: The specifications of this device are subject to change without notice. Please contact your nearest Hitachi's Sales Dept. regarding specifications.


HB56U264EJ Series

- TTL compatible

Ordering Information

Type No.	Access time	Package	Contact pad
HB56U264EJ-6B	60 ns	168-pin dual lead out socket type	Gold
HB56U264EJ-7B	70 ns		
HB56U264EJ-8B	80 ns		

Pin Arrangement



Pin Arrangement

Pin No.	Pin Name	Pin No.	Pin Name	Pin No.	Pin Name	Pin No.	Pin Name
1	V _{SS}	13	DQ9	25	NC	37	A8
2	DQ0	14	DQ10	26	V _{CC}	38	A10
3	DQ1	15	DQ11	27	$\overline{WE0}$	39	NC
4	DQ2	16	DQ12	28	$\overline{CE0}$	40	V _{CC}
5	DQ3	17	DQ13	29	$\overline{CE2}$	41	NC
6	V _{CC}	18	V _{CC}	30	$\overline{RE0}$	42	NC
7	DQ4	19	DQ14	31	$\overline{OE0}$	43	V _{SS}
8	DQ5	20	DQ15	32	V _{SS}	44	$\overline{OE2}$
9	DQ6	21	DQ16	33	A0	45	$\overline{RE2}$
10	DQ7	22	NC	34	A2	46	$\overline{CE4}$
11	NC	23	V _{SS}	35	A4	47	$\overline{CE6}$
12	V _{SS}	24	NC	36	A6	48	$\overline{WE2}$

Pin Arrangement (cont)

Pin No.	Pin Name	Pin No.	Pin Name	Pin No.	Pin Name	Pin No.	Pin Name
49	V _{CC}	79	PD1	109	NC	139	DQ56
50	NC	80	PD3	110	V _{CC}	140	DQ57
51	NC	81	PD5	111	NC	141	DQ58
52	DQ18	82	PD7	112	$\overline{CE1}$	142	DQ59
53	DQ19	83	ID0 (V _{SS})	113	$\overline{CE3}$	143	V _{CC}
54	V _{SS}	84	V _{CC}	114	NC	144	DQ60
55	DQ20	85	V _{SS}	115	NC	145	NC
56	DQ21	86	DQ36	116	V _{SS}	146	NC
57	DQ22	87	DQ37	117	A1	147	NC
58	DQ23	88	DQ38	118	A3	148	NC
59	V _{CC}	89	DQ39	119	A5	149	DQ61
60	DQ24	90	V _{CC}	120	A7	150	NC
61	NC	91	DQ40	121	A9	151	DQ63
62	NC	92	DQ41	122	NC	152	V _{SS}
63	NC	93	DQ42	123	NC	153	DQ64
64	NC	94	DQ43	124	V _{CC}	154	DQ65
65	DQ25	95	NC	125	NC	155	DQ66
66	NC	96	V _{SS}	126	B0	156	DQ67
67	DQ27	97	DQ45	127	V _{SS}	157	V _{CC}
68	V _{SS}	98	DQ46	128	NC	158	DQ68
69	DQ28	99	DQ47	129	NC	159	DQ69
70	DQ29	100	DQ48	130	$\overline{CE5}$	160	DQ70
71	DQ30	101	DQ49	131	$\overline{CE7}$	161	NC
72	DQ31	102	V _{CC}	132	$\overline{PDE}$	162	V _{SS}
73	V _{CC}	103	DQ50	133	V _{CC}	163	PD2
74	DQ32	104	DQ51	134	NC	164	PD4
75	DQ33	105	DQ52	135	NC	165	PD6
76	DQ34	106	NC	136	DQ54	166	PD8
77	NC	107	V _{SS}	137	DQ55	167	ID1 (V _{SS})
78	V _{SS}	108	NC	138	V _{SS}	168	V _{CC}

HB56U264EJ Series

Pin Description

Pin Name	Function
A0 to A10, B0	Address Input : A0 to A10, B0 Row Address : A0 to A10, B0 Column Address : A0 to A9, B0 Refresh Address : A0 to A10, B0
DQ0 to DQ7, DQ9 to DQ16, DQ18 to DQ25, DQ27 to DQ34, DQ36 to DQ43, DQ45 to DQ52, DQ54 to DQ61, DQ63 to DQ70	Data-in/Data-out
$\overline{\text{RE0}}, \overline{\text{RE2}}$	Row Address Strobe ($\overline{\text{RAS}}$)
$\overline{\text{CE0}}$ to $\overline{\text{CE7}}$	Column Address Strobe ($\overline{\text{CAS}}$)
$\overline{\text{WE0}}, \overline{\text{WE2}}$	Read/Write Enable
$\overline{\text{OE0}}, \overline{\text{OE2}}$	Output Enable
V_{CC}	Power Supply
V_{SS}	Ground
PD1 to PD8	Presence Detect
ID0, ID1	ID bit
$\overline{\text{PDE}}$	Presence Detect Enable
NC	No Connection


Presence Detect Pin Assignment

Pin Name	Pin No.	$\overline{\text{PDE}} = \text{Low}$			$\overline{\text{PDE}} = \text{High}$
		60 ns	70 ns	80 ns	All
PD1	79	1	1	1	High-Z
PD2	163	0	0	0	High-Z
PD3	80	0	0	0	High-Z
PD4	164	1	1	1	High-Z
PD5	81	1	1	1	High-Z
PD6	165	1	0	1	High-Z
PD7	82	1	1	0	High-Z
PD8	166	1	1	1	High-Z

1: High Level (Driver Output)

0: Low Level (Driver Output)

Block Diagram



HB56U264EJ Series

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Voltage on any pin relative to V_{SS}	V_T	-0.5 to +7.0	V
Supply voltage relative to V_{SS}	V_{CC}	-0.5 to +7.0	V
Short circuit output current	I_{out}	50	mA
Power dissipation	P_t	9	W
Operating temperature	T_{opr}	0 to +70	°C
Storage temperature	T_{stg}	-55 to +125	°C

Recommended DC Operating Conditions ($T_a = 0$ to 70°C)

Parameter	Symbol	Min	Typ	Max	Unit	Note
Supply voltage	V_{SS}	0	0	0	V	
	V_{CC}	4.75	5.0	5.25	V	1
Input high voltage	V_{IH}	2.4	—	5.5	V	1
Input low voltage	V_{IL}	-0.5	—	0.8	V	1

Note: 1. All voltage referred to V_{SS} .

HB56U264EJ Series

DC Characteristics (Ta = 0 to 70°C, V_{CC} = 5 V ± 5%, V_{SS} = 0 V)

Parameter	Symbol	60 ns		70 ns		80 ns		Unit	Test Conditions	Notes
		Min	Max	Min	Max	Min	Max			
Operating current	I _{CC1}	—	1024	—	944	—	864	mA	t _{RC} = min	1, 2
Standby current	I _{CC2}	—	80	—	80	—	80	mA	TTL interface RAS, CAS = V _{IH} Dout = High-Z	
		—	72	—	72	—	72	mA	CMOS interface RAS, CAS ≥ V _{CC} – 0.2 V Dout = High-Z	
RAS-only refresh current	I _{CC3}	—	1024	—	944	—	864	mA	t _{RC} = min	2
Standby current	I _{CC5}	—	104	—	104	—	104	mA	RAS = V _{IH} , CAS = V _{IL} Dout = enable	1
CAS-before-RAS refresh current	I _{CC6}	—	1024	—	944	—	864	mA	t _{RC} = min	
EDO page mode current	I _{CC7}	—	1024	—	944	—	864	mA	t _{HPC} = min	1, 3
Input leakage current	I _{LI}	–10	10	–10	10	–10	10	μA	0 V ≤ Vin ≤ 5.5 V	
Output leakage current	I _{LO}	–10	10	–10	10	–10	10	μA	0 V ≤ Vout ≤ 5.5 V Dout = disable	
Output high voltage	V _{OH}	2.4	V _{CC}	2.4	V _{CC}	2.4	V _{CC}	V	High Iout = –2 mA	
Output low voltage	V _{OL}	0	0.4	0	0.4	0	0.4	V	Low Iout = 2 mA	

Notes: 1. I_{CC} depends on output load condition when the device is selected, I_{CC} max is specified at the output open condition.

2. Address can be changed once or less while RAS = V_{IL}.

3. Address can be changed once or less while CAS = V_{IH}.

Capacitance (Ta = 25°C, V_{CC} = 5 V ± 5%)

Parameter	Symbol	Typ	Max	Unit	Notes
Input capacitance (Address)	C _{I1}	—	20	pF	1
Input capacitance (CAS, WE, OE)	C _{I2}	—	20	pF	1
Input capacitance (RAS)	C _{I3}	—	48	pF	1
I/O capacitance (DQ)	C _{I/O}	—	20	pF	1, 2

Notes: 1. Capacitance measured with Boonton Meter or effective capacitance measuring method.

2. CAS = V_{IH} to disable Dout.

HB56U264EJ Series

AC Characteristics ($T_a = 0 \text{ to } 70^\circ\text{C}$, $V_{CC} = 5 \text{ V} \pm 5\%$, $V_{SS} = 0 \text{ V}$)^{*1, *2, *18, *19}

Test Conditions

- Input rise and fall time: 2 ns
- Input level: $V_{IL} = 0 \text{ V}$, $V_{IH} = 3.0 \text{ V}$
- Input timing reference levels: 0.8 V, 2.4 V
- Output timing reference levels: 0.8 V, 2.0 V
- Output load: 1 TTL gate + C_L (100 pF) (Including scope and jig)

Read, Write, Read-Modify-Write and Refresh Cycles (Common parameters)

		HB56U264EJ							
		60 ns		70 ns		80 ns			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Random read or write cycle time	t _{RC}	104	—	124	—	144	—	ns	
$\overline{\text{RAS}}$ precharge time	t _{RP}	40	—	50	—	60	—	ns	
$\overline{\text{CAS}}$ precharge time	t _{CP}	10	—	13	—	15	—	ns	
$\overline{\text{RAS}}$ pulse width	t _{RAS}	60	10000	70	10000	80	10000	ns	
$\overline{\text{CAS}}$ pulse width	t _{CAS}	10	10000	13	10000	15	10000	ns	
Row address setup time	t _{ASR}	0	—	0	—	0	—	ns	
Row address hold time	t _{RAH}	10	—	10	—	10	—	ns	
Column address setup time	t _{ASC}	0	—	0	—	0	—	ns	
Column address hold time	t _{CAH}	10	—	13	—	15	—	ns	
$\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ delay time	t _{RCD}	20	40	20	47	20	55	ns	3
$\overline{\text{RAS}}$ to column address delay time	t _{RAD}	15	25	15	30	15	35	ns	4
$\overline{\text{RAS}}$ hold time	t _{RSH}	20	—	23	—	25	—	ns	
$\overline{\text{CAS}}$ hold time	t _{CSH}	48	—	58	—	68	—	ns	
$\overline{\text{CAS}}$ to $\overline{\text{RAS}}$ precharge time	t _{CRP}	10	—	10	—	10	—	ns	
$\overline{\text{OE}}$ to Din delay time	t _{OED}	20	—	23	—	25	—	ns	5
$\overline{\text{OE}}$ delay time from Din	t _{DZO}	0	—	0	—	0	—	ns	6
$\overline{\text{CAS}}$ delay time from Din	t _{DZC}	0	—	0	—	0	—	ns	6
Transition time (rise and fall)	t _T	2	50	2	50	2	50	ns	7
Refresh period (2048 cycle)	t _{REF}	—	32	—	32	—	32	ms	

Read Cycle

		HB56U264EJ							
		60 ns		70 ns		80 ns			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Access time from $\overline{\text{RAS}}$	t_{RAC}	—	60	—	70	—	80	ns	8, 9
Access time from $\overline{\text{CAS}}$	t_{CAC}	—	20	—	23	—	25	ns	9, 10, 17
Access time from address	t_{AA}	—	35	—	40	—	45	ns	9, 11, 17
Access time from $\overline{\text{OE}}$	t_{OEA}	—	20	—	23	—	25	ns	9
Read command setup time	t_{RCS}	0	—	0	—	0	—	ns	
Read command hold time to $\overline{\text{CAS}}$	t_{RCH}	0	—	0	—	0	—	ns	12
Read command hold time from $\overline{\text{RAS}}$	t_{RCHR}	60	—	70	—	80	—	ns	
Read command hold time to $\overline{\text{RAS}}$	t_{RRH}	0	—	0	—	0	—	ns	12
Column address to $\overline{\text{RAS}}$ lead time	t_{RAL}	35	—	40	—	45	—	ns	
Column address to $\overline{\text{CAS}}$ lead time	t_{CAL}	18	—	23	—	28	—	ns	
$\overline{\text{CAS}}$ to output in low-Z	t_{CLZ}	2	—	2	—	2	—	ns	
Output data hold time	t_{OH}	3	—	3	—	3	—	ns	
Output data hold time from $\overline{\text{OE}}$	t_{OHO}	3	—	3	—	3	—	ns	
Output buffer turn-off time	t_{OFF}	—	20	—	20	—	20	ns	13
Output buffer turn-off to $\overline{\text{OE}}$	t_{OEZ}	—	20	—	20	—	20	ns	13
$\overline{\text{CAS}}$ to Din delay time	t_{CDD}	20	—	23	—	25	—	ns	5
Output data hold time from $\overline{\text{RAS}}$	t_{OHR}	3	—	3	—	3	—	ns	
Output buffer turn-off to $\overline{\text{RAS}}$	t_{OFR}	—	15	—	15	—	15	ns	
Output buffer turn-off to $\overline{\text{WE}}$	t_{WEZ}	—	20	—	20	—	20	ns	
$\overline{\text{WE}}$ to Din delay time	t_{WED}	20	—	23	—	25	—	ns	
$\overline{\text{RAS}}$ to Din delay time	t_{RDD}	15	—	18	—	20	—	ns	

HB56U264EJ Series

Write Cycle

		HB56U264EJ							
		60 ns		70 ns		80 ns			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Write command setup time	t_{WCS}	0	—	0	—	0	—	ns	14
Write command hold time	t_{WCH}	10	—	13	—	15	—	ns	
Write command pulse width	t_{WP}	10	—	10	—	10	—	ns	
Write command to $\overline{RAS}$ lead time	t_{RWL}	15	—	18	—	20	—	ns	
Write command to $\overline{CAS}$ lead time	t_{CWL}	10	—	13	—	15	—	ns	
Data-in setup time	t_{DS}	0	—	0	—	0	—	ns	15
Data-in hold time	t_{DH}	15	—	18	—	20	—	ns	15

Read-Modify-Write Cycle

		HB56U264EJ							
		60 ns		70 ns		80 ns			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Read-modify-write cycle time	t_{RWC}	149	—	175	—	199	—	ns	
$\overline{RAS}$ to $\overline{WE}$ delay time	t_{RWD}	87	—	100	—	112	—	ns	14
$\overline{CAS}$ to $\overline{WE}$ delay time	t_{CWD}	37	—	43	—	47	—	ns	14
Column address to $\overline{WE}$ delay time	t_{AWD}	52	—	60	—	67	—	ns	14
$\overline{OE}$ hold time from $\overline{WE}$	t_{OEH}	15	—	18	—	20	—	ns	

Refresh Cycle

		HB56U264EJ							
		60 ns		70 ns		80 ns			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
$\overline{CAS}$ setup time (CBR refresh cycle)	t_{CSR}	10	—	10	—	10	—	ns	
$\overline{CAS}$ hold time (CBR refresh cycle)	t_{CHR}	10	—	10	—	10	—	ns	
$\overline{WE}$ setup time (CBR refresh cycle)	t_{WRP}	5	—	5	—	5	—	ns	
$\overline{WE}$ hold time (CBR refresh cycle)	t_{WRH}	10	—	10	—	10	—	ns	
$\overline{RAS}$ precharge to $\overline{CAS}$ hold time	t_{RPC}	0	—	0	—	0	—	ns	

EDO Page Mode Cycle

		HB56U264EJ							
		60 ns		70 ns		80 ns			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
EDO page mode cycle time	t _{HPC}	25	—	30	—	35	—	ns	20
EDO page mode $\overline{\text{RAS}}$ pulse width	t _{RASP}	—	100000	—	100000	—	100000	ns	16
Access time from $\overline{\text{CAS}}$ precharge	t _{CPA}	—	40	—	45	—	50	ns	9, 17
$\overline{\text{RAS}}$ hold time from $\overline{\text{CAS}}$ precharge	t _{CPRH}	40	—	45	—	50	—	ns	
Output data hold time from $\overline{\text{CAS}}$ low	t _{DOH}	3	—	3	—	3	—	ns	9, 17
$\overline{\text{CAS}}$ hold time refferd $\overline{\text{OE}}$	t _{COL}	10	—	13	—	15	—	ns	
$\overline{\text{CAS}}$ to $\overline{\text{OE}}$ setup time	t _{COP}	5	—	5	—	5	—	ns	
Read command hold time from $\overline{\text{CAS}}$ precharge	t _{RCHC}	35	—	40	—	45	—	ns	

EDO Page Mode Read-Modify-Write Cycle

		HB56U264EJ							
		60 ns		70 ns		80 ns			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
EDO page mode read-modify-write cycle time	t _{HPRWC}	79	—	90	—	99	—	ns	
WE delay time from $\overline{\text{CAS}}$ precharge	t _{CPW}	54	—	62	—	69	—	ns	14

- Notes: 1. AC measurements assume $t_r = 2$ ns.
2. An initial pause of 200 μ s is required after power up followed by a minimum of eight initialization cycles (any combination of cycles containing $\overline{RAS}$ -only refresh or $\overline{CAS}$ -before- $\overline{RAS}$ refresh). If the internal refresh counter is used, a minimum of eight $\overline{CAS}$ -before- $\overline{RAS}$ refresh cycles are required.
3. Operation with the t_{RCD} (max) limit insures that t_{RAC} (max) can be met, t_{RCD} (max) is specified as a reference point only; if $t_{RCD} \geq t_{RCD}(\text{max}) + t_{AA}(\text{max}) - t_{CAC}(\text{max})$, then access time is controlled exclusively by t_{CAC} .
4. Operation with the t_{RAD} (max) limit insures that t_{RAC} (max) can be met, t_{RAD} (max) is specified as a reference point only; if t_{RAD} is greater than the specified t_{RAD} (max) limit, then access time is controlled exclusively by t_{AA} .
5. Either t_{OED} or t_{CDD} must be satisfied.
6. Either t_{DZO} or t_{DZC} must be satisfied.
7. V_{IH} (min) and V_{IL} (max) are reference levels for measuring timing of input signals. Also, transition times are measured between V_{IH} (min) and V_{IL} (max).
8. Assumes that $t_{RCD} < t_{RCD}(\text{max})$ and $t_{RAD} < t_{RAD}(\text{max})$. If t_{RCD} or t_{RAD} is greater than the maximum recommended value shown in this table, t_{RAC} exceeds the value shown.
9. Measured with a load circuit equivalent to 1TTL loads and 100 pF.
10. Assumes that $t_{RCD} \geq t_{RCD}(\text{max}) + t_{AA}(\text{max}) - t_{CAC}(\text{max})$ and $t_{RAD} \leq t_{RAD}(\text{max})$.

HB56U264EJ Series

11. Assumes that $t_{\text{RCD}} \leq t_{\text{RCD}}(\text{max})$ and $t_{\text{RAD}} \geq t_{\text{RAD}}(\text{max})$.
12. Either t_{RCH} or t_{RRH} must be satisfied for a read cycles.
13. $t_{\text{OFF}}(\text{max})$ and $t_{\text{OEZ}}(\text{max})$ is define the time at which the outputs achieve the open circuit condition and are not referred to output voltage levels.
14. t_{WCS} , t_{RWD} , t_{CWD} , t_{AWD} and t_{CPW} are not restrictive operating parameters. They are included in the data sheet as electrical characteristics only; if $t_{\text{WCS}} \geq t_{\text{WCS}}(\text{min})$, the cycle is an early write cycle and the data out pin will remain open circuit (high impedance) throughout the entire cycle; if $t_{\text{RWD}} \geq t_{\text{RWD}}(\text{min})$, $t_{\text{CWD}} \geq t_{\text{CWD}}(\text{min})$, and $t_{\text{AWD}} \geq t_{\text{AWD}}(\text{min})$, or $t_{\text{CWD}} \geq t_{\text{CWD}}(\text{min})$, $t_{\text{AWD}} \geq t_{\text{AWD}}(\text{min})$ and $t_{\text{CPW}} \geq t_{\text{CPW}}(\text{min})$, the cycle is a read-modify-write and the data output will contain data read from the selected cell; if neither of the above sets of conditions is satisfied, the condition of the data out (at access time) is indeterminate.
15. These parameters are referred to $\overline{\text{CAS}}$ leading edge in early write cycle and to $\overline{\text{WE}}$ leading edge in delayed write or read-modify-write cycles.
16. t_{RASP} defines $\overline{\text{RAS}}$ pulse width in EDO page mode cycles.
17. Access time is determined by the longest among t_{AA} , t_{CAC} or t_{CPA} .
18. In delayed write or read-modify-write cycles, $\overline{\text{OE}}$ must disable output buffer prior to applying data to the device. After $\overline{\text{RAS}}$ is reset, if $t_{\text{OEH}} \geq t_{\text{CWL}}$, the DQ pins will remain open circuit (high impedance); if $t_{\text{OEH}} \leq t_{\text{CWL}}$, invalid data will be out at each DQ.
19. All the V_{CC} and V_{SS} pins shall be supplied with the same voltages.
20. $t_{\text{HPC}}(\text{min})$ can be achieved during a series of EDO page mode write cycles or EDO page mode read cycles. If both write and read operation are mixed in a EDO page mode $\overline{\text{RAS}}$ cycle (EDO page mode mix cycle (1), (2)), minimum value of $\overline{\text{CAS}}$ cycle ($t_{\text{CAS}} + t_{\text{CP}} + 2t_{\text{T}}$) becomes greater than the specified $t_{\text{HPC}}(\text{min})$ value. The value of $\overline{\text{CAS}}$ cycle time of mixed EDO page mode is shown in EDO page mode mix cycle (1) and (2).
21. When output buffers are enabled once, sustain the low impedance state until valid data is obtained. When output buffer is turned on and off within a very short time, generally it causes large $V_{\text{CC}}/V_{\text{SS}}$ line noise, which causes to degrade $V_{\text{IH}}(\text{min})/V_{\text{IL}}(\text{max})$ level.

Timing Waveforms

Refer to the HM5117805B Series data sheet.

HB56U264EJ Series

Physical Outline

Unit: mm/inch

