

714-4878 to 714-4829

Industrial Chucks and Accessories


Keyed Chucks

Plain Bearing Chucks

The Jacobs Plain Bearing Chuck is the world's most widely used for medium or heavy duty portable, bench or floor mounted power tools. This industrial quality chuck with fully hardened and ground working components, offers exceptionally high accuracy, gripping power and durability.

Features:

- Jaws centre-ground for absolute straightness and alignment.
- Through-hardened sleeve teeth, hardened nose and keyholes ensure outstanding wear resistance.
- One piece sleeve eliminates crack between driving teeth often found in other designs.
- Each chuck 100% inspected for performance and precision.



Model No.	Capacity Range mm	Mount	Special Feature	Key No.	Part No.	List Price Ea. £	Closed Length mm	Open Length mm	Sleeve Dia. mm	Weight Each gm
0	0.711 - 4	0JT		K0	6200	36.30	37	28	21.6	60
0B 5/16	0.711 - 4	5/16-24		K0	6204	36.30	39	30	22.0	60
1A ✓	0.711 - 6.5	1JT		K1	6206	21.50	49	39	28.4	140
1B 3/8	0.711 - 6.5	3/8-24		K1	6208	21.50	50	40	28.0	140
7BA 3/8 ✓	0.711 - 6.5	3/8-24	REV	K7	6255	23.00	57	44	34.0	200
2A	0.711 - 10.	2JT		K2	6214	27.30	71	55	42.4	370
2BA 3/8	0.711 - 10.	3/8-24	REV	K2	6219	27.30	71	55	42.0	370
31-01	0.711 - 10.	1JT		K30	14697	24.30	63	51	36.1	230
31-02	0.711 - 10.	2JT		K30	14698	24.30	63	51	36.1	230
41BA 1/2	0.711 - 10	1/2-20	REV	K30	31090	24.30	63	51	36.3	230
41BA 3/8-S	0.711 - 10	3/8-24	REV	K30	31138	24.30	63	51	36.3	230
41BA 3/8-F	0.711 - 10	3/8-24	REV	K30	30728	24.30	63	51	36.3	230
32BA 1/2	0.711 - 10	1/2-20	REV	K32	8859	28.00	77	59	45.0	400
34-02	0.711 - 13.	2JT		K3	14442	33.00	89	70	51.8	650
34-06	0.711 - 13.	6JT		K3	6295	33.00	89	70	51.8	650
34-33	0.711 - 13.	33JT		K3	14445	33.00	89	70	51.8	650
34-33C	0.711 - 13	33JT	LOK	K3	14451	33.00	94	75	50.8	740
33	2 - 13	33JT		K32	6279	29.50	82	64	45.5	450
3326A	2 - 13	0.6250	POS	K32	6291	38.70	90	72	45.5	510
33KD	2 - 13	33JT	POS	K32	6281	33.90	88	70	46.0	480
33BA 1/2	2 - 13.	1/2-20	REV	K32	6287	29.50	78	62	45.0	480
33BA 3/8	2 - 13	3/8-24	REV	K32	6283	29.50	78	62	45.0	480
33BA 3/8	2 - 13	3/8-16	REV	K32	6289	29.50	78	62	45.0	480
3A	3 - 16	3JT		K3	6223	39.50	97	73	58.4	900
3B 3/8	3 - 16	3/8-16		K3	6232	39.50	97	73	58.0	900
3KD	3 - 16	3JT	POS	K3	6228	55.60	103	79	58.2	940
3PD	3 - 16	3JT	PIN	K3	6230	65.10	103	79	58.2	940
35B 1/2	4 - 16	1/2-20		K3	14723	33.80	89	70	52.0	710
36	5 - 20.3	3JT		K4	6309	54.80	103	80	64.5	1280
36B 3/4	5 - 20.3	3/4-16		K4	6316	54.80	105	81	65.0	1300
36B 3/8	5 - 20.3	3/8-16		K4	6314	54.80	105	81	65.0	1300
36KD	5 - 20.3	3JT	POS	K4	14865	54.80	108	87	64.5	1250
36PD	5 - 20.3	3JT	PIN	K4	14866	54.80	108	87	64.5	1280

Special Features:

- REV** – Drilled and Countersunk for retaining screw, suitable for reversible tools
POS – Equipped with a positive drive slot
PIN – Equipped with a pin-type positive drive
LOK – Equipped with a locking collar

NOTE: 31BA Chuck Series has been replaced by 41BA Chuck Series.
 33BA Chuck Series are Hammer Capable

Jacobs®