

## IGBT MODULE ( Single-in-Line )


## ■ Outline Drawing

### ■ Features

- Square RBSOA
- Low Saturation Voltage
- Improved FWD Characteristic
- Minimized Internal Stray Inductance

### ■ Applications

- High Power Switching
- A.C. Motor Controls
- D.C. Motor Controls




## ■ Maximum Ratings and Characteristics

### • Absolute Maximum Ratings ( $T_c=25^\circ\text{C}$ )

Items	Symbols	Ratings	Units
Collector-Emitter Voltage	$V_{CES}$	600	V
Gate -Emitter Voltage	$V_{GES}$	$\pm 20$	V
Collector Current	Continuous	$I_C$	20
	1ms	$I_C \text{ PULSE}$	40
	Continuous	$-I_C$	20
	1ms	$-I_C \text{ PULSE}$	40
Max. Power Dissipation	$P_C$	70	W
Operating Temperature	$T_j$	+150	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-40 ~ +125	$^\circ\text{C}$
Isolation Voltage	A.C. 1min. $V_{is}$	2000	V
Screw Torque	Mounting *1	1.7	Nm

Note: \*1:Recommendable Value; 1.3 ~ 1.7 Nm (M4)

## ■ Equivalent Circuit




### • Electrical Characteristics ( at $T_j=25^\circ\text{C}$ )

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Zero Gate Voltage Collector Current	$I_{CES}$	$V_{GE}=0V$ $V_{CE}=600V$			1.0	mA
Gate-Emitter Leakage Current	$I_{GES}$	$V_{CE}=0V$ $V_{GE}=\pm 20V$			100	nA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=20V$ $I_C=10mA$	5.5		8.5	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V$ $I_C=10A$			2.8	V
Input capacitance	$C_{ies}$	$V_{GE}=0V$		1300		pF
Output capacitance	$C_{oes}$	$V_{CE}=10V$		300		
Reverse Transfer capacitance	$C_{res}$	$f=1MHz$		72		
Turn-on Time	$t_{ON}$	$V_{CC}=300V$			1.2	$\mu\text{s}$
	$t_r$	$I_C=20A$			1.0	
Turn-off Time	$t_{OFF}$	$V_{GE}=\pm 15V$			1.0	
	$t_f$	$R_G=120\Omega$			0.35	
Diode Forward On-Voltage	$V_F$	$I_F=20A$ $V_{GE}=0V$			3.0	V
Reverse Recovery Time	$t_{rr}$	$I_F=20A$			300	ns


### • Thermal Characteristics

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	$R_{th(j-c)}$	IGBT			1.79	$^\circ\text{C/W}$
	$R_{th(j-e)}$	Diode			2.50	
	$R_{th(c-f)}$	With Thermal Compound		0.06		


Collector-Emitter voltage vs. Collector current  
T<sub>j</sub>=25°C






Collector-Emitter voltage vs. Collector current  
T<sub>j</sub>=125°C













Collector-Emitter vs. Gate-Emitter voltage  
T<sub>j</sub>=25°C



Collector-Emitter vs. Gate-Emitter voltage  
T<sub>j</sub>=125°C







**Fuji Electric GmbH**

Lyoner Straße 26

D-60528 Frankfurt/M

Tel.: 069 - 66 90 29 - 0

Fax.: 069 - 66 90 29 - 56

**Fuji Electric (UK) Ltd.**

Commonwealth House  
2 Chalkhill Road Hammersmith

London W6 8DW, UK

Tel.: 0181 - 233 11 30

Fax.: 0181 - 233 11 60