

FEATURES

- -55°C to +125°C operation
- 12 to 50 VDC input
- Fully isolated
- Magnetic feedback
- Fixed frequency 370 kHz typ.
- Topology – Current Mode Flyback
- 80 V for up to 120 ms transient protection
(70 V for 15 V single and dual models)
- Inhibit function
- Short circuit protection
- Undervoltage lockout

DC/DC CONVERTERS

28 VOLT INPUT



MCH SERIES 1.5 WATT

MODELS

VDC OUTPUT

SINGLES	DUALS
5	±5
5.2	±12
12	±15
15	

Size (max.): 0.980 x 0.805 x 0.270 inches (24.89 x 20.45 x 6.86 mm)

Weight: 12 grams max.

Screening: Standard, ES, or 883 (Class H)

DESCRIPTION

With a miniature footprint of just 0.8 square inches, the MCH Series™ of DC/DC converters delivers 1.5 watts of output power while saving significant board real estate. The wide input voltage range of 12 to 50 VDC accepts the varying voltages of military, aerospace, or space bus power and tightly regulates output voltages to protect downstream components. Transient protection of 80 volts for up to 120 milliseconds exceeds the requirements of MIL-STD-704A for the 5, 5.2, and 12 volt single models and the 12 volt dual model. The 15 volt single and dual converters will withstand transients of up to 70 volts for up to 120 milliseconds.

CONVERTER DESIGN

MCH Series DC/DC converters incorporate a continuous flyback topology with a constant switching frequency of approximately 370 kHz. Current-mode pulse width modulation (PWM) provides output voltage regulation. Output error voltage is magnetically fed back to the input side of the PWM to regulate output voltage. Regulation is also affected by the load; refer to the Electrical Characteristics tables on the following pages.

Dual models regulate the negative output with magnetic coupling to the positive output. Up to 80% of the total load may be on one output providing that the other output carries a minimum of 20% of the total load. The dual models can be used at double the output voltage by connecting the load between positive and negative outputs, leaving the common unconnected. (ex: MCH2805D can be used as a 10 VDC output.)

INHIBIT FUNCTION

When an open collector TTL logic low is applied to the inhibit terminal, pin 7, the converter shuts down and lowers the output voltage to near zero and input current to as low as 2.3 mA. Leaving the terminal open or applying an open collector TTL logic high will enable the converter.

PROTECTION FEATURES

Undervoltage lockout prevents the MCH Series converters from operating below approximately 8 VDC input voltage to keep system current levels smooth, especially during initialization or re-start operations. All models include a soft-start function to prevent large current draw and minimize overshoot. The converters also provide short circuit protection by restricting the current.

MIL-STD-461

Use Interpoint's FMSA-461 EMI filter to pass the CE03 requirements of MIL-STD-461C.

CONVENIENT PACKAGING

The MCH Series converters are packaged in hermetically sealed, projection-welded metal cases which provide EMI/RFI shielding.




FIGURE 1: BLOCK DIAGRAM

MCH SERIES 1.5 WATT

DC/DC CONVERTERS

ABSOLUTE MAXIMUM RATINGS										TYPICAL CHARACTERISTICS					
Input Voltage										Output Voltage Temperature Coefficient					
• 12 to 50 VDC										• 100 ppm/ $^{\circ}$ C typical					
Output Power										Input to Output Capacitance					
• 1.5 W										• 100 to 170 pF typical					
Capacitive Load										Undervoltage Lockout					
• Single output models 200 μ F										• 8 V input typical					
Lead Soldering Temperature (10 sec per lead)										Current Limit					
• 300°C										• 125% of full load typical					
Storage Temperature Range (Case)										Isolation					
• -65° C to $+150^{\circ}$ C										• 100 megohm minimum at 500 V					
Inhibit – TTL Open Collector										Audio Rejection 40 dB, typical					
• Logic low (output disabled) 0.8 V max										Conversion Frequency (kHz)					
Inhibit pin current 1 mA max										• 25° C, 300 min, 370 typ, 450 max					
• Referenced to input common										• -55° C to $+125^{\circ}$ C					
• Logic high (output enabled) open collector										270 min, 370 typ, 470 max					
RECOMMENDED OPERATING CONDITIONS										Inhibit Pin Voltage (unit enabled)					
Input Voltage Range										• 7 to 12 V					
• 12 to 50 VDC continuous															
• 80 V for 120 msec transient															
(70 V for 15 V single and dual models)															
Case Operating Temperature (Tc)															
• -55° C to $+125^{\circ}$ C full power															
• -55° C to $+135^{\circ}$ C absolute															
Derating Output Power/Current (Tc)										• Linearity from 100% at 125° C to 0% at 135° C					

Electrical Characteristics: 25° C Tc, 28 VDC Vin, 100% load, unless otherwise specified.

SINGLE OUTPUT MODELS		MCH2805S			MCH285R2S			MCH2812S			MCH2815S			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT VOLTAGE ¹	Tc = 25° C	4.95	5	5.05	5.15	5.2	5.25	11.88	12	12.12	14.85	15	15.15	VDC
	Tc = -55° C TO $+125^{\circ}$ C	4.80	5	5.20	5.00	5.2	5.40	11.52	12	12.48	14.40	15	15.60	
OUTPUT CURRENT	V _{IN} = 12 to 50 VDC	—	300	0	—	288	0	—	125	0	—	100	mA	
OUTPUT POWER	V _{IN} = 12 TO 50 VDC	0	—	1.5	0	—	1.5	0	—	1.5	0	—	1.5	W
OUTPUT RIPPLE VOLTAGE	10 kHz - 2 MHz	—	45	150	—	45	150	—	50	200	—	35	150	mV p-p
LINE REGULATION	Tc = -55° C TO $+125^{\circ}$ C	—	65	300	—	65	300	—	70	300	—	50	250	
LOAD REGULATION	V _{IN} = 12 TO 50 VDC	—	35	100	—	35	100	—	60	200	—	70	300	mV
	Tc = -55° C TO $+125^{\circ}$ C	—	40	120	—	40	120	—	70	250	—	80	350	
INPUT VOLTAGE NO LOAD TO FULL	CONTINUOUS	12	28	50	12	28	50	12	28	50	12	28	50	VDC
	TRANSIENT 120 ms	0	—	80	0	—	80	0	—	80	0	—	70	V
INPUT CURRENT	NO LOAD	—	5.5	10	—	5.5	10	—	6.0	10	—	6.0	11	mA
	Tc = -55° C TO $+125^{\circ}$ C	—	6.0	11	—	6.0	11	—	6.5	12	—	6.5	12	
	FULL LOAD	—	70	74	—	70	74	—	68	72	—	68	72	
	Tc = -55° C TO $+125^{\circ}$ C	—	73	78	—	73	78	—	70	74	—	70	74	
INPUT RIPPLE CURRENT ²	INHIBITED	—	2.3	3.2	—	2.3	3.2	—	2.3	3.2	—	2.3	3.2	mA p-p
	Tc = -55° C TO $+125^{\circ}$ C	—	2.4	3.5	—	2.4	3.5	—	2.4	3.5	—	2.4	3.5	
	10k Hz - 10 MHz	—	100	200	—	100	200	—	100	200	—	100	200	
	Tc = -55° C TO $+125^{\circ}$ C	—	130	250	—	130	250	—	150	250	—	150	250	
EFFICIENCY	Tc = 25° C	72	77	—	72	77	—	74	79	—	74	79	—	%
	Tc = -55° C TO $+125^{\circ}$ C	69	75	—	69	75	—	72	77	—	72	77	—	
LOAD FAULT ^{3, 4}	POWER DISSIPATION	—	1.3	2.0	—	1.3	2.0	—	2.0	3.2	—	2.3	3.7	W
	Tc = -55° C TO $+125^{\circ}$ C	—	1.4	2.3	—	1.4	2.3	—	2.2	3.5	—	2.5	4.0	
	RECOVERY	—	3.0	12	—	3.0	12	—	3.5	15	—	4.0	18	ms
	Tc = -55° C TO $+125^{\circ}$ C	—	3.5	15	—	3.5	15	—	3.5	20	—	4.0	20	
STEP LOAD RESPONSE ⁵	50 %–100%–50% LOAD TRANSIENT	—400	185	400	—400	185	400	—700	350	700	—700	350	700	mV pk
	Tc = -55° C TO $+125^{\circ}$ C	—500	185	500	—500	185	500	—800	380	800	—800	380	800	
STEP LINE RESPONSE ⁵	12 TO 50 TO 12 V _{IN} TRANSIENT	—400	170	400	—400	170	400	—900	400	900	—750	400	750	mV pk
	Tc = -55° C TO $+125^{\circ}$ C	—500	180	500	—500	180	500	—1000	400	1000	—850	450	850	
	RECOVERY	—	0.75	3.0	—	0.75	3.0	—	0.6	2.5	—	0.47	2.0	ms
	Tc = -55° C TO $+125^{\circ}$ C	—	0.75	4.0	—	0.75	4.0	—	0.6	3.0	—	0.5	2.5	
START-UP 0 TO 28 VDC	DELAY	—	7	20	—	7	20	—	7	20	—	7	20	ms
	Tc = -55° C TO $+125^{\circ}$ C	—	10	40	—	10	40	—	10	40	—	10	40	
	OVERSHOOT	—	0	100	—	0	100	—	0	250	—	0	300	mV pk
	Tc = -55° C TO $+125^{\circ}$ C	—	0	150	—	0	150	—	0	350	—	0	450	

See notes 1, 2, 3, 4, 5, and 6 on the following page.

DC/DC CONVERTERS

MCH SERIES
1.5 WATT

Electrical Characteristics: 25°C Tc, 28 VDC Vin, 100% load, unless otherwise specified.



DUAL OUTPUT MODELS		MCH2805D			MCH2812D			MCH2815D			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT VOLTAGE ¹	Tc = 25°C	±4.95	±5	±5.05	±11.88	±12	±12.12	±14.85	±15	±15.15	VDC
	Tc = -55°C TO +125°C	±4.80	±5	±5.20	±11.52	±12	±12.48	±14.40	±15	±15.60	
OUTPUT CURRENT ⁶	V _{IN} = 12 TO 50 VDC	0	±150	240	0	±62.5	100	0	±50	80	mA
OUTPUT POWER	V _{IN} = 12 TO 50 VDC	0	—	1.5	0	—	1.5	0	—	1.5	W
OUTPUT RIPPLE VOLTAGE	10 kHz - 2 MHz	—	35	150	—	35	150	—	30	150	mV p-p
+V _{OUT}	Tc = -55°C TO +125°C	—	50	250	—	40	250	—	35	250	
-V _{OUT}	10 kHz - 2 MHz	—	35	150	—	35	150	—	30	150	
	Tc = -55°C TO +125°C	—	50	250	—	40	250	—	35	250	
LINE REGULATION ⁷	V _{IN} = 12 TO 50 VDC	—	10	50	—	100	300	—	165	500	mV
	Tc = -55°C TO +125°C	—	20	100	—	110	400	—	180	650	
LOAD REGULATION ⁸	10% TO FULL ±V _{OUT}	—	300	600	—	550	1100	—	600	1300	mV
	-55°C TO +125°C	—	350	700	—	570	1200	—	630	1400	
	50% TO FULL	—	80	200	—	115	250	—	125	300	
	-55°C TO +125°C	—	100	300	—	130	350	—	135	400	
INPUT VOLTAGE NO LOAD TO FULL	CONTINUOUS	12	28	50	12	28	50	12	28	50	VDC
	TRANSIENT 120 ms	0	—	80	0	—	80	0	—	70	V
INPUT CURRENT	NO LOAD	—	5.0	10	—	7.5	13	—	7.5	13	mA
	Tc = -55°C TO +125°C	—	6.0	12	—	8.0	14	—	8.0	14	
	FULL LOAD	—	69	73	—	70	73	—	71	74	
	Tc = -55°C TO +125°C	—	72	77	—	71	77	—	72	78	
	INHIBITED	—	2.3	3.2	—	2.3	3.2	—	2.3	3.2	
	Tc = -55°C TO +125°C	—	2.4	3.5	—	2.4	3.5	—	2.4	3.5	
INPUT RIPPLE ² CURRENT	10 kHz - 10 MHz	—	100	200	—	115	200	—	90	200	mA p-p
	Tc = -55°C TO +125°C	—	130	250	—	150	250	—	120	250	
EFFICIENCY	Tc = 25°C	73	77	—	73	77	—	72	76	—	%
	Tc = -55°C TO +125°C	70	75	—	70	75	—	69	74	—	
LOAD FAULT ^{3,4}	POWER DISSIPATION	—	1.4	2.2	—	2.5	3.8	—	2.7	4.1	W
	Tc = -55°C TO +125°C	—	1.6	2.5	—	2.7	4.2	—	3.0	4.5	
	RECOVERY	—	3.7	15	—	3.2	15	—	4.0	15	
	Tc = -55°C TO +125°C	—	3.8	20	—	3.2	20	—	4.0	20	ms
STEP LOAD RESPONSE ⁵ ± V _{OUT}	50 %–100%–50% LOAD TRANSIENT	-300	130	300	-600	250	600	-600	250	600	mV pk
	Tc = -55°C TO +125°C	-400	140	400	-700	260	700	-700	270	700	
	RECOVERY	—	100	400	—	165	700	—	50	200	μs
	-55°C TO +125°C	—	100	500	—	165	800	—	50	300	
STEP LINE RESPONSE ⁵ ± V _{OUT}	12 TO 50 TO 12 V _{IN} TRANSIENT	-250	125	250	-500	240	500	-500	220	500	mV pk
	Tc = -55°C TO +125°C	-300	130	300	-600	250	600	-600	230	600	
	RECOVERY	—	0.6	2.5	—	0.9	3.0	—	0.6	3.0	ms
	Tc = -55°C TO +125°C	—	0.6	3.0	—	0.9	4.0	—	0.7	4.0	
START-UP 0 TO 28 VDC, ± V _{OUT}	DELAY	—	8	25	—	8	25	—	8	25	ms
	Tc = -55°C TO +125°C	—	10	45	—	10	45	—	10	45	
	OVERSHOOT	—	0	100	—	0	250	—	0	750	mV pk
	Tc = -55°C TO +125°C	—	0	150	—	0	350	—	0	900	

Notes:

1. Specified at 50% load.
2. Lin = 2 μH.
3. Maximum duration of short circuit: 25°C— 90 seconds, 125°C – 30 seconds.
4. Load fault is a short circuit (<50 mohms). Recovery is into resistive full load.
5. Transition ≥ 10 μs. Recovery = time to settle to within 1% of Vout final value.
6. Max. spec indicates 80% of the converter's total power, available from either output.
7. Specification applies to both + and – Vout.
8. Although no minimum load is required, at no load the output voltage may increase up to 15%.

**MCH SERIES
1.5 WATT**

DC/DC CONVERTERS



SMD NUMBERS	
STANDARD MICROCIRCUIT DRAWING (SMD)	MCH SERIES SIMILAR PART
5962-9569601HXC IN PROCESS	MCH2805S/883
5962-9569701HXC	MCH285R2S/883
5962-9569801HXC	MCH2812S/883
5962-9570201HXC	MCH2815S/883
5962-9570301HXC	MCH2805D/883
5962-9570401HXC	MCH2812D/883
5962-9570401HXC	MCH2815D/883

For exact specifications for an SMD product, refer to the SMD drawing. Call your Interpoint representative for status on the MCH Series SMD releases which are "in process". SMDs can be downloaded from <http://www.dscccols.com/programs/smcr>

DC/DC CONVERTERS

MCH SERIES
1.5 WATT

TYPICAL PERFORMANCE CURVES: $T_c = 25^\circ\text{C}$, full load, $V_{in} = 28 \text{ VDC}$, unless otherwise specified.




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11

MCH SERIES 1.5 WATT

DC/DC CONVERTERS

TYPICAL PERFORMANCE CURVES: $T_c = 25^\circ\text{C}$, full load, $V_{in} = 28 \text{ VDC}$, unless otherwise specified.




FIGURE 12




FIGURE 13




FIGURE 14




FIGURE 15




FIGURE 16






FIGURE 17

DC/DC CONVERTERS

MCH SERIES
1.5 WATT



Note: Although every effort has been made to render the case drawings at actual size, variations in the printing process may cause some distortion. Please refer to the numerical dimensions for accuracy.

MCH SERIES
1.5 WATT

DC/DC CONVERTERS

ENVIRONMENTAL SCREENING

TEST	125°C STANDARD	125°C /ES	/883 (Class H)*
PRE-CAP INSPECTION Method 2017, 2032	yes	yes	yes
TEMPERATURE CYCLE (10 times) Method 1010, Cond. C, -65°C to 150°C Method 1010, Cond. B, -55°C to 125°C	no no	no yes	yes no
CONSTANT ACCELERATION Method 2001, 3000 g Method 2001, 500 g	no no	no yes	yes no
BURN-IN Method 1015, 160 hours at 125°C 96 hours at 125°C case (typical)	no no	no yes	yes no
FINAL ELECTRICAL TEST MIL-PRF-38534, Group A Subgroups 1 through 6: -55°C, +25°C, +125°C Subgroups 1 and 4: +25°C case	no yes	no yes	yes no
HERMETICITY TESTING Fine Leak, Method 1014, Cond. A Gross Leak, Method 1014, Cond. C Gross Leak, Dip (1×10^{-3})	no no yes	yes yes no	yes yes no
FINAL VISUAL INSPECTION Method 2009	yes	yes	yes

Test methods are referenced to MIL-STD-883 as determined by MIL-PRF-38534.

*883 products are built with element evaluated components and are 100% tested and guaranteed over

Contact Information:

www.interpoint.com

Interpoint Headquarters USA
Phone: 1-800-822-8782
+425-882-3100
Email: power@intp.com

Interpoint UK
Phone: +44-1252-872266
Email: poweruk@intp.com

Interpoint France
Phone: +33-134285455
Email: powerfr@intp.com