

G2U09N70


N-CHANNEL ENHANCEMENT MODE POWER MOSFET

BV_{DSS} 600/650/700V
RDS(ON) 0.75Ω
ID 9A**Description**

The G2U09N70 series are specially designed as main switching devices for universal 90~265VAC off-line AC/DC converter applications. TO-262 type provide high blocking voltage to overcome voltage surge and sag in the toughest power system with the best combination of fast switching, ruggedized design and cost-effectiveness. The TO-262 package is universally preferred for all commercial-industrial applications. The device is suited for switch mode power supplies, DC-AC converters and high current high speed switching circuits.

Features

- *Dynamic dv/dt Rating
- *Simple Drive Requirement
- *Repetitive Avalanche Rated
- *Fast Switching Speed

Package Dimensions**Absolute Maximum Ratings**

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage - /A/H	V _{DS}	600/650/700	V
Gate-Source Voltage	V _{GS}	±20	V
Continuous Drain Current , V _{GS} @10V	I _D @T _C =25°C	9	A
Continuous Drain Current , V _{GS} @10V	I _D @T _C =100°C	5	A
Pulsed Drain Current ¹	I _{DM}	40	A
Total Power Dissipation	P _D @T _C =25°C	156	W
Linear Derating Factor		1.25	W/°C
Single Pulse Avalanche Energy ²	E _{AS}	305	mJ
Avalanche Current	I _{AR}	9	A
Repetitive Avalanche Energy	E _{AR}	9	mJ
Operating Junction and Storage Temperature Range	T _j , T _{stg}	-55 ~ +150	°C

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-case Max.	R _{thj-c}	0.8	°C/W
Thermal Resistance Junction-ambient Max.	R _{thj-a}	62	°C/W

Electrical Characteristics($T_j = 25^\circ\text{C}$ Unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV_{DSS}	600	-	-	V	$\text{V}_{\text{GS}}=0, \text{I}_D=250\mu\text{A}$ -
		650	-	-	V	$\text{V}_{\text{GS}}=0, \text{I}_D=250\mu\text{A}$ A
		700	-	-	V	$\text{V}_{\text{GS}}=0, \text{I}_D=250\mu\text{A}$ H
Breakdown Voltage Temperature Coefficient	$\Delta \text{BV}_{\text{DSS}} / \Delta T_j$	-	0.6	-	V/ $^\circ\text{C}$	Reference to 25°C , $\text{I}_D=1\text{mA}$
Gate Threshold Voltage	$\text{V}_{\text{GS}(\text{th})}$	2.0	-	4.0	V	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250\mu\text{A}$
Forward Transconductance	g_{fs}	-	4.5	-	S	$\text{V}_{\text{DS}}=50\text{V}, \text{I}_D=4.5\text{A}$
Gate-Source Leakage Current	I_{GSS}	-	-	± 1	μA	$\text{V}_{\text{GS}}= \pm 20\text{V}$
Drain-Source Leakage Current($T_j=25^\circ\text{C}$)	I_{DSS}	-	-	100	μA	$\text{V}_{\text{DS}}=600\text{V}, \text{V}_{\text{GS}}=0$
Drain-Source Leakage Current($T_j=150^\circ\text{C}$)		-	-	500	μA	$\text{V}_{\text{DS}}=480\text{V}, \text{V}_{\text{GS}}=0$
Static Drain-Source On-Resistance	$\text{R}_{\text{DS}(\text{ON})}$	-	-	0.75	Ω	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=4.5\text{A}$
Total Gate Charge ³	Q_g	-	44	-	nC	$\text{I}_D=9\text{A}$ $\text{V}_{\text{DS}}=480\text{V}$ $\text{V}_{\text{GS}}=10\text{V}$
Gate-Source Charge	Q_{gs}	-	11	-		
Gate-Drain ("Miller") Change	Q_{gd}	-	12	-		
Turn-on Delay Time ³	$\text{T}_{\text{d}(\text{on})}$	-	19	-	ns	$\text{V}_{\text{DD}}=300\text{V}$ $\text{I}_D=9\text{A}$ $\text{V}_{\text{GS}}=10\text{V}$ $\text{R}_G=10\Omega$ $\text{R}_D=34\Omega$
Rise Time	T_r	-	21	-		
Turn-off Delay Time	$\text{T}_{\text{d}(\text{off})}$	-	56	-		
Fall Time	T_f	-	24	-		
Input Capacitance	C_{iss}	-	2660	-	pF	$\text{V}_{\text{GS}}=0\text{V}$ $\text{V}_{\text{DS}}=25\text{V}$ $f=1.0\text{MHz}$
Output Capacitance	C_{oss}	-	170	-		
Reverse Transfer Capacitance	C_{rss}	-	10	-		







Source-Drain Diode

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage ³	V_{SD}	-	-	1.5	V	$\text{I}_S=9\text{A}, \text{V}_{\text{GS}}=0\text{V}, \text{T}_j=25^\circ\text{C}$
Continuous Source Current (Body Diode)	I_S	-	-	9	A	$\text{V}_{\text{D}}= \text{V}_{\text{G}}=0\text{V}, \text{V}_{\text{S}}=1.5\text{V}$
Pulsed Source Current (Body Diode) ¹	I_{SM}	-	-	40	A	

Notes: 1. Pulse width limited by safe operating area.

2. Staring $\text{T}_j=25^\circ\text{C}$, $\text{V}_{\text{DD}}=50\text{V}$, $\text{L}=6.8\text{mH}$, $\text{R}_G=25\Omega$, $\text{I}_{\text{AS}}=9\text{A}$.

3. Pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.

Characteristics Curve**Fig 1. Typical Output Characteristics****Fig 2. Typical Output Characteristics****Fig 3. Normalized BV_{DSS} v.s. Junction Temperature****Fig 4. Normalized On-Resistance v.s. Junction Temperature****Fig 5. Maximum Drain Current v.s. Case Temperature****Fig 6. Type Power Dissipation**




Fig 7. Maximum Safe Operating Area




Fig 8. Effective Transient Thermal Impedance




Fig 9. Gate Charge Characteristics




Fig 10. Typical Capacitance Characteristics




Fig 11. Forward Characteristics of Reverse Diode




Fig 12. Gate Threshold Voltage v.s. Junction Temperature




Fig 13. Switching Time Circuit




Fig 14. Switching Time Waveform




Fig 15. Gate Charge Circuit




Fig 16. Gate Charge Waveform

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165