






unimec 16300/16700/16800





Technical Data:

- 250mA/120V/9W AC/6W DC
- 2 pole
- momentary or alternate
- 8 contact functions
- temperature range:
low temp: -40/+75°C
high temp: -40/+160°C
- through-hole only



Dimensions 16300:





PCB layout






Dimensions 16700:



PCB layout



Dimensions 16800:



Blanking Cap
to be used with
VARIO SUPPORT

HOW TO ORDER

1 5

+

1 6 3 0 0



Switch

- 15501** mom. silver
- 15551** alt. silver
- 15502** mom. gold
- 15552** alt. gold
- 15500** silent silver
- 15401** mom. silver
high temp.
- 15451** alt. silver
high temp.

Cap



- 00** blue
- 01** brown
- 02** green
- 03** grey
- 04** yellow
- 05** golden
- 06** white
- 07** orange
- 08** red
- 09** black

1 5

+

1 6 7 0 0

Switch



Cap



- 00** blue
- 02** green
- 03** grey
- 04** yellow
- 06** white
- 08** red
- 09** black

1 6 8 0 0

Blanking Cap



- 00** blue
- 01** brown
- 02** green
- 03** grey
- 04** yellow
- 05** golden
- 06** white
- 07** orange
- 08** red
- 09** black
- 11** transparent
- 12** transparent green
- 14** transparent yellow
- 18** transparent red

Ordering example: 15551 + 1670009