

2SD 1322

Silicon NPN Triple-Diffused Planar Darlington Type

Medium Speed Power Switching

■ Features

- 30V Zener diode built-in between C and B
- Very small fluctuation in breakdown voltages
- Large energy handling capability
- High speed switching
- “Full Pack” package for simplified mounting on a heat sink with one screw

■ Absolute Maximum Ratings (Tc=25°C)

Item	Symbol	Value	Unit
Collector-base voltage	V_{CBO}	30 ± 5	V
Collector-emitter voltage	V_{CEO}	30 ± 5	V
Emitter-base voltage	V_{EB0}	5	V
Peak collector current	I_{CP}	4	A
Collector current	I_C	2	A
Collector power dissipation	P_C	35	W
		2	
Junction temperature	T_j	150	°C
Storage temperature	T_{stk}	$-55 \sim +150$	°C


■ Electrical Characteristics (Tc=25°C)

Item	Symbol	Condition	min	typ	max	Unit
Collector cutoff current	I_{CBO}	$V_{CE} = 25 \text{ V}, I_E = 0$			100	μA
Emitter cutoff current	I_{EBO}	$V_{EB} = 5 \text{ V}, I_C = 0$			2	mA
Collector-emitter voltage	V_{CE0}	$I_C = 5 \text{ mA}, I_B = 0$	25		35	V
DC current gain	h_{FE1}	$V_{CE} = 4 \text{ V}, I_C = 1 \text{ A}$	1000			
	h_{FE2}^{*1}	$V_{CE} = 4 \text{ V}, I_C = 2 \text{ A}$	1000		10000	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 2 \text{ A}, I_B = 8 \text{ mA}$			2.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = 2 \text{ A}, I_B = 8 \text{ mA}$			2.5	V
Transition frequency	f_T	$V_{CE} = 10 \text{ V}, I_C = 0.5 \text{ A}, f = 1 \text{ MHz}$		20		MHz
Turn-on time	t_{on}	$I_C = 2 \text{ A}, I_{B1} = 8 \text{ mA}, I_{B2} = -8 \text{ mA}$ $V_{CC} = 20 \text{ V}$		0.4		μs
Storage time	t_{stg}			3		μs
Fall time	t_f			1		μs
Energy handling capability	E_{ch}^{*2}	$I_C = 1.45 \text{ A}, L = 100 \text{ mH}, R_{B1} = 100 \Omega$	100			mJ


*¹h_{FE2} Classifications

Class	R	Q	P
high	1000~2500	2000~5000	4000~10000


■ Package Dimensions









- Inner Circuit




* $^2F_{1,1}$ Test method



$P_C - T_a$  $I_C - V_{CE}$  $V_{CE(sat)} - I_C$  $V_{BE(sat)} - I_C$  $h_{FE} - I_C$  $I_C - L_{coil}$ 

Area of safe operation (ASO)

 $R_{th}(t) - t$ 