

Trim Trio Interconnection System


Metalok Bantam Connectors

Description

Metalok Bantam circular plastic connectors are a range of multiway connectors available in 8 shell sizes and 10 insert arrangements.

Features and benefits

- Connectors and accessories moulded from a highly durable glass-filled thermoplastic
- UL94V-O rated
- Metal Bayonet couplings assure 500 matings and unmatings
- Five keys and keyways assure correct mating between plug and receptacle
- Available in 3-4-7-8-12-19-23-28-35 and 48 contact positions including 2 VDE versions.



Performance characteristics

Operating temperature : - 55°C to + 125°C

Insulation resistance : 5000 MΩ min

Test potential: 2000 VAC

Durability : 500 cycles

Vibration Per MIL-STD 202
resistance : method 204

Shock : Per MIL-STD 202
method 207

Construction

Insulating materials:
Glass-filled thermoplast

Coupling ring:
Brass nickelplated as standard

Coupling spring: Spring steel
Tri-Lock pins: Stainless steel

Contact accommodation

Metalok Bantam connectors accept TRIM TRIO crimp-type removable snap-lock contacts

1. N° 16 machined contacts Type RM/RC for wire sizes from 0,05 to 1,50 mm²
2. Type RMDX/RCDX contacts for sub-miniature coaxial and twisted pair wires.
3. N° 16 strip feed contacts Type SMM/SCM for wire sizes from 0,05 to 1,50 mm²

Contacts to be ordered separately

How to order

UTG 0 14 12 P H 02
UTG 6 14 12 S N H 03

No letter : Molded in contact marking (standard version).
02 : White silkscreen contact marking.
03 : Yellow silkscreen contact marking.

No letter : Standard version.
H : Water protected version.

No letter : Tin plated aluminium bayonet coupling.
N : CuZn nickelplated (standard version). bayonet coupling.

P : PIN contacts.
S : Socket contacts.


Insert arrangement.

Shell size.

0 : Wall mounting receptacle.
6 : Straight plug.

Metalok Bantam


Insert arrangements



*Spacing according VDE 0110

Contact identification positions shown for mating face of plug and wiring face of receptacle.


Mating dimensions



No of contacts	Size	Dimensions in mm								
		A max.	B max.	C max.	D max.	E max.	F max.	G $\pm 0,2$	H max.	J max.
4	10-4	57	72	31,8	57,5	72,5	24,3	11,4	106	136
8	12-8	57	74	31,8	57,5	74,0	24,3	11,4	106	139
12	14-12	63	81	31,8	63,5	81	24,3	11,4	118	153
19	16-19	63	85	31,8	63,5	85	24,3	11,4	118	161
23	18-23	67	88	31,8	67,5	89	24,3	11,4	126	168
28	20-28	74	101	31,8	76	103	26	14,6	140	191
35	22-35	79	117	31,8	82	110	26	14,6	151	207
48	24-48	84	123	31,8	88	127	26	15,4	162	238
3	10-3 VDE	57	72	31,8	57,5	72,5	24,3	11,4	106	136
7	18-7 VDE U	73,5	94	33	74	89	34	17,8	132,5	168

Plug connector for pin contacts

UTG6-PN




Catalogue number	Dimensions in mm				
	A	B max.	C $\pm 0,15$	D $\pm 0,15$	E $\pm 0,2$
UTG610-4PN*	21,6	31,8	10,9	12,2	19,1
UTG612-8PN*	24,8	31,8	13,8	15,1	19,1
UTG614-12PN*	28,0	31,8	17	18,3	19,1
UTG616-19PN*	31,2	31,8	19,9	21,4	19,1
UTG618-23PN*	34,3	31,8	22,4	24	19,1
UTG620-28PN*	37,5	31,8	25,6	27,1	19,1
UTG622-35PN*	40,7	31,8	26,5	30,4	19,1
UTG624-48PN*	43,9	31,8	31,7	33,5	19,1
UTG610-3PNVDE	21,5	31,8	10,9	12,2	19,1
UTG618-7PNVDEU	34,3	29	22,5	24	19,1

*Standard item.

Plug connector for socket contacts


UTG6-SN



Catalogue number	Dimensions in mm				
	A	B max.	C $\pm 0,15$	D $\pm 0,15$	E $\pm 0,2$
UTG610-4SN	21,6	23,7	10,8	12,2	19,1
UTG612-8SN	24,8	23,7	13,8	15,1	19,1
UTG614-12SN	28,0	23,7	17	18,3	19,1
UTG616-19SN	31,2	23,7	19,9	21,4	19,1
UTG618-23SN	34,3	23,7	22,4	24	19,1
UTG620-28SN	37,5	24,9	25,6	27,1	19,1
UTG622-35SN	40,7	24,9	28,5	30,4	19,1
UTG624-48SN	43,9	26,2	31,7	33,5	19,1
UTG610-3SNVDE	21,6	23,7	10,8	12,2	19,1
UTG618-7SNVDEU	34,3	29,0	22,5	24	19,1

Receptacle for pin contacts


UTG0-P



Catalogue number	Dimensions in mm								
	A max.	B ± 0,15	C ± 0,2	D ± 0,15	E ± 0,15	F ± 0,25	G ± 0,1	H** ± 0,1	J** ± 0,1
UTG010-4P	31,7	2,3	11,3	15	18,2	23,1	3,2	17,3	15,1
UTG012-8P	31,7	2,3	11,3	19	20,5	26,2	3,2	21,8	18,2
UTG014-12P	31,7	2,3	11,3	22,2	22,9	28,5	3,2	25	21,4
UTG016-19P	31,7	2,3	11,3	25,3	24,5	30,8	3,2	28,1	24,6
UTG018-23P	31,7	2,5	11,3	28,5	26,9	33,1	3,2	31,3	27,8
UTG020-28P	33,3	2,5	14,4	31,7	29,2	36,3	3,2	34,5	30,9
UTG022-35P	33,3	3,5	14,4	34,9	31,6	39,3	3,2	37,7	34,1
UTG024-48P	33,3	3,5	15,1	38,0	34,7	42,6	3,9	40,9	37,3
UTG010-3PVDE	31,7	2,3	11,3	15	18,2	23,1	3,2	17,3	15,1
UTG018-7PVDEU	34,0	2,5	17,8	28,5	27,0	33,3	3,1	31,3	27,8

Receptacle for socket contacts

UTG0-S



Catalogue number	Dimensions in mm								
	A max.	B ± 0,15	C ± 0,2	D ± 0,15	E ± 0,15	F ± 0,25	G ± 0,1	H** ± 0,1	J** ± 0,1
UTG010-4S*	24,3	2,3	11,3	15	18,2	23,8	3,2	17,3	15,1
UTG012-8S*	24,3	2,3	11,3	19	20,5	26,2	3,2	21,8	18,2
UTG014-12S*	24,3	2,3	11,3	22,2	22,9	28,5	3,2	25	21,4
UTG016-19S*	24,3	2,3	11,3	25,3	24,5	30,8	3,2	28,1	24,6
UTG018-23S*	24,3	2,5	11,3	28,5	26,9	33,1	3,2	31,3	27,8
UTG020-28S*	27,0	2,5	14,5	31,7	29,2	36,3	3,2	34,5	30,9
UTG022-35S*	28,0	3,5	14,5	34,9	31,6	39,3	3,2	37,7	34,1
UTG024-48S*	30,4	3,5	15,2	38,0	34,7	42,6	3,9	40,9	37,3
UTG010-3SVDE	24,3	2,3	11,3	15	18,2	23,8	3,2	17,3	15,1
UTG018-7SVDEU	30,4	2,5	17,8	28,5	27,0	33,3	3,1	31,3	27,8


* Standard item.

** H : Dimensions for rear panel mounting. J : Dimensions for front panel mounting.

Accessories

Cable clamp

UTG-AC




Catalogue number	Dimensions in mm				
	A	B	C	D	E
UTG10AC*	39,9	21,5	6,4	8,7	21
UTG12AC*	30	24,9	6,4	12,8	24
UTG14AC*	46	27	6,4	12,8	27
UTG16AC*	46	30,1	6,4	17	30,2
UTG18AC*	50	32	7	19	33,2
UTG20AC*	55	34,3	7	21	36,4
UTG22AC*	60	37,1	8,2	23	39,6
UTG24AC*	65	41,8	8,2	27	42,8

*Standard item.

Cable clamp

UTG-PG




Catalogue number	Dimensions in mm		
	A	B	C
UTG10PG*	55	11	20,9
UTG12PG*	58	13,5	24
UTG14PG*	65	14,5	27
UTG16PG*	69	16,5	30,1
UTG18PG*	73	16,5	33,3
UTG20PG*	83	22	36,5
UTG22PG*	90	22	39,6
UTG24PG*	105	29,5	42,8

*Standard item.

Accessories

Environmental dust caps


UTG-DC



Catalogue number	Dust cap dimensions in mm		
	ϕA	B	C
UTG10DC	20,8	11,1	17
UTG12DC	24,9	11,1	17
UTG14DC	28,1	11,1	17
UTG16DC	31,3	11,1	17
UTG18DC	34,4	11,1	17
UTG20DC	37,6	11,1	17
UTG22DC	40,8	11,1	17
UTG24DC	43,9	11,1	17

Shrink boot adaptor

UTG-AD



Catalogue number	Shrink boot adaptor dimensions in mm	
	ϕA	B
UTG10AD	21,0	19,2
UTG12AD	24,0	19,2
UTG14AD	27,0	19,2
UTG16AD	30,2	21,5
UTG18AD	33,3	21,5
UTG20AD	36,5	22,8
UTG22AD	39,7	22,8
UTG24AD	42,9	21,9