




# STB60N55F3, STD60N55F3, STF60N55F3 STI60N55F3, STP60N55F3, STU60N55F3

N-channel 55 V, 6.5 mΩ, 80 A, DPAK, IPAK, D<sup>2</sup>PAK, I<sup>2</sup>PAK, TO-220  
TO-220FP STripFET™ III Power MOSFET

## Features

| Type       | V <sub>DSS</sub> | R <sub>DS(on)</sub> | I <sub>D</sub> | P <sub>w</sub> |
|------------|------------------|---------------------|----------------|----------------|
| STB60N55F3 | 55V              | <8.5mΩ              | 80A            | 110W           |
| STD60N55F3 | 55V              | <8.5mΩ              | 80A            | 110W           |
| STF60N55F3 | 55V              | <8.5mΩ              | 42A            | 30W            |
| STI60N55F3 | 55V              | <8.5mΩ              | 80A            | 110W           |
| STP60N55F3 | 55V              | <8.5mΩ              | 80A            | 110W           |
| STU60N55F3 | 55V              | <8.5mΩ              | 80A            | 110W           |

- Standard threshold drive
- 100% avalanche tested



## Application

- Switching applications

## Description

This STripFET™ III Power MOSFET technology is among the latest improvements, which have been especially tailored to minimize on-state resistance providing superior switching performances.

Figure 1. Internal schematic diagram




Table 1. Device summary

| Order codes | Marking | Package            | Packaging     |
|-------------|---------|--------------------|---------------|
| STB60N55F3  | 60N55F3 | D <sup>2</sup> PAK | Tape and reel |
| STD60N55F3  | 60N55F3 | DPAK               | Tape and reel |
| STF60N55F3  | 60N55F3 | TO-220FP           | Tube          |
| STI60N55F3  | 60N55F3 | I <sup>2</sup> PAK | Tube          |
| STP60N55F3  | 60N55F3 | TO-220             | Tube          |
| STU60N55F3  | 60N55F3 | IPAK               | Tube          |

---

# Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Electrical ratings</b> .....               | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics</b> .....       | <b>4</b>  |
|          | 2.1 Electrical characteristics (curves) ..... | 6         |
| <b>3</b> | <b>Test circuits</b> .....                    | <b>9</b>  |
| <b>4</b> | <b>Package mechanical data</b> .....          | <b>10</b> |
| <b>5</b> | <b>Packaging mechanical data</b> .....        | <b>17</b> |
| <b>6</b> | <b>Revision history</b> .....                 | <b>19</b> |

# 1 Electrical ratings

**Table 2. Absolute maximum ratings**

| Symbol                             | Parameter  | Value  |          | Unit |
|------------------------------------|--|--|----------|------|
|                                    |  | DPAK/D <sup>2</sup> PAK<br>TO-220<br>IPAK/I <sup>2</sup> PAK | TO-220FP |      |
| V <sub>DS</sub>                    | Drain-source voltage (V <sub>GS</sub> =0)  | 55   |          | V    |
| V <sub>GS</sub>                    | Gate-source voltage  | ± 20   |          | V    |
| I <sub>D</sub>                     | Drain current (continuous) at T <sub>C</sub> = 25°C  | 80   | 42       | A    |
| I <sub>D</sub>                     | Drain current (continuous) at T <sub>C</sub> = 100°C   | 56   | 30       | A    |
| I <sub>DM</sub> <sup>(1)</sup>     | Drain current (pulsed)   | 320  | 168      | A    |
| P <sub>TOT</sub>                   | Total dissipation at T <sub>C</sub> = 25°C   | 110  | 30       | W    |
|                                    | Derating factor  | 0.73   | 0.2      | W/°C |
| dv/dt <sup>(2)</sup>               | Peak diode recovery voltage slope  | 11   |          | V/ns |
| E <sub>AS</sub> <sup>(3)</sup>     | Single pulse avalanche energy  | 390  |          | mJ   |
| V <sub>ISO</sub>                   | Insulation withstand voltage (RMS) from all three leads to external heat sink (t=1s; T <sub>C</sub> =25°C) |  | 2500     | V    |
| T <sub>j</sub><br>T <sub>stg</sub> | Operating junction temperature<br>Storage temperature  | -55 to 175   |          | °C   |

1. Pulse width limited by safe operating area
2. I<sub>SD</sub> ≤ 80 A, di/dt ≤ 300A/μs, V<sub>DD</sub> ≤ V<sub>(BR)DSS</sub>. T<sub>j</sub> ≤ T<sub>jmax</sub>
3. Starting T<sub>j</sub>=25°C, I<sub>d</sub>=32 A, V<sub>dd</sub>= 25 V

**Table 3. Thermal resistance**

| Symbol                              | Parameter                                      | Value |                            |                    |        |          | Unit |
|-------------------------------------|--|-------|----------------------------|--------------------|--------|----------|------|
|                                     |  | DPAK  | IPAK<br>I <sup>2</sup> PAK | D <sup>2</sup> PAK | TO-220 | TO-220FP |      |
| R <sub>thj-case</sub>               | Thermal resistance junction-case max           | 1.36  |                            |                    | 5      | °C/W     |      |
| R <sub>thj-pcb</sub> <sup>(1)</sup> | Thermal resistance junction-pcb max            | 50    |                            | 35                 |        | °C/W     |      |
| R <sub>thj-a</sub>                  | Thermal resistance junction-ambient max        |       | 100                        |                    | 62.5   | °C/W     |      |
| T <sub>l</sub>                      | Maximum lead temperature for soldering purpose |       | 275                        |                    | 300    | °C       |      |

1. When mounted on FR-4 board of 1inch<sup>2</sup>, 2oz Cu

## 2 Electrical characteristics

(T<sub>CASE</sub> = 25 °C unless otherwise specified)

**Table 4. Static**

| Symbol               | Parameter   | Test conditions   | Min. | Typ. | Max.      | Unit     |
|----------------------|---|---|------|------|-----------|----------|
| V <sub>(BR)DSS</sub> | Drain-source breakdown voltage                        | I <sub>D</sub> = 250µA, V <sub>GS</sub> = 0                               | 55   |      |           | V        |
| I <sub>DSS</sub>     | Zero gate voltage drain current (V <sub>GS</sub> = 0) | V <sub>DS</sub> = Max rating,<br>V <sub>DS</sub> = Max rating, Tc = 125°C |      |      | 10<br>100 | µA<br>µA |
| I <sub>GSS</sub>     | Gate body leakage current (V <sub>DS</sub> = 0)       | V <sub>GS</sub> = ±20V  |      |      | ±200      | nA       |
| V <sub>GS(th)</sub>  | Gate threshold voltage                                | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250µA                | 2    |      | 4         | V        |
| R <sub>DS(on)</sub>  | Static drain-source on resistance                     | V <sub>GS</sub> = 10V, I <sub>D</sub> = 32A                               |      | 6.5  | 8.5       | mΩ       |

**Table 5. Dynamic**

| Symbol                         | Parameter                    | Test conditions                                      | Min. | Typ. | Max. | Unit |
|--------------------------------|------------------------------|--|------|------|------|------|
| g <sub>fs</sub> <sup>(1)</sup> | Forward transconductance     | V <sub>DS</sub> = 25V, I <sub>D</sub> = 32A          | -    | 50   |      | S    |
| C <sub>iss</sub>               | Input capacitance            | V <sub>DS</sub> = 25V, f = 1MHz, V <sub>GS</sub> = 0 | -    | 2200 |      | pF   |
| C <sub>oss</sub>               | Output capacitance           |  |      | 500  |      | pF   |
| C <sub>rss</sub>               | Reverse transfer capacitance |  |      | 25   |      | pF   |
| Q <sub>g</sub>                 | Total gate charge            | V <sub>DD</sub> = 27V, I <sub>D</sub> = 65A          | -    | 33.5 | 45   | nC   |
| Q <sub>gs</sub>                | Gate-source charge           | V <sub>GS</sub> = 10V                                |      | 12.5 |      | nC   |
| Q <sub>gd</sub>                | Gate-drain charge            | (see Figure 16)                                      |      | 9.5  |      | nC   |

1. Pulsed: pulse duration = 300 µs, duty cycle 1.5%

**Table 6. Switching on/off (inductive load)**

| Symbol              | Parameter           | Test conditions   | Min. | Typ. | Max. | Unit |
|---------------------|---------------------|---|------|------|------|------|
| t <sub>d(on)</sub>  | Turn-on delay time  | V <sub>DD</sub> = 27V, I <sub>D</sub> = 32A,<br>R <sub>G</sub> = 4.7Ω, V <sub>GS</sub> = 10V<br>(see Figure 18) | -    | 20   | -    | ns   |
| t <sub>r</sub>      | Rise time           |   |      | 50   | -    | ns   |
| t <sub>d(off)</sub> | Turn-off delay time | V <sub>DD</sub> = 27V, I <sub>D</sub> = 32A,<br>R <sub>G</sub> = 4.7Ω, V <sub>GS</sub> = 10V<br>(see Figure 18) | -    | 35   | -    | ns   |
| t <sub>f</sub>      | Fall time           |   |      | 11.5 | -    | ns   |


Table 7. Source drain diode

| Symbol                            | Parameter  | Test conditions  | Packages   | Min. | Typ.            | Max.      | Unit          |
|-----------------------------------|--|--|--|------|-----------------|-----------|---------------|
| $I_{SD}$<br>$I_{SDM}^{(1)}$       | Source-drain current<br>Source-drain current (pulsed)                        |  | DPAK-D <sup>2</sup> PAK-<br>I <sup>2</sup> PAK-I <sup>2</sup> PAK-<br>TO-220 | -    |                 | 80<br>320 | A<br>A        |
| $I_{SD}$<br>$I_{SDM}^{(1)}$       | Source-drain current<br>Source-drain current (pulsed)                        |  | TO-220FP   | -    |                 | 42<br>168 | A<br>A        |
| $V_{SD}$                          | Forward on voltage   | $I_{SD} = 65A, V_{GS} = 0$   |  | -    |                 | 1.5       | V             |
| $t_{rr}$<br>$Q_{rr}$<br>$I_{RRM}$ | Reverse recovery time<br>Reverse recovery charge<br>Reverse recovery current | $I_{SD} = 65A, V_{DD} = 30V$<br>$di/dt = 100A/\mu s,$<br>$T_j = 150^\circ C$<br><i>(see Figure 17)</i> |  | -    | 47<br>87<br>3.7 |           | ns<br>nC<br>A |


1. Pulsed: pulse duration = 300  $\mu s$ , duty cycle 1.5%

## 2.1 Electrical characteristics (curves)


**Figure 2. Safe operating area for TO-220 D<sup>2</sup>PAK / IPAK / I<sup>2</sup>PAK / DPAK**



**Figure 3. Thermal impedance for TO-220 D<sup>2</sup>PAK / IPAK / I<sup>2</sup>PAK / DPAK**



**Figure 4. Safe operating area for TO-220FP**



**Figure 5. Thermal impedance for TO-220FP**




Figure 6. Output characteristics




Figure 7. Transfer characteristics




Figure 8. Normalized  $BV_{DSS}$  vs temperature




Figure 9. Static drain-source on resistance




Figure 10. Gate charge vs gate-source voltage




Figure 11. Capacitance variations




Figure 12. Normalized gate threshold voltage vs temperature




Figure 13. Normalized on resistance vs temperature






Figure 14. Source-drain diode forward characteristics






### 3 Test circuits


**Figure 15. Switching times test circuit for resistive load**




**Figure 16. Gate charge test circuit**




**Figure 17. Test circuit for inductive load switching and diode recovery times**




**Figure 18. Unclamped inductive load test circuit**



**Figure 19. Unclamped inductive waveform**



**Figure 20. Switching time waveform**




## 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.


I<sup>2</sup>PAK (TO-262) mechanical data

| Dim | mm   |     |       | inch  |     |       |
|-----|------|-----|-------|-------|-----|-------|
|     | Min  | Typ | Max   | Min   | Typ | Max   |
| A   | 4.40 |     | 4.60  | 0.173 |     | 0.181 |
| A1  | 2.40 |     | 2.72  | 0.094 |     | 0.107 |
| b   | 0.61 |     | 0.88  | 0.024 |     | 0.034 |
| b1  | 1.14 |     | 1.70  | 0.044 |     | 0.066 |
| c   | 0.49 |     | 0.70  | 0.019 |     | 0.027 |
| c2  | 1.23 |     | 1.32  | 0.048 |     | 0.052 |
| D   | 8.95 |     | 9.35  | 0.352 |     | 0.368 |
| e   | 2.40 |     | 2.70  | 0.094 |     | 0.106 |
| e1  | 4.95 |     | 5.15  | 0.194 |     | 0.202 |
| E   | 10   |     | 10.40 | 0.393 |     | 0.410 |
| L   | 13   |     | 14    | 0.511 |     | 0.551 |
| L1  | 3.50 |     | 3.93  | 0.137 |     | 0.154 |
| L2  | 1.27 |     | 1.40  | 0.050 |     | 0.055 |




D<sup>2</sup>PAK (TO-263) mechanical data

| Dim | mm   |      |       | inch  |       |       |
|-----|------|------|-------|-------|-------|-------|
|     | Min  | Typ  | Max   | Min   | Typ   | Max   |
| A   | 4.40 |      | 4.60  | 0.173 |       | 0.181 |
| A1  | 0.03 |      | 0.23  | 0.001 |       | 0.009 |
| b   | 0.70 |      | 0.93  | 0.027 |       | 0.037 |
| b2  | 1.14 |      | 1.70  | 0.045 |       | 0.067 |
| c   | 0.45 |      | 0.60  | 0.017 |       | 0.024 |
| c2  | 1.23 |      | 1.36  | 0.048 |       | 0.053 |
| D   | 8.95 |      | 9.35  | 0.352 |       | 0.368 |
| D1  | 7.50 |      |       | 0.295 |       |       |
| E   | 10   |      | 10.40 | 0.394 |       | 0.409 |
| E1  | 8.50 |      |       | 0.334 |       |       |
| e   |      | 2.54 |       |       | 0.1   |       |
| e1  | 4.88 |      | 5.28  | 0.192 |       | 0.208 |
| H   | 15   |      | 15.85 | 0.590 |       | 0.624 |
| J1  | 2.49 |      | 2.69  | 0.099 |       | 0.106 |
| L   | 2.29 |      | 2.79  | 0.090 |       | 0.110 |
| L1  | 1.27 |      | 1.40  | 0.05  |       | 0.055 |
| L2  | 1.30 |      | 1.75  | 0.051 |       | 0.069 |
| R   |      | 0.4  |       |       | 0.016 |       |
| V2  | 0°   |      | 8°    | 0°    |       | 8°    |




**TO-252 (DPAK) mechanical data**

| DIM. | mm.  |      |       |
|------|------|------|-------|
|      | min. | typ  | max.  |
| A    | 2.20 |      | 2.40  |
| A1   | 0.90 |      | 1.10  |
| A2   | 0.03 |      | 0.23  |
| b    | 0.64 |      | 0.90  |
| b4   | 5.20 |      | 5.40  |
| c    | 0.45 |      | 0.60  |
| c2   | 0.48 |      | 0.60  |
| D    | 6.00 |      | 6.20  |
| D1   |      | 5.10 |       |
| E    | 6.40 |      | 6.60  |
| E1   |      | 4.70 |       |
| e    |      | 2.28 |       |
| e1   | 4.40 |      | 4.60  |
| H    | 9.35 |      | 10.10 |
| L    | 1    |      |       |
| L1   |      | 2.80 |       |
| L2   |      | 0.80 |       |
| L4   | 0.60 |      | 1     |
| R    |      | 0.20 |       |
| V2   | 0°   |      | 8°    |




**TO-251 (IPAK) mechanical data**

| DIM. | mm.  |       |      |
|------|------|-------|------|
|      | min. | typ   | max. |
| A    | 2.20 |       | 2.40 |
| A1   | 0.90 |       | 1.10 |
| b    | 0.64 |       | 0.90 |
| b2   |      |       | 0.95 |
| b4   | 5.20 |       | 5.40 |
| c    | 0.45 |       | 0.60 |
| c2   | 0.48 |       | 0.60 |
| D    | 6.00 |       | 6.20 |
| E    | 6.40 |       | 6.60 |
| e    |      | 2.28  |      |
| e1   | 4.40 |       | 4.60 |
| H    |      | 16.10 |      |
| L    | 9.00 |       | 9.40 |
| (L1) | 0.80 |       | 1.20 |
| L2   |      | 0.80  |      |
| V1   |      | 10°   |      |




TO-220 mechanical data

| Dim | mm    |       |       | inch  |       |       |
|-----|-------|-------|-------|-------|-------|-------|
|     | Min   | Typ   | Max   | Min   | Typ   | Max   |
| A   | 4.40  |       | 4.60  | 0.173 |       | 0.181 |
| b   | 0.61  |       | 0.88  | 0.024 |       | 0.034 |
| b1  | 1.14  |       | 1.70  | 0.044 |       | 0.066 |
| c   | 0.48  |       | 0.70  | 0.019 |       | 0.027 |
| D   | 15.25 |       | 15.75 | 0.6   |       | 0.62  |
| D1  |       | 1.27  |       |       | 0.050 |       |
| E   | 10    |       | 10.40 | 0.393 |       | 0.409 |
| e   | 2.40  |       | 2.70  | 0.094 |       | 0.106 |
| e1  | 4.95  |       | 5.15  | 0.194 |       | 0.202 |
| F   | 1.23  |       | 1.32  | 0.048 |       | 0.051 |
| H1  | 6.20  |       | 6.60  | 0.244 |       | 0.256 |
| J1  | 2.40  |       | 2.72  | 0.094 |       | 0.107 |
| L   | 13    |       | 14    | 0.511 |       | 0.551 |
| L1  | 3.50  |       | 3.93  | 0.137 |       | 0.154 |
| L20 |       | 16.40 |       |       | 0.645 |       |
| L30 |       | 28.90 |       |       | 1.137 |       |
| ∅P  | 3.75  |       | 3.85  | 0.147 |       | 0.151 |
| Q   | 2.65  |       | 2.95  | 0.104 |       | 0.116 |



TO-220FP mechanical data

| Dim. | mm   |      |      |
|------|------|------|------|
|      | Mn.  | Typ. | Max. |
| A    | 4.4  |      | 4.6  |
| B    | 2.5  |      | 2.7  |
| D    | 2.5  |      | 2.75 |
| E    | 0.45 |      | 0.7  |
| F    | 0.75 |      | 1    |
| F1   | 1.15 |      | 1.70 |
| F2   | 1.15 |      | 1.5  |
| G    | 4.95 |      | 5.2  |
| G1   | 2.4  |      | 2.7  |
| H    | 10   |      | 10.4 |
| L2   |      | 16   |      |
| L3   | 28.6 |      | 30.6 |
| L4   | 9.8  |      | 10.6 |
| L5   | 2.9  |      | 3.6  |
| L6   | 15.9 |      | 16.4 |
| L7   | 9    |      | 9.3  |
| Dia  | 3    |      | 3.2  |




7012510\_Rev\_J



# 5 Packaging mechanical data

## DPAK FOOTPRINT




## TAPE AND REEL SHIPMENT

| REEL MECHANICAL DATA |      |      |       |        |
|----------------------|------|------|-------|--------|
| DIM.                 | mm   |      | inch  |        |
|                      | MIN. | MAX. | MIN.  | MAX.   |
| A                    |      | 330  |       | 12.992 |
| B                    | 1.5  |      | 0.059 |        |
| C                    | 12.8 | 13.2 | 0.504 | 0.520  |
| D                    | 20.2 |      | 0.795 |        |
| G                    | 16.4 | 18.4 | 0.645 | 0.724  |
| N                    | 50   |      | 1.968 |        |
| T                    |      | 22.4 |       | 0.881  |

| BASE QTY |  | BULK QTY |  |
|----------|--|----------|--|
| 2500     |  | 2500     |  |

| DIM. | mm   |      | inch  |       |
|------|------|------|-------|-------|
|      | MIN. | MAX. | MIN.  | MAX.  |
| A0   | 6.8  | 7    | 0.267 | 0.275 |
| B0   | 10.4 | 10.6 | 0.409 | 0.417 |
| B1   |      | 12.1 |       | 0.476 |
| D    | 1.5  | 1.6  | 0.059 | 0.063 |
| D1   | 1.5  |      | 0.059 |       |
| E    | 1.65 | 1.85 | 0.065 | 0.073 |
| F    | 7.4  | 7.6  | 0.291 | 0.299 |
| K0   | 2.55 | 2.75 | 0.100 | 0.108 |
| P0   | 3.9  | 4.1  | 0.153 | 0.161 |
| P1   | 7.9  | 8.1  | 0.311 | 0.319 |
| P2   | 1.9  | 2.1  | 0.075 | 0.082 |
| R    | 40   |      | 1.574 |       |
| W    | 15.7 | 16.3 | 0.618 | 0.641 |

### D<sup>2</sup>PAK FOOTPRINT



### TAPE AND REEL SHIPMENT

**TAPE MECHANICAL DATA**

| DIM. | mm   |      | inch   |        |
|------|------|------|--------|--------|
|      | MIN. | MAX. | MIN.   | MAX.   |
| A0   | 10.5 | 10.7 | 0.413  | 0.421  |
| B0   | 15.7 | 15.9 | 0.618  | 0.626  |
| D    | 1.5  | 1.6  | 0.059  | 0.063  |
| D1   | 1.59 | 1.61 | 0.062  | 0.063  |
| E    | 1.65 | 1.85 | 0.065  | 0.073  |
| F    | 11.4 | 11.6 | 0.449  | 0.456  |
| K0   | 4.8  | 5.0  | 0.189  | 0.197  |
| P0   | 3.9  | 4.1  | 0.153  | 0.161  |
| P1   | 11.9 | 12.1 | 0.468  | 0.476  |
| P2   | 1.9  | 2.1  | 0.075  | 0.082  |
| R    | 50   |      | 1.574  |        |
| T    | 0.25 | 0.35 | 0.0098 | 0.0137 |
| W    | 23.7 | 24.3 | 0.933  | 0.956  |

**REEL MECHANICAL DATA**

| DIM. | mm   |      | inch  |        |
|------|------|------|-------|--------|
|      | MIN. | MAX. | MIN.  | MAX.   |
| A    |      | 330  |       | 12.992 |
| B    | 1.5  |      | 0.059 |        |
| C    | 12.8 | 13.2 | 0.504 | 0.520  |
| D    | 20.2 |      | 0.795 |        |
| G    | 24.4 | 26.4 | 0.960 | 1.039  |
| N    | 100  |      | 3.937 |        |
| T    |      | 30.4 |       | 1.197  |

| BASE QTY | BULK QTY |
|----------|----------|
| 1000     | 1000     |

10 pitches cumulative tolerance on tape +/- 0.2 mm

\* on sales type

## 6 Revision history

**Table 8. Document revision history**

| Date        | Revision | Changes   |
|-------------|----------|---|
| 09-Feb-2007 | 1        | First release   |
| 22-Feb-2007 | 2        | Description has been updated  |
| 07-Mar-2007 | 3        | The <i>Figure 2</i> , <i>Figure 4</i> , <i>Figure 9</i> have been changed |
| 17-Apr-2009 | 4        | Added device in I <sup>2</sup> PAK<br>Updated all mechanical data         |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)