



140 462

TECHNICAL BULLETIN**Date : 12/08/97****Ref. : KME 0104****Cable : General Audio Interconnect, Single Core Cable****Part Number : 4619****Description :**

Conductor	1 conductor 18x0.10 Plain Copper
Insulation	PE Diam. 1.1mm
Core colour	Transparent
Screening	Plain Copper Lapscreen
Sheath	Black PVC
Diameter	1.9mm
Weight	7 kg/km
Min. insulation Resistance at +20°C	1000 MΩxkm
Capacitance	145 pF/m
Operating voltage	250V max

Approved to ISO 9002

ALCATEL CABLENET LTD • REGISTERED IN ENGLAND No. 6911215
REGISTERED OFFICE: TANDY HOUSE, FELIXSTOWE ROAD, ABBEY WOOD, LONDON, SE2 9AA

140-463 + 567 863

ALCATEL
CABLE**TECHNICAL BULLETIN**

Date : 12/08/97

Ref. : KME 1152

Cable : General Audio Interconnect, Twin Cable**Part Number** : 4635**Description** :

Conductor	2 conductors 18/0.1 Plain Copper
Insulation	PVC Diam. 1.1mm
Cores colours	White - Brown
Screening	Plain Copper Lapscreen
Sheath	Grey PVC
Diameter	3.7mm
Weight	18 kg/km
Min. insulation Resistance at +20°C	200 MΩxkm
Capacitance	90 pF/m
Operating voltage	250V max

Whilst every care has been taken, Alcatel accepts no responsibility for inaccuracies. All product information is subject to change.

Approved to ISO 9002

ALCATEL CABLENET LTD • REGISTERED IN ENGLAND No. 698215
REGISTERED OFFICE: TANDY HOUSE, FELIXSTOWE ROAD, ABBEY WOOD, LONDON, SE2 9AA