

P-tec Corp. Tel:(800)688-0613
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa Co. 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL0016 Series Ultra-Bright White Side View SMD LED

Features

- *Side View Package
2.85mm x 1.2mm x 1.0mm
- *Right Angle Design Ideal for Backlighting
- *Low Current Requirements
- *High Light Output
- *Wide Viewing Angle
- *Space Saving Design
- *Compatible with IR Solder-Process
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Reverse Voltage (<100µA)	5.0V
Power Dissipation	120mW
D.C. Forward Current	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100mA
Operating Temperature Range	-30°C to +85°C
Storage Temperature Range	-40°C to +100°C
Reflow Soldering Temperature	260°C for 10 seconds
ESD Threshold (HBM)	300V

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Material	Chromacity Coordinates		View Angle 2θ ½ Deg	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)		Luminous Flux mlm
			X	Y		Typ	Max	Min	Max	
PL0016-WCW24	White	InGaN	0.31	0.30	120°	3.2	3.8	800	1300	1300

Package Dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

