












Amp	Volt	Hz	IP Ident. colour + h	Part No.	Panel sockets straight	2 P +	IEC/EN 60 309	 9	EAN No. 4015609...																														
					flange dimension 75 x 75, fingerproof according to VBG 4																																		
16	230	50/60	6	411 306	   			10	018734 018727 018758																														
	110	50/60	4	411 304																																			
	400	50/60	9	411 309																																			
32	230	50/60	6	430 306				10	019564 019557 019571																														
	110	50/60	4	430 304																																			
	400	50/60	9	430 309																																			
					fixing dimension = a + b, flange dim = d + e																																		
					<table><tr><td>Ampère</td><td>a</td><td>b</td><td>c</td><td>d</td><td>e</td><td>f</td><td>h</td><td>n</td><td>p</td></tr><tr><td>16 A</td><td>60</td><td>60</td><td>5,5</td><td>75</td><td>75</td><td>52</td><td>46</td><td>28</td><td>6</td></tr><tr><td>32 A</td><td>60</td><td>60</td><td>5,5</td><td>75</td><td>75</td><td>65</td><td>60</td><td>27</td><td>9</td></tr></table>				Ampère	a	b	c	d	e	f	h	n	p	16 A	60	60	5,5	75	75	52	46	28	6	32 A	60	60	5,5	75	75	65	60	27	9	
Ampère	a	b	c	d	e	f	h	n	p																														
16 A	60	60	5,5	75	75	52	46	28	6																														
32 A	60	60	5,5	75	75	65	60	27	9																														
					flange dimension 107 x 100, fingerproof according to VBG 4																																		
63	230	50/60	6	460 306	   			5	020287 020270 020294																														
	110	50/60	4	460 304																																			
	400	50/60	9	460 309																																			
125	see page 2/134							586																															
										fixing dimension = a + b, flange dim = d + e																													
										<table><tr><td>Ampère</td><td>a</td><td>b</td><td>c</td><td>d</td><td>e</td><td>f</td><td>h</td><td>n</td><td>p</td></tr><tr><td>63 A</td><td>85</td><td>77</td><td>6,5</td><td>107</td><td>100</td><td>85</td><td>90</td><td>52</td><td>12</td></tr></table>				Ampère	a	b	c	d	e	f	h	n	p	63 A	85	77	6,5	107	100	85	90	52	12						
Ampère	a	b	c	d	e	f	h	n	p																														
63 A	85	77	6,5	107	100	85	90	52	12																														
					flange dimension 62 x 62, fingerproof according to VBG 4																																		
16	230	50/60	6	410 306	   			10/60	018376 018369 018406																														
	110	50/60	4	410 304																																			
	400	50/60	9	410 309																																			
					fixing dimension = a + b, flange dim = d + e																																		
					<table><tr><td>Ampère</td><td>a</td><td>b</td><td>c</td><td>d</td><td>e</td><td>f</td><td>h</td><td>n</td><td>p</td></tr><tr><td>16 A</td><td>47</td><td>47</td><td>5,5</td><td>62</td><td>62</td><td>52</td><td>46</td><td>28</td><td>6</td></tr></table>				Ampère	a	b	c	d	e	f	h	n	p	16 A	47	47	5,5	62	62	52	46	28	6											
Ampère	a	b	c	d	e	f	h	n	p																														
16 A	47	47	5,5	62	62	52	46	28	6																														
					installation in switch cabinets, junction box mountable on DIN-rails, seizes 4,5 MCB module units																																		
16	230	50/60	6	411 306VS	  			10	132546 160754 160761																														
	110	50/60	4	411 304VS																																			
	400	50/60	9	411 309VS																																			
32	230	50/60	6	430 306VS				10	160969 160952 160976																														
	110	50/60	4	430 304VS																																			
	400	50/60	9	430 309VS																																			
					fixing dimension = a + b, flange dim = d + e																																		
					<table><tr><td>Ampère</td><td>a</td><td>b</td><td>d</td><td>e</td><td>f</td><td>n</td><td>p</td></tr><tr><td>16 A</td><td>60</td><td>60</td><td>80</td><td>80</td><td>56</td><td>52</td><td>10</td></tr><tr><td>32 A</td><td>60</td><td>60</td><td>80</td><td>80</td><td>62</td><td>52</td><td>10</td></tr></table>				Ampère	a	b	d	e	f	n	p	16 A	60	60	80	80	56	52	10	32 A	60	60	80	80	62	52	10							
Ampère	a	b	d	e	f	n	p																																
16 A	60	60	80	80	56	52	10																																
32 A	60	60	80	80	62	52	10																																

Amp	Volt	Hz	IP Ident. colour + h	Part No.	Panel sockets straight	2 P +	IEC/EN 60 309		EAN No. 4015609...																																	
					detachable flange, flange dimension 62 x 62, fingerproof according to VBG 4																																					
16	230	50/60	6	412 306	 																																					
	110	50/60	4	412 304																																						
	400	50/60	9	412 309																																						
					fixing dimension = a + b, flange dim. = d + e																																					
					<table><tr><th>Ampère</th><th>a</th><th>b</th><th>c</th><th>d</th><th>e</th><th>f</th><th>h</th><th>n</th><th>p</th></tr><tr><td>16 A</td><td>47</td><td>47</td><td>5,5</td><td>62</td><td>62</td><td>58</td><td>50</td><td>32</td><td>8,5</td></tr></table>	Ampère	a	b	c	d	e	f	h	n	p	16 A	47	47	5,5	62	62	58	50	32	8,5																	
Ampère	a	b	c	d	e	f	h	n	p																																	
16 A	47	47	5,5	62	62	58	50	32	8,5																																	
					detachable flange, flange dimension 80 x 80, fingerproof according to VBG 4																																					
32	230	50/60	6	431 306	 																																					
	110	50/60	4	431 304																																						
	400	50/60	9	431 309																																						
					fixing dimension = a + b, flange dimension = d + e																																					
					<table><tr><th>Ampère</th><th>a</th><th>b</th><th>c</th><th>d</th><th>e</th><th>f</th><th>h</th><th>n</th><th>p</th></tr><tr><td>32 A</td><td>60</td><td>60</td><td>5,5</td><td>80</td><td>80</td><td>60</td><td>71</td><td>32</td><td>8,5</td></tr></table>	Ampère	a	b	c	d	e	f	h	n	p	32 A	60	60	5,5	80	80	60	71	32	8,5																	
Ampère	a	b	c	d	e	f	h	n	p																																	
32 A	60	60	5,5	80	80	60	71	32	8,5																																	
					mondo RAL 7035 light grey																																					
16	230	50/60	6	415 306	 																																					
	110	50/60	4	415 304																																						
	400	50/60	9	415 309																																						
					RW = clear white, RAL 9010																																					
					230 50/60 6 415 306 RW																																					
					PW = pearl white, RAL 1013																																					
					230 50/60 6 415 306 PW																																					
32	230	50/60	6	435 306	 																																					
	110	50/60	4	435 304																																						
	400	50/60	9	435 309																																						
					RW = clear white, RAL 9010																																					
					230 50/60 6 435 306 RW																																					
					PW = pearl white, RAL 1013																																					
					230 50/60 6 435 306 PW																																					
					fixing dimension = a + b, flange dimension = d + e																																					
					<table><tr><th>Ampère</th><th>a</th><th>b</th><th>c</th><th>d</th><th>e</th><th>f</th><th>h</th><th>n</th><th>r</th><th>z</th></tr><tr><td>16 A</td><td>30,4</td><td>65,2</td><td>4,1</td><td>90</td><td>90</td><td>38</td><td>65</td><td>36</td><td>96</td><td>/</td></tr><tr><td>32 A</td><td>60</td><td>60</td><td>4,1</td><td>90</td><td>90</td><td>45</td><td>75</td><td>31</td><td>104</td><td>80</td></tr></table>	Ampère	a	b	c	d	e	f	h	n	r	z	16 A	30,4	65,2	4,1	90	90	38	65	36	96	/	32 A	60	60	4,1	90	90	45	75	31	104	80				
Ampère	a	b	c	d	e	f	h	n	r	z																																
16 A	30,4	65,2	4,1	90	90	38	65	36	96	/																																
32 A	60	60	4,1	90	90	45	75	31	104	80																																