

BREADBOARD


967 324

FEATURES OF WISHBOARD WBU-5XX SERIES

(USA PATENT NO.4,606,725&D.299,253)

1. High-class acetal material allows insertion hole to withstand wear and tear without easily deforming, also ideal for high frequency and low static.
2. Horizontal assembly corresponds to the operation flow design of the PC boards for handy operation.
3. The power distribution strip provides 4 sections of positive voltage terminals handy for using different voltages at the same time, also 45 connected tie points for negative circuit.
4. Exquisitely printed coordinates for easy recognition and calculation.
5. Easy-on-the eyes color for longer operation without eye fatigue.
6. Durable base stand aluminum nameplate means no static interference.
7. Especially small volume saves space.
8. The dovetail protrusions and recesses designed to connect two adjacent boards tightly together (i.e. perfect size distance from one board to another) and forming a V-shaped cross-sectional groove which allows DIP IC pins inserting across two parts and to increase the rate of utilization.

Item No.	Distribution strips	Distribution holes	Terminal strips	Terminal holes	Aluminum plate thick	Knob posts	Foot pads	Jumper wires	Dimension(m/m) LxWxH	Packing
WBU-5D WBU-5DJ	2	85x2	0	0	0	0	0	0	141.6x10.2x8.2	Paper box /2pcs Skin packing/2pcs
WBU-5T WBU-5TJ	0	0	1	800	0	0	0	0	141.6x55.7x8.2	Paper box Skin packing
WBU-501 WBU-501J	1	85	1	800	0.4	0	0	0	141.6x64.4x8.2	Paper box Skin packing
WBU-502 WBU-502+J	2	170	1	800	0.4	0	0	$\frac{0}{70}$	141.6x73.1x8.2	Paper box Skin packing
WBU-502L WBU-502L+J	2	170	1	800	1.6	4	$\frac{4}{5}$	$\frac{0}{140}$	125x160x31	Paper box Skin packing
WBU-504 WBU-504+J	3	255	2	1600	1.6	4	$\frac{4}{5}$	$\frac{0}{140}$	160x190x31	Paper box Skin packing
WBU-504L WBU-504L+J	4	340	2	1600	1.6	4	5	$\frac{0}{140}$	125x305x31	Paper box Skin packing
WBU-506 WBU-506+J	4	340	3	2400	1.6	4	5	$\frac{0}{140}$	250x160x31	Paper box Skin packing
WBU-508L WBU-508L+J	6	510	4	3200	1.6	4	5	$\frac{0}{140}$	190x305x31	Paper box Skin packing
WBU-57 WBU-57J	1	90	1	795	0.4	0	0	0	143x64x8.2	Paper box Skin packing
WB-601 WB-601J	2	600	1	+30(6 sections) -35(All through)	0.4	0	0	0	115x70x8.2	Paper box Skin packing




- a. In distribution strip of WBU 5xx each clip group has 10 tie-points connect together For (+) and 45 tie points connect together For(-).
- b. In terminal strips of WBU 5xx each clip group has 5 tie-points connect together.

GROUND PLATE

1. Materials: Aluminum name plate.
2. Efficiency: Ideal for high frequency and high-speed/low-noise circuits.
3. WBU502L - WBU508L mounted on a name plate + 4 binding posts.

THE COMMON FEATURES OF WISH-BOARD SPRING CLIP

1. Materials: Phospher Bronze/Nickel Silver.
2. Thickness: (0.15mm) 0.0059 inch.
3. Insertion Range: 20-29 AWG(ϕ 0.3- ϕ 0.8mm) wire all dip size components acceptable. (Special design over 10,000 insertion cycles.)
4. Surface Finish: Gold Plated, Silver-plated, Nickel-plated.



PLASTIC BODY

Maplize: Screen printed with Number and letter showed on surface available for circuit design.