


Schottky PowerMod

CPT40030 – CPT40050



Dim.		Inches	Millimeters		
Min.	Max.		Min.	Max.	Notes
A	---	3.630	---	92.20	
B	0.700	0.800	17.78	20.32	
C	---	0.630	---	16.00	
E	0.120	0.130	3.05	3.30	
F	0.490	0.510	12.45	12.95	
G	1.375	BSC	34.92	BSC	
H	0.010	---	0.25	---	
N	---	---	---	---	1/4-20
Q	0.275	0.290	6.99	7.37	Dia.
R	3.150	BSC	80.01	BSC	
U	0.600	---	15.24	---	
V	0.312	0.340	7.92	8.64	
W	0.180	0.195	4.57	4.95	Dia.

Microsemi Catalog Number	Industry Part Number	Working Reverse Voltage	Peak Voltage	Repetitive Reverse Voltage
CPT40030*		30V	30V	
CPT40035*	401CNQ035 MBR40035CT	35V	35V	
CPT40040*	401CNQ040 MBR40040CT	40V	40V	
CPT40045*	401CNQ045 MBR40045CT	45V	45V	
CPT40050*		50V	50V	

*Add Suffix A for Common Anode, D for Doubler

- Schottky Barrier Rectifier
- Guard Ring Protection
- 400 Amperes/ 30 to 50 Volts
- 175°C Junction Temperature
- Reverse Energy Tested
- ROHS Compliant

Electrical Characteristics

Average forward current per pkg	F(AV) 400 Amps	T _C = 127°C, Square wave, R _{θJC} = 0.16°C/W
Average forward current per leg	F(AV) 200 Amps	T _C = 127°C, Square wave, R _{θJC} = 0.32°C/W
Maximum surge current per leg	FSM 3000 Amps	8.3ms, half sine, T _J = 175°C
Maximum repetitive reverse current per leg	R(OV) 2 Amps	f = 1 KHZ, 25°C, 1 μsec square wave
Max peak forward voltage per leg	V _{FM} 0.78 Volts	FM = 200A:T _J = 25°C*
Max peak forward voltage per leg	V _{FM} 0.62 Volts	FM = 200A:T _J = 175°C*
Max peak reverse current per leg	RM 100 mA	V _{RRM} , T _J = 125°C*
Max peak reverse current per leg	RM 5.0 mA	V _{RRM} , T _J = 25°C
Typical junction capacitance per leg	C _J 7200 pF	V _R = 5.0V, T _C = 25°C

*Pulse test: Pulse width 300μsec, Duty cycle 2%

Thermal and Mechanical Characteristics

Storage temp range	T _{STG}	-55°C to 175°C
Operating junction temp range	T _J	-55°C to 175°C
Max thermal resistance per leg	R _{θJC}	0.32°C/W Junction to case
Max thermal resistance per pkg	R _{θJC}	0.16°C/W Junction to case
Typical thermal resistance (greased)	R _{θCS}	0.08°C/W Case to sink
Terminal Torque		35–50 inch pounds
Mounting Base Torque (outside holes)		30–40 inch pounds
Mounting Base Torque (center hole) center hole must be torqued first		8–10 inch pounds
Weight		2.8 ounces (72 grams) typical

CPT40030 – CPT40050

Figure 1
Typical Forward Characteristics – Per Leg




Figure 2
Typical Reverse Characteristics – Per Leg




Figure 3
Typical Junction Capacitance – Per Leg




Figure 4
Forward Current Derating – Per Leg




Figure 5
Maximum Forward Power Dissipation – Per Leg

