

## HEATSINK CALCULATION AND EXAMPLES

In many cases, GS-Rx and GSxTy-z modules don't require any additional cooling methods because the dimensions and the shape of the metal boxes were studied to offer the minimum possible thermal resistance case to ambient for a given module.

It should be remembered, that GS-R and GS-T modules are power devices i.e. products that deliver power and dissipate power and, depending on ambient temperature, an additional heat-sink or forced ventilation or both may be required to keep the unit within safe temperature range.

We would like here to eliminate a wrong parameter that has been plaguing the technical literature of power devices for 30 years: the operating ambient temperature specified among Absolute Maximum Rating.

The concept of operating ambient temperature is totally meaningless when we deal with power components, because the operating ambient temperature depends on how a power device is used.

What can be unambiguously defined is the maximum junction temperature of a power semiconductor device or the case temperature of a module. To prove this, let's consider the following example:

GS-R1005 at :

$V_{in} = 24V$     $I_o = 10A$     $P_o = 50W$     $T_{casemax} = 75^\circ C$

GS100T300-12 at :

$V_{in} = 300V$     $I_o = 8A$     $P_o = 96W$     $T_{casemax} = 70^\circ C$

From data sheets we can get the respective efficiencies  $\eta$  and power dissipations

$$P_d = P_o \left( \frac{1}{\eta} - 1 \right)$$

GS-R1005             $\eta = 0.83$              $P_d = 10.2W$

GS100T300-12     $\eta = 0.84$              $P_d = 18.3W$

In case of natural convection (no heat-sink or forced ventilation) the thermal resistance case to ambient and the maximum ambient temperature ( $T_{ambMAX} = T_{Cmax} - R_{th} \cdot P_d$ ) will be:

GS-R1005

$R_{th} = 7.5^\circ C/W$        $T_{ambMAX} = 75 - 7.5 \cdot 10.2 = -1.5^\circ C$

GS100T300-12

$R_{th} = 7.5^\circ C/W$        $T_{ambMAX} = 70 - 7.5 \cdot 18.3 = -62.25^\circ C$

As data show, the maximum operating ambient temperatures are a "non-sense" in the two cases, due to the fact that both devices are for use with an external heatsink.

In practice a designer must fix four preliminary values such as:

$V_{in}$  = Input voltage

$V_{out}$  = Output voltage

$I_{out}$  = Output current

$T_{amb}$  = Maximum ambient temperature at which the system must operate.

From these data, it is easy to determine whether an additional heat-sink is required or not and the relevant size i.e. the required thermal resistance. The step by step calculation is as follows:

1. Calculate output power:

$$P_o = V_o \cdot I_o$$

2. On data sheet, from  $V_o$ ,  $V_{in}$ ,  $I_o$ , the efficiency is obtained directly or by calculation:

$$\eta = \frac{P_o}{P_{IN}}$$

3. The actual power dissipation is given by:

$$P_d = P_o \left( \frac{1}{\eta} - 1 \right)$$

4. The case temperature is calculated:

$$T_{CASE} = T_{AMBmax} + R_{th} \cdot P_d$$

( $R_{th}$  is shown on data sheet)

5. If  $T_{case} < T_{caseMAX}$  no external heat-sink is required

If  $T_{case} > T_{caseMAX}$  then proceed as follows.

6. Let's calculate what thermal resistance case to ambient is needed:

$$T_{TH(tot)} = \frac{T_{CASEmax} - T_{AMBmax}}{P_d}$$

## HEATSINK APPLICATION NOTES

---

This is the total thermal resistance i.e. the parallel of the module and external heat- sink thermal resistances.

7. The thermal resistance of the additional heat-sink is calculated:

$$R_{TH(HS)} = \frac{R_{THmodule} \cdot R_{TOT}}{R_{THmodule} - R_{TOT}}$$

As an example, let's consider two cases.  
Conditions:

|  |  |
|--|--|
| GS-R1005                                 | GS100T300-12                             |
| $V_{in1} = 24 \text{ V}$                 | $V_{in2} = 300 \text{ V}$                |
| $V_{o1} = 5\text{V}$                     | $V_{o2} = 12 \text{ V}$                  |
| $I_{o1} = 2\text{A}$                     | $I_{o2} = 5\text{A}$                     |
| $R_{th1} = 7.5 \text{ }^\circ\text{C/W}$ | $R_{th2} = 7.5 \text{ }^\circ\text{C/W}$ |
| $T_{caseMAX}=75^\circ\text{C}$           | $T_{caseMAX}=70^\circ\text{C}$           |
| $T_{ambMAX} = 55^\circ\text{C}$          |  |

1. Output powers:

$$P_{O1} = 5 \cdot 2 = 10 \text{ W} \quad P_{O2} = 12 \cdot 5 = 60 \text{ W}$$

2. From data sheet:

$$\eta_1 = 0.83 \quad \eta_2 = 0.84$$

3. Power dissipations:

$$P_{d1} = 10 \left( \frac{1}{0.83} - 1 \right) = 2.0 \text{ W}$$

$$P_{d2} = 60 \left( \frac{1}{0.84} - 1 \right) = 11.4$$

4. Case temperatures:

$$T_{C1} = 55 + 2.0 \cdot 7.5 = 70 \text{ }^\circ\text{C}$$

$$T_{C2} = 55 + 11.4 \cdot 7.5 = 140.5 \text{ }^\circ\text{C}$$

5. The GS-R1005 does not require heat-sink that is, on the contrary, required for GS100T300-12.

6. Total thermal resistance for GS100T300-12

$$R_{TH(TOT)} = \frac{70 - 55}{11.4} = 1.31 \text{ }^\circ\text{C} / \text{W}$$

7. Required thermal resistance of heat-sink:

$$R_{TH(HS)} = \frac{7.5 \cdot 1.31}{7.5 - 1.31} = 1.58 \text{ }^\circ\text{C} / \text{W}$$

## HEATSINK APPLICATION NOTE

The following table gives the thermal resistance of commercially available heat-sinks.

| Manufacturer | Part Number | Rth °C/W | Mounting | Fastening |
|--------------|-------------|----------|----------|-----------|
| SGS-THOMSON  | HS01        | 2.8      | Vert.    | Screw     |
| THERMALLOY   | 6177        | 3        | Horiz.   | Screw     |
| THERMALLOY   | 6152        | 4        | Vert.    | Screw     |
| THERMALLOY   | 6111        | 10       | Vert.    | Adeshive  |
| THERMALLOY   | 6155        | 4.5      | Vert.    | Screw     |
| THERMALLOY   | 6601        | 5        | Vert.    | Screw     |
| THERMALLOY   | 6176        | 4.5      | Vert.    | Screw     |
| THERMALLOY   | 6320        | 1.5      | Horiz.   | Screw     |
| ALUTRONIC    | PR139       | 3        | Vert.    | Screw     |
| ALUTRONIC    | PR140       | 2        | Horiz.   | Screw     |
| ALUTRONIC    | PR159       | 2.5      | Vert.    | Screw     |
| AAVID        | 60885       | 4.5      | Vert.    | Screw     |
| AAVID        | 60660       | 1.5      | Horiz.   | Screw     |
| AAVID        | 62355       | 3        | Vert.    | Screw     |
| AUSTERLITZ   | KS50        | 3        | Vert.    | Screw     |
| AUSTERLITZ   | KS100.3     | 2.5      | Horiz.   | Screw     |
| FISCHER      | SK18        | 3        | Vert.    | Screw     |
| FISCHER      | SK48        | 3        | Vert.    | Screw     |
| FISCHER      | SK16        | 1.5      | Horiz.   | Screw     |
| FISCHER      | SK52        | 2        | Horiz.   | Screw     |
| FISCHER      | SK07        | 4        | Vert.    | Adeshive  |
| SGE Bosari   | L30         | 3        | Horiz.   | Screw     |
| SGE Bosari   | LZ50        | 3        | Vert.    | Screw     |
| SGE Bosari   | SR50        | 6        | Vert.    | Adeshive  |
| ASSMAN       | V5280       | 2        | Horiz.   | Screw     |
| ASSMAN       | V5805       | 2        | Vert.    | Screw     |
| ASSMAN       | V5440       | 4        | Vert.    | Adeshive  |
| ASSMAN       | V5382       | 4        | Horiz.   | Screw     |
| ASSMAN       | V5460       | 3        | Vert.    | Screw     |
| ASSMAN       | V5510       | 3        | Vert.    | Screw     |

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics – All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.