

N- and P-Channel 20-V (D-S) MOSFETs

PRODUCT SUMMARY



	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)	Q _g (Typ.)
N-Channel	20	0.022 at V _{GS} = 4.5 V	6.7 ^a	6.7 nC
		0.036 at V _{GS} = 2.5 V	5.2 ^a	
P-Channel	- 20	0.030 at V _{GS} = - 4.5 V	- 6.1 ^a	17 nC
		0.045 at V _{GS} = - 2.5 V	- 5.0 ^a	

FEATURES


- Halogen-free
- TrenchFET[®] Power MOSFETs

APPLICATIONS

- Load Switch
- DC/DC Converter


RoHS
COMPLIANT

Ordering Information: Si6562CDQ-T1-GE3 (Lead (Pb)-free and Halogen-free)


N-Channel MOSFET



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter		Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage		V _{DS}	20	- 20	V
Gate-Source Voltage		V _{GS}	± 12		
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	I _D	6.7	- 6.1	A
	T _C = 70 °C		4.2	- 4.9	
	T _A = 25 °C		5.7 ^{b, c}	- 5.1 ^{b, c}	
	T _A = 70 °C		4.5 ^{b, c}	- 4.1 ^{b, c}	
Pulsed Drain Current		I _{DM}	30	- 30	W
Source Drain Current Diode Current	T _C = 25 °C	I _S	1.3	- 1.4	
	T _A = 25 °C		0.9 ^{b, c}	- 1.0 ^{b, c}	
Maximum Power Dissipation	T _C = 25 °C	P _D	1.6	1.7	
	T _C = 70 °C		1.0	1.1	
	T _A = 25 °C		1.1 ^{b, c}	1.2 ^{b, c}	
	T _A = 70 °C		0.7 ^{b, c}	0.76 ^{b, c}	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	- 55 to 150		°C

THERMAL RESISTANCE RATINGS

Parameter	Symbol	N-Channel		P-Channel		Unit
		Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^{b, d}	R _{thJA}	85	110	81	105	°C/W
Maximum Junction-to-Foot (Drain)	R _{thJF}	62	80	57	75	

Notes:

a. T_C = 25 °C.

b. Surface Mounted on 1" x 1" FR4 board.

c. t = 10 s.

d. Maximum under Steady State conditions is 145 °C/W.

SPECIFICATIONS T _J = 25 °C, unless otherwise noted								
Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit	
Static								
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	N-Ch	20			V	
		V _{GS} = 0 V, I _D = - 250 μA	P-Ch	- 20				
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA	N-Ch		22		mV/°C	
		I _D = - 250 μA	P-Ch		- 21			
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J	I _D = 250 μA	N-Ch		- 3.5			
		I _D = - 250 μA	P-Ch		3.5			
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	N-Ch	0.6		1.5	V	
		V _{DS} = V _{GS} , I _D = - 250 μA	P-Ch	- 0.6		- 1.5		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 12 V	N-Ch P-Ch			± 100 ± 100	nA	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V	N-Ch			1	μA	
		V _{DS} = - 20 V, V _{GS} = 0 V	P-Ch			- 1		
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C	N-Ch			10		
		V _{DS} = - 20 V, V _{GS} = 0 V, T _J = 55 °C	P-Ch			- 10		
On-State Drain Current ^b	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 4.5 V	N-Ch	30			A	
		V _{DS} ≤ - 5 V, V _{GS} = - 4.5 V	P-Ch	- 30				
Drain-Source On-State Resistance ^b	R _{DS(on)}	V _{GS} = 4.5 V, I _D = 5.7 A	N-Ch		0.018	0.022	Ω	
		V _{GS} = - 4.5 V, I _D = - 5.1 A	P-Ch		0.024	0.030		
		V _{GS} = 2.5 V, I _D = 4.4 A	N-Ch		0.029	0.036		
		V _{GS} = - 2.5 V, I _D = - 4.2 A	P-Ch		0.036	0.045		
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 5.7 A	N-Ch		17		S	
		V _{DS} = - 10 V, I _D = - 5.1 A	P-Ch		22			
Dynamic ^a								
Input Capacitance	C _{iss}	N-Channel V _{DS} = 10 V, V _{GS} = 0 V, f = 1 MHz	N-Ch P-Ch		850 1200		pF	
Output Capacitance	C _{oss}		N-Ch P-Ch		150 260			
Reverse Transfer Capacitance	C _{rss}	P-Channel V _{DS} = - 10 V, V _{GS} = 0 V, f = 1 MHz	N-Ch P-Ch		70 45			
Total Gate Charge	Q _g		V _{DS} = 10 V, V _{GS} = 10 V, I _D = 5.7 A	N-Ch		15		23
		V _{DS} = - 10 V, V _{GS} = - 10 V, I _D = - 5.1 A	P-Ch		34	51		
		N-Channel V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 5.7 A	N-Ch		6.7	11		
			P-Ch		17	30		
Gate-Source Charge	Q _{gs}	P-Channel V _{DS} = - 10 V, V _{GS} = - 4.5 V, I _D = - 5.1 A	N-Ch P-Ch		1.8 3			
			N-Ch P-Ch		0.9 5.5			
Gate-Drain Charge	Q _{gd}							
Gate Resistance	R _g	f = 1 MHz	N-Ch P-Ch		2 6		Ω	

Notes:

a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.









SPECIFICATIONS T _J = 25 °C, unless otherwise noted							
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	
Dynamic ^a							
Turn-On Delay Time	t _{d(on)}	N-Channel V _{DD} = 10 V, R _L = 2.2 Ω I _D ≅ 4.5 A, V _{GEN} = 4.5 V, R _g = 1 Ω P-Channel V _{DD} = - 10 V, R _L = 2.4 Ω I _D ≅ - 4.1 A, V _{GEN} = - 4.5 V, R _g = 1 Ω	N-Ch		12	20	ns
			P-Ch		30	45	
Rise Time	t _r		N-Ch		10	15	
			P-Ch		25	40	
Turn-Off Delay Time	t _{d(off)}		N-Ch		25	40	
			P-Ch		45	70	
Fall Time	t _f		N-Ch		10	15	
			P-Ch		15	25	
Turn-On Delay Time	t _{d(on)}	N-Channel V _{DD} = 10 V, R _L = 2.2 Ω I _D ≅ 4.5 A, V _{GEN} = 10 V, R _g = 1 Ω P-Channel V _{DD} = - 10 V, R _L = 2.4 Ω I _D ≅ - 4.1 A, V _{GEN} = - 10 V, R _g = 1 Ω	N-Ch		10	15	ns
			P-Ch		10	15	
Rise Time	t _r		N-Ch		10	15	
			P-Ch		10	15	
Turn-Off Delay Time	t _{d(off)}		N-Ch		20	30	
			P-Ch		45	70	
Fall Time	t _f		N-Ch		8	15	
			P-Ch		15	25	
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I _S	T _C = 25 °C	N-Ch			1.3	A
			P-Ch			- 1.4	
Pulse Diode Forward Current ^a	I _{SM}		N-Ch			30	
			P-Ch			- 30	
Body Diode Voltage	V _{SD}	I _S = 4.5 A, V _{GS} = 0 V	N-Ch		0.8	1.2	V
		I _S = - 4.1 A, V _{GS} = 0 V	P-Ch		- 0.8	- 1.2	
Body Diode Reverse Recovery Time	t _{rr}	N-Channel I _F = 4.5 A, dl/dt = 100 A/μs, T _J = 25 °C P-Channel I _F = - 4.1 A, dl/dt = - 100 A/μs, T _J = 25 °C	N-Ch		15	30	ns
			P-Ch		35	55	
Body Diode Reverse Recovery Charge	Q _{rr}		N-Ch		6	12	nC
			P-Ch		21	35	
Reverse Recovery Fall Time	t _a		N-Ch		7.6		ns
			P-Ch		18		
Reverse Recovery Rise Time	t _b		N-Ch		7.4		
			P-Ch		17		

Notes:


a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**


N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage





Single Pulse Power











* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified






Safe Operating Area, Junction-to-Ambient



N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.



**N-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted**Normalized Thermal Transient Impedance, Junction-to-Ambient****Normalized Thermal Transient Impedance, Junction-to-Foot**

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**

**P-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted**Source-Drain Diode Forward Voltage****On-Resistance vs. Gate-to-Source****Threshold Voltage****Single Pulse Power*** $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified**Safe Operating Area, Junction-to-Ambient**

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

**P-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted**Normalized Thermal Transient Impedance, Junction-to-Ambient****Normalized Thermal Transient Impedance, Junction-to-Foot**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?68954>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.