



ISTS823A
ISTS824A



**1mm APERTURE OPTO-ELECTRONIC SINGLE CHANNEL
SLOTTED INTERRUPTER SWITCHES WITH TRANSISTOR
SENSORS AND 450mm FLYING LEADS**



DESCRIPTION

The ISTS823A, ISTS824A opaque photointerrupters are single channel switches consisting of a Gallium Arsenide infrared emitting diode and a NPN silicon photo transistor mounted in a polycarbonate housing with 450mm flying leads. The package is designed to optimise the mechanical resolution, coupling efficiency, ambient light rejection, cost and reliability. Operating on the principle that objects opaque to infrared will interrupt the transmission of light between an infrared emitting diode and a photo sensor switching the output from an "ON" state to an "OFF" state.

FEATURES

- High Gain
- 3mm Gap between LED and Detector
- Polycarbonate case protected against ambient light

APPLICATIONS

- Copiers, Printers, Facsimiles, Record Players, Casette Decks, Optoelectronic Switches

ABSOLUTE MAXIMUM RATINGS (25°C unless otherwise specified)

Storage Temperature	—	-40°C to + 85°C
Operating Temperature	—	-25°C to + 85°C
Lead Soldering Temperature (1/16 inch (1.6mm) from case for 10 secs)	—	260°C

INPUT DIODE

Forward Current	—	50mA
Reverse Voltage	—	5V
Power Dissipation	—	75mW

OUTPUT TRANSISTOR

Collector-emitter Voltage BV _{CEO}	—	30V
Emitter-collector Voltage BV _{ECO}	—	5V
Collector Current I _C	—	20mA
Power Dissipation	—	75mW

ISOCOM COMPONENTS LTD

Unit 25B, Park View Road West,
Park View Industrial Estate, Brenda Road
Hartlepool, Cleveland, TS25 1YD
Tel: (01429) 863609 Fax : (01429) 863581






ISOCOM INC

720 E., Park Boulevard, Suite 104,
Plano, TX 75074 USA
Tel: (972) 423-5521
Fax: (972) 422-4549

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION
Input	Forward Voltage (V_F) Reverse Voltage (V_R) Reverse Current (I_R)	5	1.2	1.7 100	V V μA	$I_F = 50\text{mA}$ $I_R = 100\mu\text{A}$ $V_R = 5\text{V}$
Output	Collector-emitter Breakdown (BV_{CEO}) (Note 1)	30			V	$I_C = 1\text{mA}$
	Emitter-collector Breakdown (BV_{ECO})	5		100	V	$I_E = 100\mu\text{A}$
	Collector-emitter Dark Current (I_{CEO})			nA		$V_{CE} = 15\text{V}$
Coupled	On-State Collector Current $I_C(ON)$ (Note 1) ISTS823A ISTS824A	200 500			μA μA	20mA I_F , 10V V_{CE} 20mA I_F , 10V V_{CE}
	Collector-emitter Saturation Voltage $V_{CE(SAT)}$ ISTS823A ISTS824A			0.4 0.4	V V	20mA I_F , 100 μA I_C 20mA I_F , 250 μA I_C
	Turn-on Time ton Turn-off Time toff		8	50	μs μs	$V_{CC} = 5\text{V}$, $I_F = 30\text{mA}$, $R_L = 2.5\text{k}\Omega$

Note 1 Special Selections are available on request. Please consult the factory.

Collector Power Dissipation vs. Ambient Temperature**Normalized Output Current vs. Collector-emitter Voltage****Forward Current vs. Ambient Temperature****Normalized Output Current vs. Forward Current****Normalized Output Current vs. Ambient Temperature****Collector-emitter Saturation Voltage vs. Ambient Temperature**