



**Sonomatic®
Ultrasonic
Cleaning
Units**

- T80**
- 175**
- 375**
- 475**
- 575**

| | | | T80 | 175 | 375 | 475 | 575 |
|--|----------------|--------|--|------------|------------|------------|------------|
| Technical Data | | | | | | | |
| Overall Dimensions: | Length | [mm] | 175 | 175 | 295 | 295 | 350 |
| | Width | [mm] | 110 | 165 | 170 | 170 | 180 |
| | Height | [mm] | 160 | 200 | 195 | 240 | 240 |
| Weight | approx. | [kg] | 1,4 | 2,4 | 3,7 | 4,6 | 5,2 |
| Outer Case: | | | Rigidised stainless steel | | | | |
| Internal Dimensions: | Length | [mm] | 151 | 151 | 240 | 240 | 300 |
| | Width | [mm] | 83 | 137 | 135 | 135 | 150 |
| | Height | [mm] | 65 | 100 | 100 | 150 | 150 |
| Tank Volume: | approx. | [ltr] | 0,6 | 1,6 | 2,3 | 3,6 | 4,9 |
| Tank Material: | | | Chromium Nickel Alloy | | | | |
| High Frequency Generator: | | | Double half wave | | | | |
| HF-Peak Power: | | [Watt] | 80 | 100 | 150 | 300 | 300 |
| Frequency | approx. | [kHz] | 40 | 40 | 40 | 40 | 40 |
| Mains voltage: | | | 220/240V - 50/60Hz | | | | |
| Power consumption: | | [Watt] | 60 | 75 | 290 | 410 | 460 |
| Fuses: | | [A} | 1,0 | 1,0 | 2x2,0M | 2x3,15M | 2x3,15M |
| Heating capacity: | | [Watt] | n/a | n/a | 200 | 250 | 300 |
| Temperature Control of Cleaning Fluid | | | approx. 60° C, thermostatically controlled | | | | |
| Timer Control, Ultrasonics | | | 0 - 15 Minutes and continuous ∞ | | | | |
| Maintenance free: | | | yes | yes | yes | yes | yes |
| FTZ - Approval | | | yes | yes | yes | yes | yes |

Accessories: Lids and Baskets - stainless Steel
Ask for Details of larger Units, up to 200 Litres Capacity

| | | |
|---|----------------------------|-----|
| Langford Electronics Ltd. Crown Road, Unit 23, The Kings Norton Business Centre Birmingham B30 3HY - UK | Phone: 021-433 4343 | ☎ |
| | | 4 ☎ |
| | | 5 ☎ |
| | Fax: 021-433 3075 | ☎ |