

SANYO

No.2439A

2SA1540/2SC3955

PNP/NPN Epitaxial Planar Silicon Transistor

**High-Definition CRT Display
Video Output Applications****Applications**

- High-definition CRT display video output, wide-band amp

Features

- High gain-bandwidth product ($f_T=300\text{MHz}$)
- High breakdown voltage ($V_{CE0}=200\text{Vmin}$)
- Small reverse transfer capacitance and excellent high frequency characteristics ($C_{re}=1.5\text{pF/NPN}$, 1.8pF/PNP)
- Complementary PNP and NPN types
- Adoption of FBET process
- Micaless type (T0126 plastic package)

(): PNP

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

			unit
Collector-to-Base Voltage	V_{CB0}	(-)200	V
Collector-to-Emitter Voltage	V_{CE0}	(-)200	V
Emitter-to-Base Voltage	V_{EB0}	(-)3	V
Collector Current	I_C	(-)100	mA
Collector Current (Pulse)	I_{CP}	(-)200	mA
Collector Dissipation	P_C	1.3	W
	$T_c=25^\circ\text{C}$	7	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics at $T_a=25^\circ\text{C}$

			min	typ	max	unit
Collector Cutoff Current	I_{CB0}	$V_{CB}=(-)150\text{V}, I_E=0$			(-)0.1	μA
Emitter Cutoff Current	I_{EB0}	$V_{EB}=(-)2\text{V}, I_C=0$			(-)1.0	μA
DC Current Gain	h_{FE1}	$V_{CE}=(-)10\text{V}, I_C=(-)10\text{mA}$	40*		320*	
	h_{FE2}	$V_{CE}=(-)10\text{V}, I_C=(-)50\text{mA}$	20			
Gain-Bandwidth Product	f_T	$V_{CE}=(-)30\text{V}, I_C=(-)30\text{mA}$		300		MHz
Output Capacitance	C_{ob}	$V_{CB}=(-)30\text{V}, f=1\text{MHz}$		1.9		pF
				(2.4)		pF
Reverse Transfer Capacitance	C_{re}	$V_{CB}=(-)30\text{V}, f=1\text{MHz}$		1.5		pF
				(1.8)		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C=(-)20\text{mA}, I_B=(-)2\text{mA}$			(-)1.0	V
E-B Saturation Voltage	$V_{BE(sat)}$	$I_C=(-)20\text{mA}, I_B=(-)2\text{mA}$			(-)1.0	V

* h_{FE1} : The 2SA1540/2SC3955 are classified by 10mA h_{FE} as follows:


40	C	80	60	D	120	100	E	200	160	F	320
----	---	----	----	---	-----	-----	---	-----	-----	---	-----

Package Dimensions 2042A

(unit: mm)

B: Base
C: Collector
E: Emitter

SANYO: T0126ML

**SANYO Electric Co., Ltd. Semiconductor Business Headquarters**

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

