

Product SKU: C2118.21.08

Product Description: Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 20, Conductor/Strands: Solid, Jacket:

Premium Grade PVC, Temperature Range: -20°C to +105°C - Brown - 1000 Ft. Spool

Product Category: Electronics - Hook-Up Wire - UL 1015, CSA TEW - SOLID CONDUCTORS - Brown



Product Construction:

Conductor: • 24 thru 10 AWG

• Fully-annealed, tinned copper per ASTM B-33

• Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$

Product Specification:

Conductor Size (AWG): • 20

Conductor/Strands: • Solid

No. of Pairs: • 1

Jacket Color:

• Brown

Nominal Insulation Thickness • 0.032 (in):

Nominal Insulation Thickness • 0.81 (mm):

Nominal Outside Diameter (in): • 0.096

Nominal Outside Diameter • 2.44 (mm):

Standard Packaging: • 1000' Spool

Standard Package Quantity:	• 1
UPC #:	• 079407770786
Put-up:	• 1000
SCC-14:	• 50079407770788
Cube:	• 277.0596
Weight Per Unit of Measure:	• .007
ColorOption:	• Brown
Product Information:	
Applications:	• Internal wiring of electrical and electronic equipment
	 Internal wiring of panels and meters
	Point-to-point wiring
	• Suggested voltage rating: 600 Volts
Compliances:	• CSA Type TEW
	• Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1015 - 105°C, 600V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305 m) Spools
	Other put-ups available- consult Customer Service
Reference Charts Color Code Chart	
Technical Specifications Unit Conversion Factors	
<u>Unit Conversion Factors</u> <u>Cable Design Equations - Balanced Pair</u>	
Insulation and Jacket Properties	
Temperature Conversion Chart	
Decimal and Unit Conversion Factors	
Cable Design Equations - Braid Shield	
AWG Conductor Chart	

Conduit Capacity Chart

<u>Cable Design Equations - Coaxial Cable</u> <u>Engineering Prefixes</u> <u>Coax Connector Cross Reference</u>



Glossary



Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

