


FEATURES

- Differential D, clock and Q
- Extended 100E VEE range of -4.2V to -5.5V
- VBB output for single-ended use
- 1100MHz min. toggle frequency
- Edge-triggered asynchronous set and reset
- Fully compatible with Motorola MC10E/100E431
- Available in 28-pin PLCC package

BLOCK DIAGRAM



TRUTH TABLE⁽¹⁾

D _n	CLK _n	R _n	S _n	Q _n
L	Z	L	L	L
H	Z	L	L	H
X	L	Z	L	L
X	L	L	Z	H

NOTE:

1. Z = LOW-to-HIGH transition.


DESCRIPTION

The SY10/100E431 are 3-bit flip-flops with differential clock, data input and data output.

The asynchronous Set and Reset controls are edge-triggered rather than level controlled. This allows the user to rapidly set or reset the flip-flop and then continue clocking at the next clock edge without the necessity of de-asserting the set/reset signal (as would be the case with a level controlled set/reset).

The E431 is also designed with larger internal swings, an approach intended to minimize the time spent crossing the threshold region and thus reduces the metastability susceptibility window.

PIN CONFIGURATION



PIN NAMES

Pin	Function
D[0:2], $\overline{D}$ [0:2]	Differential Data Inputs
CLK[0:2], $\overline{CLK}$ [0:2]	Differential Clock Inputs
S[0:2]	Edge Triggered Set Inputs
R[0:2]	Edge Triggered Reset Inputs
VBB	VBB Reference Output
Q[0:2], $\overline{Q}$ [0:2]	Differential Data Outputs
VccO	Vcc to Output

DC ELECTRICAL CHARACTERISTICS⁽²⁾V_{EE} = V_{EE} (Min.) to V_{EE} (Max.); V_{CC} = V_{CCO} = GND

Symbol	Parameter	T _A = 0°C			T _A = +25°C			T _A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
V _{BB}	Output Reference Voltage										V	—
	10E	-1.38	—	-1.27	-1.35	—	-1.25	-1.31	—	-1.19		
	100E	-1.38	—	-1.26	-1.38	—	-1.26	-1.38	—	-1.26		
I _{IH}	Input HIGH Current	—	—	150	—	—	150	—	—	150	μA	—
I _{EE}	Power Supply Current										mA	—
	10E	—	110	132	—	110	132	—	110	132		
	100E	—	110	132	—	110	132	—	110	152		
V _{CMR}	Common Mode Range	-1.5	—	0	-1.5	—	0	-1.5	—	0	V	1

NOTES:

- V_{CMR} is referenced to the most positive side of the differential input signal. Normal operation is obtained when the input signals are within the V_{CMR} range and the input swing is greater than V_{PP} (min.) and <1V.
- Specification for packaged product only.

AC ELECTRICAL CHARACTERISTICS⁽⁴⁾V_{EE} = V_{EE} (Min.) to V_{EE} (Max.); V_{CC} = V_{CCO} = GND

Symbol	Parameter	T _A = 0°C			T _A = +25°C			T _A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
f _{MAX}	Max. Toggle Frequency	1100	1400	—	1100	1400	—	1100	1400	—	MHz	—
t _{PLH} t _{PHL}	Propagation Delay to Output CLK (Diff) CLK (SE) R S	450 400 550 550	600 600 725 725	750 800 925 925	450 400 550 550	600 600 725 725	750 800 925 925	450 400 550 550	600 600 725 725	750 800 925 925	ps	—
t _S	Set-up Time										ps	1 1
	D	200	0	—	200	0	—	200	0	—		
	R	1000	700	—	1000	700	—	1000	700	—		
	S	1000	700	—	1000	700	—	1000	700	—		
t _H	Hold Time, D	200	0	—	200	0	—	200	0	—	ps	—
t _{PW}	Minimum Pulse Width, CLK	400	—	—	400	—	—	400	—	—	ps	—
t _{skew}	Within-Device Skew	—	50	—	—	50	—	—	50	—	ps	2
V _{PP} (AC)	Minimum Input Swing	150	—	—	150	—	—	150	—	—	mV	3
t _r t _f	Rise/Fall Time 20% to 80%	275	450	650	275	450	650	275	450	650	ps	—

NOTES:


- These set-up times define the minimum time the CLK or SET/RESET input must wait after the assertion of the RESET/SET input to assure the proper operation of the flip-flop.
- Within-device skew is defined as identical transitions on similar paths through a device.
- Minimum input swing for which AC parameters are guaranteed.
- Specification for packaged product only.

PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range
SY10E431JI	J28-1	Industrial
SY10E431JITR*	J28-1	Industrial
SY100E431JI	J28-1	Industrial
SY100E431JITR*	J28-1	Industrial

*Tape and Reel

28 LEAD PLCC (J28-1)



Rev. 03

MICREL, INC. 1849 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL + 1 (408) 944-0800 FAX + 1 (408) 944-0970 WEB <http://www.micrel.com>

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel, Inc.

© 2002 Micrel, Incorporated.
