

TTC-1T13

1 × 9 Fiber Optic Transceiver for 100BASE-SX

FEATURES:

- High quality VCSEL transmitter at 850 nm wavelength
- 50% energy saving over LED transmitters
- Low dispersion secures better optical signal after long distance transmission
- Link distance up to 300m with 62.5/125 um and 50/125 um optical fibers.
- Compatible with 10BASE-FL
- Capability of auto-negotiating with 10BASE-FL, 100BASE-SX and 1000BASE-SX
- Satisfy TIA 100BASE-SX-SP-4360A specification
- Meet IEC 825-1 Eye Safety Standard
- Industrial standard 1X9 package footprint
- Duplex ST* ports



TRANSMITTER ELECTRO-OPTICAL CHARACTERISTICS

PARAMETERS	SYMBOL	MIN	TYP	MAX	UNIT
Supply Current	I _{CC}		35	45	mA
Power Dissipation	P _{DISS}		0.175		W
Supply Voltage	V _{CC}	4.75		5.25	V
Wavelength	λ	830	850	860	nm
Output Optical Power	P _O	-17		-12	dBm
Data Input Voltage - Low ⁽¹⁾	V _{IL}	-1.810		-1.475	V _{CC}
Data Input Voltage - High ⁽¹⁾	V _{IH}	-1.165		-0.880	V _{CC}
Output Extinction Ratio ⁽²⁾			10		dB
Optical Rise Time	t _r		1.3	2.2	ns
Optical Fall Time	t _f		1.3	2.2	ns
Duty Cycle Distortion	DCD			0.6	ns p-p
Systematic Jitter	SJ			0.60	ns p-p
Random Jitter	RJ		0.20	0.69	ns p-p

(1) Voltage levels listed are compatible with 100K Series PECL logic levels. The parts are compatible with 10K and 10KH Series logic when driven with differential signals.

(2) This Optical Extinction Ratio is expressed in decibels (dB) by the relationship $10 \times \log(P_{\text{high avg}}/P_{\text{low avg}})$.

RECEIVER ELECTRO-OPTICAL CHARACTERISTICS

PARAMETERS	SYMBOL	MIN	TYP	MAX	UNIT
Supply Current	I _{CC}		55		mA
Power Dissipation	P _{DISS}		0.275		W
Supply Voltage	V _{CC}	4.75		5.25	V
Data Output Voltage – Low ⁽¹⁾	V _{IL}	-1.810		-1.475	V _{CC}
Data Output Voltage - High ⁽¹⁾	V _{IH}	-1.165		-0.880	V _{CC}
Signal Detect Output Voltage - Low	V _{IL}	-1.810		-1.475	V _{CC}
Signal Detect Output Voltage - High	V _{IH}	-1.165		-0.880	V _{CC}
Rise Time	t _r		1.3	2.2	ns
Fall Time	t _f		1.3	2.2	ns
Duty Cycle Distortion	DCD			0.4	ns p-p
Systematic Jitter	SJ			1.00	ns p-p
Random Jitter	RJ		0.2	2.14	ns p-p

Sensitivity		-30	-27	dBm
Input power	P _{in}	0	dBm	
Power level (avg.) Detect Assert	P _A	-33	dBm	
Power level (avg.) Detect Deassert	P _D	-45	dBm	
Level detect hysteresis	P _A -P _D	1.75	2.25	2.75
Signal Detect Assert Time			100	μs
Signal Detect Deassert Time			350	μs





(1) Voltage levels listed are compatible with 100K Series PECL logic levels. The parts are compatible with 10K and 10KH Series logic when driven with differential signals.

ABSOLUTE MAXIMUM RATINGS:

PARAMETERS	SYMBOL	MIN	MAX	UNIT
Storage Temperature	T _S	-40	100	°C
Lead Soldering Limits			260/10	°C/sec
Operating Temperature	T _A	0	70	°C
Supply Voltage	V _{CC}	-0.5	7	V

OUTLINE and PINOUT

Unit:mm



Pinout

- | | |
|-----------------------|-----------------------|
| 1. Rx V _{EE} | 6. Tx V _{cc} |
| 2. Rx Out+ | 7. Tx In- |
| 3. Rx Out- | 8. Tx In+ |
| 4. Signal Detect | 9. Tx V _{ee} |
| 5. Rx V _{cc} | |

* ST is registered trademark of AT&T.