

SPECIFICATION SHEET
JFW MODEL 75BR-023
BENCH TOP ROTARY ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-2150 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-70 dB in 1 dB steps
VSWR	1.5:1 maximum DC-1000 MHz 1.7:1 maximum 1000-2150 MHz
Attenuation Accuracy	DC-1000 MHz ± 0.4 dB (0-10) ± 0.6 dB or 2% (11-70) 1000-2150 MHz ± 0.5 dB (0-10) ± 0.6 dB or 3% (11-70)
Insertion Loss	1.0 dB maximum DC-1000 MHz 1.5 dB maximum 1000-2150 MHz
RF Input Power	1 Watt average 1000 Watts Peak
Direction of Rotation	Attenuation increases in a Counter-Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, N or F
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-4335

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/14/2003		BAC 11/14/2003	14307	06/25/2007	C	TRS 06/25/2007
4532	03/19/2004	A	CLV 03/19/2004				
11617	08/02/2005	B	BAC 08/02/2005				