



- ▶ 13 mm length coupling nut for buffer cable housing realizes easy connection/disconnection
- ▶ Total length 26 mm is similar to SAP-4 and SNP-5
- ▶ Applicable for standard PC/UPC and APC (N-type, R-type) by selection of plug frame and hood color
- ▶ Possible to use plug frame of R-type for standard PC/UPC application
- ▶ Applicable products for PC/UPC: SZ-1A/3A and SFZ-3A ferrule and SAA-3 & 4 adaptor series
- ▶ Applicable products for Angle PC: SNZ-1A/ 3A ferrule and SNA-1 & 3 adaptor series

### ORDERING INFORMATION

Model Number	Type Number						
SAP-6	5	8	0	1	0	D	0
Hood Color		Hood I.D. (mm)		Marking of Hood		Package	
2	Red	8	0.9mm (non-flamable)	0	Without Marking	D0	N type
3	White					K0	R type
5	Blue					Cap	
8	Green					1	Black (PVC)
						8	Green PVC
						A	Black Ferrule Cap
						B	Green Ferrule Cap

Housing

**SAP-6 Series**  
**PC & Angle PC Application**  
**Designed for Ø 0.9 mm**  
**Buffer Cable**  
**Single Mode**



- ▶ Housing designed for Angle PC application
- ▶ Two types of frames available consisting of cutout type and inexpensive molded type
- ▶ Combined with SNZ-1A/ 3A (ferrule) provides low insertion loss and ultra high return loss
- ▶ Keying width: 2.14+0/-0.05 mm (N type); 2.02+0/-0.05 (R type)
- ▶ Recommended adaptor: SNA series

### ORDERING INFORMATION

Model Number	Type Number						
SNP-2	8	3	0	B	1	D	1
Hood Color		Hood I.D. (mm)		Marking of Hood		Specifications	
8	Green	2	2.0 mm	0	Without Marking	01	Cutout frame N type
		3	3.0 mm			D1	Molded frame N type
						J1	Cutout frame R type
						K1	Molded frame R type
						Cap	
						2	Black rubber with strings
						8	Green PVC
						B	Green Ferrule Cap
						Package	
						0	Bulk
						1	Pre-assy

Housing

**SNP-2 Series**  
**Angle PC Application**  
**Designed for**  
**Ø 2.0 mm Cable**  
**Ø 3.0 mm Cable**  
**Single Mode**