


Small Signal Zener Diodes

Features

- Very sharp reverse characteristic
- Low reverse current level
- Very high stability
- Low noise
- High reliability
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



9612009

Applications

- Voltage stabilization

Mechanical Data

Case: QuadroMELF SOD-80

Weight: approx. 34 mg

Cathode band color: black

Packaging codes/options:

GS18/10 k per 13" reel (8 mm tape), 10 k/box

GS08/2.5 k per 7" reel (8 mm tape), 12.5 k/box

Absolute Maximum Ratings

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Power dissipation	R _{thJA} ≤ 300 K/W	P _{tot}	500	mW
Z-current		I _Z	P _{tot} /V _Z	mA
Junction temperature		T _j	175	°C
Storage temperature range		T _{stg}	- 65 to + 175	°C

Thermal Characteristics

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Junction to ambient air	on PC board 50 mm x 50 mm x 1.6 mm	R _{thJA}	500	K/W

Electrical Characteristics

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Forward voltage	I _F = 200 mA	V _F			1.5	V

VLZ-Series

Vishay Semiconductors



Electrical Characteristics

Part-number-group	Part-number	Zener Voltage		Dynamic Resistance		Test Current		Reverse Leakage Current	
		V _Z at I _{ZT}		Z _Z at I _{ZT}	Z _{ZK} at I _{ZK}	I _{ZT}	I _{ZK}	I _R at V _R	
		V	V	Ω	Ω	mA	mA	μA	V
VLZ2V4	VLZ2V4A	2.33	2.52	100	2000	20	1	70	1
	VLZ2V4B	2.43	2.63	100	2000	20	1	70	1
VLZ2V7	VLZ2V7A	2.54	2.75	100	1000	20	1	50	1
	VLZ2V7B	2.69	2.91	100	1000	20	1	50	1
VLZ3V0	VLZ3V0A	2.85	3.07	80	1000	20	1	50	1
	VLZ3V0B	3.01	3.22	80	1000	20	1	10	1
VLZ3V3	VLZ3V3A	3.16	3.38	70	1000	20	1	10	1
	VLZ3V3B	3.32	3.53	70	1000	20	1	10	1
VLZ3V6	VLZ3V6A	3.455	3.695	60	1000	20	1	5	1
	VLZ3V6B	3.6	3.845	60	1000	20	1	5	1
VLZ3V9	VLZ3V9A	3.74	4.01	50	1000	20	1	3	1
	VLZ3V9B	3.89	4.16	50	1000	20	1	3	1
VLZ4V3	VLZ4V3A	4.04	4.29	40	1000	20	1	3	1
	VLZ4V3B	4.17	4.43	40	1000	20	1	3	1
	VLZ4V3C	4.3	4.57	40	1000	20	1	3	1
VLZ4V7	VLZ4V7A	4.44	4.68	25	900	20	1	10	2
	VLZ4V7B	4.55	4.8	25	900	20	1	6	2
	VLZ4V7C	4.68	4.93	25	900	20	1	3	2
VLZ5V1	VLZ5V1A	4.81	5.07	20	800	20	1	2	2
	VLZ5V1B	4.94	5.2	20	800	20	1	2	2
	VLZ5V1C	5.09	5.37	20	800	20	1	2	2
VLZ5V6	VLZ5V6A	5.28	5.55	13	500	20	1	1	2
	VLZ5V6B	5.45	5.73	13	500	20	1	1	2
	VLZ5V6C	5.61	5.91	13	500	20	1	1	2
VLZ6V2	VLZ6V2A	5.78	6.09	10	300	20	1	3	4
	VLZ6V2B	5.96	6.27	10	300	20	1	3	4
	VLZ6V2C	6.12	6.44	10	300	20	1	3	4
VLZ6V8	VLZ6V8A	6.29	6.63	8	150	20	0.5	2	4
	VLZ6V8B	6.49	6.83	8	150	20	0.5	2	4
	VLZ6V8C	6.66	7.01	8	150	20	0.5	2	4
VLZ7V5	VLZ7V5A	6.85	7.22	8	120	20	0.5	3	6.5
	VLZ7V5B	7.07	7.45	8	120	20	0.5	3	6.73
	VLZ7V5C	7.29	7.67	8	120	20	0.5	3	6.93
VLZ8V2	VLZ8V2A	7.53	7.92	8	120	20	0.5	7.5	7.15
	VLZ8V2B	7.78	8.19	8	120	20	0.5	7.5	7.39
	VLZ8V2C	8.03	8.45	8	120	20	0.5	7.5	7.63
VLZ9V1	VLZ9V1A	8.29	8.73	8	120	20	0.5	0.04	7.88
	VLZ9V1B	8.57	9.01	8	120	20	0.5	0.04	8.14
	VLZ9V1C	8.83	9.3	8	120	20	0.5	0.04	8.39
VLZ10	VLZ10A	9.12	9.59	8	120	20	0.5	0.04	8.66
	VLZ10B	9.41	9.9	8	120	20	0.5	0.04	8.94
	VLZ10C	9.7	10.2	8	120	20	0.5	0.04	9.22
	VLZ10D	9.94	10.44	8	120	20	0.5	0.04	9.44
VLZ11	VLZ11A	10.18	10.71	10	120	10	0.5	0.04	9.67
	VLZ11B	10.5	11.05	10	120	10	0.5	0.04	9.98
	VLZ11C	10.82	11.38	10	120	10	0.5	0.04	10.28

Part-number-group	Part-number	Zener Voltage		Dynamic Resistance		Test Current		Reverse Leakage Current	
		V _Z at I _{ZT}		Z _Z at I _{ZT}	Z _{ZK} at I _{ZK}	I _{ZT}	I _{ZK}	I _R at V _R	
		V	V	Ω	Ω	mA	mA	μA	V
		min.	max.	max.	max.			max.	
VLZ12	VLZ12A	11.13	11.71	12	110	10	0.5	0.04	10.6
	VLZ12B	11.44	12.03	12	110	10	0.5	0.04	10.9
	VLZ12C	11.74	12.35	12	110	10	0.5	0.04	11.2
VLZ13	VLZ13A	12.11	12.75	14	110	10	0.5	0.04	11.5
	VLZ13B	12.55	13.21	14	110	10	0.5	0.04	11.9
	VLZ13C	12.99	13.66	14	110	10	0.5	0.04	12.3
VLZ15	VLZ15A	13.44	14.13	16	110	10	0.5	0.04	12.8
	VLZ15B	13.89	14.62	16	110	10	0.5	0.04	13.2
	VLZ15C	14.35	15.09	16	110	10	0.5	0.04	13.6
VLZ16	VLZ16A	14.8	15.57	18	150	10	0.5	0.04	14.1
	VLZ16B	15.25	16.04	18	150	10	0.5	0.04	14.5
	VLZ16C	15.69	16.51	18	150	10	0.5	0.04	14.9
VLZ18	VLZ18A	16.22	17.06	23	150	10	0.5	0.04	15.4
	VLZ18B	16.82	17.7	23	150	10	0.5	0.04	16
	VLZ18C	17.42	18.33	23	150	10	0.5	0.04	16.5
VLZ20	VLZ20A	18.02	18.96	28	200	10	0.5	0.04	17.1
	VLZ20B	18.63	19.59	28	200	10	0.5	0.04	17.7
	VLZ20C	19.23	20.22	28	200	10	0.5	0.04	18.3
	VLZ20D	19.72	20.72	28	200	10	0.5	0.04	18.7
VLZ22	VLZ22A	20.15	21.2	30	200	5	0.5	0.04	19.1
	VLZ22B	20.64	21.71	30	200	5	0.5	0.04	19.6
	VLZ22C	21.08	22.17	30	200	5	0.5	0.04	20
	VLZ22D	21.52	22.63	30	200	5	0.5	0.04	20.4
VLZ24	VLZ24A	22.05	23.18	35	200	5	0.5	0.04	20.9
	VLZ24B	22.61	23.77	35	200	5	0.5	0.04	21.5
	VLZ24C	23.12	24.31	35	200	5	0.5	0.04	22
	VLZ24D	23.63	24.85	35	200	5	0.5	0.04	22.4
VLZ27	VLZ27A	24.26	25.52	45	250	5	0.5	0.04	23
	VLZ27B	24.97	26.26	45	250	5	0.5	0.04	23.7
	VLZ27C	25.63	26.95	45	250	5	0.5	0.04	24.3
	VLZ27D	26.29	27.64	45	250	5	0.5	0.04	25
VLZ30	VLZ30A	26.99	28.39	55	250	5	0.5	0.04	25.6
	VLZ30B	27.7	29.13	55	250	5	0.5	0.04	26.3
	VLZ30C	28.36	29.82	55	250	5	0.5	0.04	26.9
	VLZ30D	29.02	30.51	55	250	5	0.5	0.04	27.6
VLZ33	VLZ33A	29.68	31.22	65	250	5	0.5	0.04	28.2
	VLZ33B	30.32	31.88	65	250	5	0.5	0.04	28.8
	VLZ33C	30.9	32.5	65	250	5	0.5	0.04	29.4
	VLZ33D	31.49	33.11	65	250	5	0.5	0.04	29.9
VLZ36	VLZ36A	32.14	33.79	75	250	5	0.5	0.04	30.5
	VLZ36B	32.79	34.49	75	250	5	0.5	0.04	31.2
	VLZ36C	33.4	35.13	75	250	5	0.5	0.04	31.7
	VLZ36D	34.01	35.77	75	250	5	0.5	0.04	32.3

Part-number-group	Part-number	Zener Voltage		Dynamic Resistance		Test Current		Reverse Leakage Current	
		V _Z at I _{ZT}		I _{ZT}	Z _{ZK} at I _{ZK}	I _{ZT}	I _{ZK}	I _R at V _R	
		V	V	Ω	Ω	mA	mA	μA	V
		min.	max.	max.	max.			max.	
VLZ39	VLZ39A	34.68	36.47	85	250	5	0.5	0.04	32.9
	VLZ39B	35.36	37.19	85	250	5	0.5	0.04	33.6
	VLZ39C	36	37.85	85	250	5	0.5	0.04	34.2
	VLZ39D	36.63	38.52	85	250	5	0.5	0.04	34.8
	VLZ39E	37.36	39.29	85	250	5	0.5	0.04	35.5
	VLZ39F	38.14	40.11	85	250	5	0.5	0.04	36.2
	VLZ39G	38.94	40.8	85	250	5	0.5	0.04	37
VLZ43	VLZ43	40	45	90	-	5	-	0.04	38
VLZ47	VLZ47	44	49	90	-	5	-	0.04	41.8
VLZ51	VLZ51	48	54	100	-	5	-	0.04	45.6
VLZ56	VLZ56	53	60	100	-	5	-	0.04	50.4

Typical Characteristics

T_{amb} = 25 °C, unless otherwise specified




Figure 1. Total Power Dissipation vs. Ambient Temperature




Figure 3. Typical Change of Working Voltage vs. Junction Temperature




Figure 2. Typical Change of Working Voltage under Operating Conditions at T_{amb} = 25°C









Figure 4. Temperature Coefficient of Vz vs. Z-Voltage








Figure 10. Thermal Response

Package Dimensions in millimeters (inches): QuadroMELF SOD-80



20909
Created - Date: 16.October.2007
Document no.:6.560-5006.01a-4



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.