

LED



FEATURES

DIRECTLY REPLACES STANDARD INCANDESCENTS

- LONG LIFE, 100,000 HOURS
- HIGH SHOCK / VIBRATION RESISTANCE SOLID STATE
- BUILT-IN RESISTOR FOR DIRECT 6V TO 130 VAC / DC
- POWER SAVINGS UPTO 500%
- IDEAL FOR MARKER LIGHTS, LARGE MOVING DISPLAYS, SIGNS, PILOT LIGHTS & AUTOMOTIVE LIGHTS...

REPLACES FOLLOWING INCANDESCENTS

198, 1016, 1034, 1154, 1157, 1534, 2057, 2357

PART NO: IDB624 CW6 -28V/30-P

MODEL #	LENS/COLOR/BRIGHT	VOLTS/mAmps Typ	POLARITY
MULTICHIP (24-CHIP) IDB624 (MOL 1.38) IDBM624 (MOL 1.75) IDBL624 (MOL 2.20)	CR3K,CR7,CR6,CO6, CY6,CLY6,CG6,CPG6, CB6,CW6	IDB/IDBM/IDBL624: 16V/50,24V/30,48V/15= EXT. RES. REQD. 24V/50,28V/30,36V/30,48V/30, 60V/15,72V/15,120VAC/15...	CENTER CONTACT: SAME AS BELOW
CLUSTERS 6-7 LEDs (15mm) IDB606/607 (MOL 1.38) IDBM606/607 (MOL 1.75) IDBL606/607 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	IDB/IDBM/IDBL606: 4V/90,6V/90,12V/60 5V/90,6V/90,12V/60 IDB/IDBM/IDBL607: 14V/30= EXT. RES. REQD. 18V/30,24V/30,28V/30,36V/30, 48V/20,60V/20,120VAC/10...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES AC = VAC
CLUSTERS 8-9 LEDs (15mm) IDB608/609 (MOL 1.38) IDBM608/609 (MOL 1.75) IDBL608/609 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	IDB/IDBM/IDBL608: 4V/120,8V/60= EXT. RES. REQD. 5V/120,6V/120,12V/60 IDB/IDBM/IDBL609: 18V/30= EXT. RES. REQD. 24V/30,28V/30,36V/30,48V/20, 60V/20,120VAC/10...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES. AC = VAC
CLUSTERS 18-19 LEDs (15mm) IDB618/619 (MOL 1.38) IDBM618/619 (MOL 1.75) IDBL618/619 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	IDB/IDBM/IDBL618: 18V/60= EXT. RES. REQD. 24V/60,28V/60,36V/40 IDB/IDBM/IDBL619: 38V/30= EXT. RES. REQD. 48V/20,60V/20,72V/20, 120VAC/10...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES. AC = VAC
CLUSTERS 40 LEDs (15mm) IDB640 (MOL 1.38) IDBM640 (MOL 1.75) IDBL640 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	IDB/IDBM/IDBL640: 20V/120,40V/60,80V/30= EXT. RES. REQD. 24V/120,28V/120,36V/80,48V/80, 60V/80,72V/80,120VAC/20...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES. AC = VAC

SPECIALS:

- FLASHING/BLINKING MULTI-LED CLUSTERS
- BICOLOR MULTI-LED CLUSTERS
- DUAL CHIP LEDs IN MULTI-LED CLUSTERS
- INFRARED 850, 880 & 940nm
- MULTI-LED 360° CLUSTERS
- CUSTOM LED CLUSTERS

LENS TYPE: C=CLEAR
 COLOR CODES: R=RED, O=ORANGE, A=AMBER YELLOW, LY=LIME YELLOW, G=GREEN,
 PG=PURE GREEN, B=BLUE, W=WHITE (RED/GREEN)

BRIGHTNESS CODES: 900=900mcd WIDE RED, 3K=3Kmcd NARROW RED, 5K=5Kmcd NARROW RED,
 7=HI ULTRA RED ONLY, 6=ULTRA, 5=SUPER BRIGHT, 3/4= HI EFFICIENCY.

NOTE: WHEN PLACING ORDERS OR REQUESTING SAMPLES, PLEASE INDICATE INCANDESCENT LAMP
 NUMBER BEING REPLACED. WHEN SELECTING THE LED COLOR, MATCH EXISTING LENS COLOR TO
 LED COLOR.

