


Sta-Kon®

Locking Fork Terminals



Stock thickness same as ring terminal of same size.

Vinyl Insulated Locking Fork—Insulation Support



Cat. No.	Bulk. Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Wt./lbs. Bolt Hole	Per 1000	Dimensions			
							A	B	C	M
18RA-6FL	RA2217	100/1M	22-16	.150	#6	5	.97	.25	.25	.81
—	RA2227	1000	22-16	.155	#6	5	.97	.29	—	.81
18RA-8FL	RA2247	100/1M	22-16	.150	#8	5	.97	.29	.25	.81
18RA-10FL	RA2257	100/1M	22-16	.150	#10	5	.97	.29	.25	.81
14RB-6FL	RB2207	100/1M	18-14	.170	#6	6	.97	.25	.27	.81
—	RB2217	1000	—	.170	#6	6	.97	.29	.27	.81
14RB-8FL	RB2237	100/1M	18-14	.170	#8	6	.97	.29	.27	.81
14RB-10FL	RB2257	100/1M	18-14	.170	#10	6	.97	.29	.27	.81
10RC-6FL	RC2207	50/500	12-10	.220	#6	8	1.09	.31	.27	.90
10RC-8FL	RC2217	50/500	12-10	.220	#8	8	1.09	.37	.27	.90
10RC-10FL	RC2227	50/500	12-10	.220	#10	8	1.09	.37	.27	.90
10RC-14FL	RC2237	50/500	12-10	.220	1/4"	8	1.09	.49	.27	.90

U.L. Listed E-9809

Installing tools: ERG-2001, ERG-2003, WT145C, WT2000, WT112M

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

For Mil Specs listing, please refer to page C73.