




[PAGE BACK](#) [CLOSE](#)

**Product Name**      **Multilayer Inductor for Signal Line**  
**Series**              **MLF Series**  
**Type**                 **1608-J Type**  
**Part Number**       **MLF1608E100JT000**

Product Lifecycle Stage    PROD  
Release Date                 2001/10/01



#### Specification

Mounting Method Flag	Yes	
Processing	MULTI-LAYER	
Shape	SMD	
Size Code	1608	
Body Length(L)	Nom	1.6 m m
Body Breadth(W)	Nom	0.8 m m
Body Height(T)	Nom	0.8 m m
Rated Inductance	Nom	10 micro H
Inductance Tolerance (%)	Min	-5 %
	Max	5 %
Test Frequency of Inductance	Nom	2 M Hz
	Min	30
Q	Typ	55
	Nom	2 M Hz
Test Frequency of Q	Min	30 M Hz
	Typ	50 M Hz
Self Resonant Frequency	Max	1.7 Ohm
	Nom	1 Ohm
DC Resistance	Max	10 m A
Terminal Material	Ag(100%)/Sn plating	
Polarity Marking	No	
Magnetic Shielding	Yes	
Soldering Method	Reflow,Iron Soldering	
Measuring Equipment(L, Q, Rdc)	LQ:4294A,RDC:7561	
Category Temperature Range	Min	-55 Cel
	Max	125 Cel
Storage Temperature Range	Min	-55 Cel
	Max	125 Cel
Weight	Nom	0.004 g

#### Summary/Applications/Feature

Summary	As multilayer chip inductor using ferrite material with a new design, it features narrow tolerance(+/-5%) small inductor in the industry.
Applications	Signal processing such as cellular phone, car audio, tuner, DVC.
Feature	As multilayer chip inductor using ferrite material, it is the first narrow tolerance(+/-5%) small inductor in the industry. Inductance change by soldering is less than 1/3 from elegance conventionally. The products contain no lead and also support lead-free soldering. It is a product conforming to RoHS directive.

#### Packaging

Packing	Punched (Paper)Taping [180mm Reel]	
Minimum Package Qty	Nom	4000 Pcs
Minimum Order Qty	Nom	4000 Pcs

[Details](#)

**[ Caution ]**

Specifications which provide more details for the proper and safe use of the described product are available upon request.

● [ **Notice of Revision and Improve** ]

All specifications are subject to change without notice.

[PAGE TOP](#) 

Copyright(c) 1996-2008 All rights reserved.