



NOTES:

1. MATERIALS
SATA RECEPTACLE 15 PIN
P/N:10028509-001LF
INSULATOR: HIGH TEMP THERMOPLASTIC
UL94V-0, BLACK
CONTACT: COPPER ALLOY
CONTACT AREA: GOLD PLATED OVER NICKEL
 2. 2.50 WIRE TO BOARD 1x4. (CN2) JST EHR-4
INSULATOR: PA66 UL94V-0, WHITE.
CONTACT: COPPER ALLOY, TIN PLATED;
JST P/N: SEH-001T-P0.6
 3. SERIAL ATA CABLE
WIRE: UL 3385 22 AWG. PVC FREE
P/N: J99HF8522AA01 BLACK X 2
P/N: J99HF8522CA01 RED X 1
P/N: J99HF8522EA01 YELLOW X 1
MAKER: WONDERFUL
 4. HOOD: PBT 15%GF, COLOR BLACK
P/N: 10082616-5000HLF
2. PRODUCT SPEC: GS-12-194
PACKING SPEC: GS-14-866
3. THE PRODUCT IS NOT INTENDED TO EXPOSED TO A MANUFACTURING SOLDER PROCESS
4. PRODUCT NUMBERING

10077325-X XXX H LF

LEAD FREE
H: PVC & HELOGEN FREE

LENGTH CODE

050 - DIM. A: 50 ± 5 mm
060 - DIM. A: 60 ± 5 mm
078 - DIM. A: 78 ± 5 mm
085 - DIM. A: 85 ± 5 mm
095 - DIM. A: 95 ± 5 mm
105 - DIM. A: 105 ± 5 mm

PLATING CODE
5-15 U" GOLD

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		FCI	
ltr	ecn no	dr	date	linear	.X ± 0.38		projection	title	www.fciconnect.com	
A	T07-1136	S.Lin	11/01/07		.XX ± 0.25			S-ATA 15P POWER CABLE VT- RA ASS'Y		
B	T07-1177	S.Lin	12/05/07		.XXX ± 0.15					
C	T08-1024	S.Lin	02/15/08	angles	0' ± 2'					
D	T08-1090	S.Lin	05/13/08	dr	Sterling Lin	10/30/07	MM	product family	S-ATA	code
E	T08-1112	R.C	06/23/08	enrg	Sterling Lin	10/30/07	scale	size	dwg no	TWN
F	T08-1154	R.C	08/11/08	chr	Sterling Lin	10/30/07	N/A	A4	10077325	sheet
				appd	MINERVA WANG	10/30/07				1 of
sheet index	revision sheet	F	1							

ACAD