



4-Port Waveguide Junction Circulators

Description

These dual junction units are available in two configurations. Add the appropriate configuration letter at the end of the part number. Loads may be added to port 4 for a duplexer function or to ports 3 and 4 for a high ratio isolator application. Contact the factory for part numbers and specifications.

The 4-port waveguide junction circulators shown represent only a sampling of M/A-COM's product capability. Consult the factory for custom options.

Mechanical Outline



Specifications

Waveguide	Frequency (GHz)	Isolation (dB) Min./Max.	Insertion Loss (dB) Min./Max.	VSWR	Max. Oper. Power		Dimensions Inches (mm)			Circulator Model No.*
					Peak kW	Avg. W	L	W	H	
WR-284	2.8-3.1	20/35	.3/5	1.20	800	600	12.00(305.0)	5.00(122.5)	3.00(77.0)	8M590-101
WR-229	3.4-3.8	30/50	.2/4	1.05	1	50	10.00(254.0)	5.00(122.5)	2.00(51.0)	8M550-101
WR-187	3.9-5.0	20/40	.3/6	1.20	10	20	9.0(228.6)	4.25(108.0)	3.00(76.2)	8M204
WR-187	5.0-5.9	20/40	.3/6	1.20	10	20	9.0(228.6)	4.25(108.0)	3.00(76.2)	8M205
WR-137	5.9-6.5	26/40	.3/6	1.10	10	10	7.00(177.8)	3.25(82.6)	2.32(58.8)	8M207
WR-137	6.5-7.1	26/40	.3/6	1.10	10	10	7.00(177.8)	3.25(82.6)		8M208

Specifications Subject to Change Without Notice.

M/A-COM, Inc.

North America: Tel. (800) 366-2266
Fax (800) 618-8883

■ Asia/Pacific: Tel. +81 (03) 3226-1671
Fax +81 (03) 3226-1451

■ Europe: Tel. +44 (1344) 869 595
Fax +44 (1344) 300 020

Specifications continued

Waveguide	Frequency (GHz)	Isolation (dB) Min./Max.	Insertion Loss (dB) Min./Max.	VSWR	Max. Oper. Power		Dimensions Inches (mm)			Circulator Model No.*
					Peak kW	Avg. W	L	W	H	
WR-112	7.0-8.4	20/40	.3/6	1.20	10	10	5.00(127.0)	2.25(57.2)	2.00(50.8)	8M210
WR-112	7.1-8.6	26/40	.2/4	1.15	10	50	6.50(165.1)	3.00(76.2)	1.40(35.6)	8M551
WR-90	8.2-10.0	26/40	.4/8	1.10	10	100	4.62(117.3)	2.25(57.2)	2.00(50.8)	8M212
WR-90	8.5-9.6	20/40	.3/6	1.20	130	200	4.04(102.6)	1.63(41.4)	1.63(44.1)	8M623
WR-90	10.0-12.4	26/40	.4/8	1.10	10	100	4.62(117.3)	2.25(57.2)	1.95(49.5)	8M213
WR-75	10.7-11.7	26/40	.3/6	1.10	10	10	4.00(101.6)	1.75(44.5)	1.50(38.1)	8M214
WR-75	12.2-12.7	26/40	.3/6	1.10	10	10	4.00(101.6)	1.75(44.5)	1.50(38.1)	8M215
WR-75	12.2-13.2	26/40	.3/6	1.10	10	20	4.13(105.0)	16.5(42.0)	1.61(41.0)	8M311
WR-62	12.4-18.0	20/35	.3/6	1.20	10	10	3.00(76.2)	1.50(38.1)	1.44(36.6)	8M220
WR-62	13.0-15.0	20/40	.3/6	1.15	10	10	3.00(76.2)	1.50(38.1)	1.44(36.6)	8M216
WR-62	14.0-16.0	20/40	.3/6	1.15	10	10	3.00(76.2)	1.50(38.1)	1.44(36.6)	8M217
WR-62	15.0-17.0	20/40	.3/6	1.15	10	10	3.00(76.2)	1.50(38.1)	1.44(36.6)	8M218
WR-62	16.0-18.0	20/40	.3/6	1.15	10	10	3.00(76.2)	1.50(38.1)	1.44(36.6)	8M219
WR-42	18.0-22.5	20/35	.3/6	1.25	.5	5	2.50(63.5)	1.25(38.1)	1.00(25.4)	8M679-101
WR-42	23.0-25.0	20/35	.25/5	1.20	.5	5	2.50(63.5)	1.25(38.1)	1.00(25.4)	8M679-102
WR-42	21.0-26.5	20/35	.3/6	1.25	.5	5	2.50(63.5)	1.25(38.1)	1.00(25.4)	8M679-103

*Available in either "T" or "PI" configuration. Designate configuration by adding appropriate letter suffix to model number.
Mechanical sizes shown are for the "PI" configuration.

Specifications Subject to Change Without Notice.