

FEATURES AND SPECIFICATIONS


molex® Splash Proof Snap Plug and Receptacle Insulators

Features and Benefits

- Seals Snap Plug and Snap Plug Receptacle Terminals from moisture, condensation and contamination
- Provides insulation protection along with easy inspection of terminals
- Fits most 22AWG through 14AWG wire





Male Insulator





Female Insulator

Insulator	Part No.
Male	19161-0333
Female	19161-0334


Open Barrel Strip Snap Plugs and Receptacles





KRIMPITITE (No Strain Relief)													
Wire Range	Diameter	Pcs/Reel	Male Plug					Female Receptacle					
			Order No.	Length	Plating	Applicator w/Tool-Kit*	Spare Tool Kit	Order No.	Length	Plating	Detent Dimple	Applicator w/Tool-Kit*	Spare Tool Kit
14-18 (2.00-0.80)	.156	7000	19724-4000	13.33 (.525)	None	19061-0005	19031-0005	19723-4000	13.72 (.540)	None	Yes	19061-0006	19031-0006
			19724-4002		Tin			19723-4001		None	No		
								19723-4002		Tin	Yes		
								19723-4003		Tin	No		



VIBRAKRIMP (Strain Relief)													
Wire Range	Diameter	Pcs/Reel	Male Plug					Female Receptacle					
			Order No.	Length	Plating	Applicator w/Tool-Kit*	Spare Tool Kit	Order No.	Length	Plating	Detent Dimple	Applicator w/Tool-Kit*	Spare Tool Kit
14-18 (2.00-0.80)	.156	7000	19724-4100	18.03 (.710)	None	19061-0001	19031-0001	19723-4100	17.78 (.700)	None	Yes	19061-0002	19031-0002
								19723-4101		None	No		
								19723-4102		Tin	Yes		
								19723-4103		Tin	No		



KRIMPITITE (No Strain Relief)													
Wire Range	Diameter	Pcs/Reel	Male Plug					Female Receptacle					
			Order No.	Length	Plating	Applicator w/Tool-Kit*	Spare Tool Kit	Order No.	Length	Plating	Detent Dimple	Applicator w/Tool-Kit*	Spare Tool Kit
14-18 (2.00-0.80)	.180	6000	19724-4200	16.51 (.650)	None	19061-0007	19031-0007	19723-4200	16.51 (.650)	None	Yes	19061-0008	19031-0008
			19724-4202		Tin			19723-4201		None	No		
								19723-4202		Tin	Yes		
								19723-4203		Tin	No		



VIBRAKRIMP (Strain Relief)													
Wire Range	Diameter	Pcs/Reel	Male Plug					Female Receptacle					
			Order No.	Length	Plating	Applicator w/Tool-Kit*	Spare Tool Kit	Order No.	Length	Plating	Detent Dimple	Applicator w/Tool-Kit*	Spare Tool Kit
14-18 (2.00-0.80)	.180	6000	19724-4400	18.80 (.740)	None	19061-0003	19031-0003	19723-4400	19.86 (.782)	None	Yes	19061-0004	19031-0004
			19724-4402		Tin			19723-4401		None	No		
								19723-4402		Tin	Yes		
								19723-4403		Tin	No		

* The applicator with tool kit, designated by product type, contains the rear feed Mini-Mac applicator and complete tool kit of perishable components including crimp dies and cutter sets. In order to crimp a second product type in the same applicator, a spare tool kit for that product type is required.