



Notes: Unless Otherwise Specified:

- 1.0 Connector Electrical Characteristics:
 - 1.1 Withstanding Voltage: DC 500+50V
 - 1.2 Insulation Resistance: 100 megohms min.
 - 1.3 Contact Resistance: 30 milliohms max
- 2.0 Materials:
 - 2.1 Housing: High Temperature Thermoplastics UL94V-0
 - 2.2 Shell: Copper Alloy
 - 2.3 Contacts: Copper Alloy
 - 2.3 Back Shell: Steel
- 3.0 Finish:
 - 3.1 Shell: Tin-Lead or Bright Tin-Lead Plating
 - 3.2 Contacts: Plated Gold in Mating Area: Tin-Lead on Tails
- 4.0 Others:
 - 4.1 All Dimensions are in millimeters with Inch Equivalents Shown in Brackets
 - 4.2 Dimensioning Per ANSI Y14.5m-1982
 - 4.3 The Drawing are Redrew.



ITEM NO
A-IE-S-SMT-R

TITLE
IEEE 1394, for PCB Mounting, SMD Version



1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved