



D X X S 3 3 E 6 X X 0 9 L F

SEE NOTE RoHS

SERIES

NO.OF CONTACTS

09,15,25,37

TYPE OF CONTACTS

S-SOCKET

TYPE OF TERMINATION

33-ANGLED SPILL

PITCH 2.84 USA

FOOT PRINT 8.08 USA

HEIGHT OF TERMINATION

E-2.00mm COMPATIBLE FOR 1.6mm PCB

RoHS INFORMATIONS

"This LF product meets European Union Directives and other country regulations as described in GS-22-008"

The housing will withstand exposure to 260°C peak temperature for 30 seconds in a convection,infra-red or vapor reflow oven solder application.

Packaging as per GS-14-920

PRODUCT SPECIFICATION

See :- GS-12-433

PACKAGING SPECIFICATION

See :- GS-14-1157

PACKAGING SPECIFICATION

09- TRAY PACKAGING

MOUNTING OPTIONS

RV->LIF METAL PEG +F.SCREW LOCK UNC 4 40+METAL BRACKET

RL->LIF METAL PEG+ INSERT M3+METAL BRACKET

RX->LIF METAL PEG + INSERT UNC 4-40 +METAL BRACKET

PLATING

6->500 Mating/Un-mating performance  
4->200 Mating/Un-mating performance



Copyright FCI

mat'l. code SEE.TECH.SPEC				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection MM		product family DELTA-D			
ltr				ecn no		dr		date		tolerances unless otherwise specified		title	
A				I07-0038		GWJ		07-03-16		angles		DELTA-D A/S FEMALE PIP CONNECTOR	
B				I08-0175		AS		09-01-14		linear		US VERSION	
C				I09-0162		AS		2009-08-13		0°±1°		scale -	
										dr		ANISH.SALAM 2007-12-04	
										enr		ANISH.SALAM 2009-08-13	
										chr		ANISH.SALAM 2009-08-13	
										appd		ANISH.SALAM 2009-08-13	
sheet index		revision sheet		C C		1 2						FCI	
										dwg no		sheet 1 of 2 size 5	
												C-DD-0099 A3	
												type Product Customer Drawing	

