



orange 1	green 2
white	white
blue 3	brown 4
white	white

**Material:**

- Plug: YUS-06 8P8C 50μ"
- Conductor:
  - Wire: Cat.6 PIMF STR 26AWG
  - Bare Copper 26AWG 7/0.16±0.015MM
- Insulator:
  - Thickness Min. at any point: 0.2MM
  - Thickness Max. Avg.: 0.35MM
  - Diameter: 1.05±0.06MM
- Jacket PVC:
  - Thickness Min. at any point: 0.50MM
  - Thickness Max. Avg.: 0.60MM
  - Diameter: 6.1±0.02MM

PA/R	PINOUT		
	P1(T568B)	WIRE	P2(T568B)
1	1	WHT	1
	2	ORG	2
2	3	WHT	3
	6	GRN	6
3	4	BLU	4
	5	WHT	5
4	7	WHT	7
	8	PPN	8

⊕ = Assmann logo



ITEM NO.  
**A-MCSSP60005/G-R**  
 TITLE  
 Cat.6 SFTP Patch Cable - 8P8C 50μ", Green, 0.5 Meter

**ASSMANN**  
 Electronics, Inc.  
 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
 Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
 ©Copyright 2010 by Assmann Electronic Components  
 All International Rights Reserved