

# SSL12 - SSL14

## 1.0 AMP. Surface Mount Low $V_F$ Schottky Barrier Rectifiers

### SMA/DO-214AC




### Features

- ✧ For surface mounted application
- ✧ Metal silicon junction, majority carrier conduction
- ✧ Low forward voltage drop
- ✧ Easy pick and place
- ✧ High surge current capability
- ✧ Plastic material used carries Underwriters Laboratory Classification 94V-0
- ✧ Epitaxial construction
- ✧ High temperature soldering:  
260°C / 10 seconds at terminals

### Mechanical Data

- ✧ Cases: Molded plastic
- ✧ Terminals: Matte tin plating
- ✧ Polarity: Indicated by cathode band
- ✧ Packaging: 12mm tape
- ✧ Weight: 0.064 gram



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SSL12	SSL13	SSL14	Units
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	40	V
Maximum RMS Voltage	$V_{RMS}$	14	21	28	V
Maximum DC Blocking Voltage	$V_{DC}$	20	30	40	V
Maximum Average Forward Rectified Current See Fig. 1	$I_{(AV)}$	1.0			A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	50			A
Maximum Instantaneous Forward Voltage (Note 1) @ 1.0A	$V_F$	0.39			V
Maximum DC Reverse Current @ $T_A = 25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A = 100^\circ\text{C}$	$I_R$	0.2			mA
		50			
Maximum Thermal Resistance (Note 2)	$R_{\theta JL}$	28			$^\circ\text{C}/\text{W}$
	$R_{\theta JA}$	88			
Marking Code		SL12	SL13	SL14	
Operating Temperature Range	$T_J$	-55 to +125			$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 to +150			$^\circ\text{C}$

Notes: 1. Pulse Test with PW=300 usec, 1% Duty Cycle.

2. Measured on P.C. Board with 0.2 x 0.2" (5.0 x 5.0mm) Copper Pad Areas.

# SSL12 - SSL14

## 1.0 AMP. Surface Mount Low $V_F$ Schottky Barrier Rectifiers

### RATINGS AND CHARACTERISTIC CURVES (SSL12 THRU SSL14)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE

