



Features

- Frequency Range: 2.4~2.8GHz
- Standard Hermetic Package
- Operating Temperature Range: -55°C ~ +85°C


Specifications (50 Ω, V_{CC} = +12V, T_A = -55°C ~ +85°C)

Parameter	Symbol	Unit	Guaranteed	Typical
Frequency Range	f _L ~f _H	GHz	2.4~2.8	---
Gain	G _p	dB	≥22.0	24.0
Gain Flatness	ΔG _p	dB	---	±0.5
Noise Figure	F _n	dB	≤1.5Δ	1.2
Input VSWR	VSWR _i	---	≤2.5:1Δ	1.8:1
Output VSWR	VSWR _o	---	≤2.5:1Δ	1.6:1
Output Power @ 1dB Compression	P-1	dBm	≥10.0Δ	10.5
DC Current	I _{CC}	mA	---	65


“Δ” T_A = 24 ± 1°C;

Maximum Rating

- DC Voltage : +13.5VDC
- RF Input: +10dBm
- Storage Temp: +125°C




TO-8D



SMO-8D

Application Notes

1. Typical application shown as right, C₁ = 10~33 μF ; C₂ = 3300~6800pF;
2. See assembly section for mounting information
3. Connectorized package(SMA-1) available
4. ESD observe handling precautions



Typical Curves

