

New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

TELEPHONE: (201) 376-2922
(212) 227-6005
TELFX: 13-8720

1N3062 • 1N3063 • 1N3064 • 1N4305 • 1N4454
ULTRA FAST LOW CAPACITANCE
DIFFUSED SILICON PLANAR* DIODES

- C ... 2.0 pF @ $V_R = 0$, $f = 1.0$ MHz
- $t_{rr} \dots 4.0$ ns @ $I_f = 10$ mA, $R_L = 10$ mA, $V_r = 1.0$ V
- BV ... 75 V (MIN)

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$) (Note 1)

Maximum Temperatures

	1N3062	1N3063	1N3064	1N4454	1N4305
Storage Temperature	-65°C to +200°C	-65°C to +200°C	-65°C to +175°C	-65°C to +175°C	-65°C to +200°C
Operating Temperature	-65°C to +175°C	-65°C to +175°C	-65°C to +150°C	-65°C to +150°C	-65°C to +200°C

Maximum Power Dissipation

Total Dissipation	250 mW	250 mW	500 mW	500 mW
Linear Derating Factor	1.67 mW/°C	2.0 mW/°C	4.0 mW/°C	2.85 mW/°C

Maximum Voltages and Currents

WIV	Working Inverse Voltage	50 V	50 V	40 V	75 V
I_O	Average Rectified Current	75 mA	75 mA	200 mA	
I_F	Forward Current Steady State dc	115 mA	115 mA	400 mA	
i_f	Recurrent Peak Forward Current	225 mA	225 mA	600 mA	
i_f (surge)	Peak Forward Surge Current				
	Pulse Width = 1.0 s	500 mA	500 mA	1.0 A	
	Pulse Width = 1.0 μs	2.0 A	2.0 A	4.0 A	

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN.	MAX.	UNITS	TEST CONDITIONS
V_F	Forward Voltage	1N3062	1.0	V	$I_F = 20$ mA
		1N3063	0.700	V	$I_F = 10$ mA
		1N4305	0.610	V	$I_F = 2.0$ mA
			0.550	V	$I_F = 1.0$ mA
			0.505	V	$I_F = 250$ μA
		1N3064	1.0	V	$I_F = 10$ mA
I_R	Reverse Current	1N4454	0.1	μA	$V_R = 50$ V
			100	μA	$V_R = 50$ V, $T_A = 150^\circ\text{C}$
BV	Breakdown Voltage	75		V	$I_R = 5.0$ μA
t_{rr}	Reverse Recovery Time	1N4305	2.0	ns	$I_f = 10$ mA, $V_r = 6.0$ V, $R_L = 100$ Ω
		1N3062			
		1N3063			
		1N3064			
		1N4454	4.0	ns	
		1N4305			$I_f = I_r = 10$ mA, $R_L = 100$ Ω , $V_r = 1.0$ V
C	Capacitance	1N3062	1.0	pF	$V_R = 0$, $f = 1.0$ MHz
		1N3063			
		1N3064			
		1N4454	2.0	pF	$V_R = 0$, $f = 1.0$ MHz
		1N4305			
RE	Rectification Efficiency	1N3062	45	%	$f = 1.0$ MHz
	Forward Voltage Temperature Coefficient	1N3063			
		1N3064	1.8		mV/°C
		1N4454			
		1N4305	3.0		mV/°C