

New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
 SPRINGFIELD, NEW JERSEY 07081
 U.S.A.


TELEPHONE: (973) 376-2922
 (212) 227-8005
 FAX: (973) 376-8860

PARAMETERS

SI RECTIFIER, 5A < I(O)/I(F) ≤ 10A 1N250


Description: Si Rectifier, 5A < I(O)/I(F) ≤ 10A

Manufacturer.....	many
Mil/High-Rel? (Y/N).....	
I(out) (If AVG) Max.....	10
@Temp. (test) (°C).....	150n
VRRM.....	200
1-Cycle Surge Current (A).....	
Vf Max.....	1.5
@If (test).....	25
@Temp. (test) for Vf).....	25
Ir @25°C.....	
@Volts (test) (V).....	200
Ir @ Diff. Temp (A).....	5.0m
@Temp (test) (°C).....	150#
Oper. Temp (°C) Max.....	175•
Pkg Style.....	DO-5
Surface Mounted (Y/N).....	N



NOTES:

1. COMPLETE THREADS TO EXTEND TO WITHIN 2-1/2 THREADS OF SEATING PLANE.
2. ANGULAR ORIENTATION OF THIS TERMINAL IS UNDEFINED.
3. 1/4-28 UNF-2A. MAXIMUM PITCH DIAMETER OF PLATED THREADS SHALL BE BASIC PITCH DIAMETER (.2268", 5.74 MM) REF. (SCREW THREAD STANDARDS FOR FEDERAL SERVICES 1957) HANDBOOK H28 1957 P1.
4. MINIMUM FLAT



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.