## TOSHIBA LED Lamp InGaAlP Pure Green Light Emission

# TLPGE183P


#### Panel Circuit Indicator

Unit in mm

- 5mm diameter(T1-3/4)
- InGaAlP pure green LED
- All plastic mold type.
- Colorless clear lens
- Low drive current, high intensity pure green light emission Recommended forward current: IF =  $15 \sim 20 \text{mA(DC)}$
- All plastic molded lens, provides an excellent on-off contrast ratio.
- Fast response time, capable of pulse operation.
- · High power luminous intensity
- Without stand-offs
- Applications: Suitable for traffic signal, safety equipment, automotive

## **Maximum Ratings (Ta = 25°C)**

Characteristic	Symbol	Rating	Unit
Forward current (DC)	I <sub>F</sub>	50	mA
Reverse voltage	$V_{R}$	4	V
Power dissipation	P <sub>D</sub>	140	mW
Operating temperature range	T <sub>opr</sub>	-30~85	°C
Storage temperature range	T <sub>stg</sub>	-40~120	°C



## **Electrical And Optical Characteristics (Ta = 25°C)**

Characteristic	Symbol	Test Condition	Min	Тур.	Max	Unit
Forward voltage	V <sub>F</sub>	I <sub>F</sub> = 20mA	_	2.27	2.8	V
Reverse current	I <sub>R</sub>	V <sub>R</sub> = 4V	_	_	50	μΑ
Luminous intensity	l <sub>V</sub>	I <sub>F</sub> = 20mA (Note)	476	2000	_	mcd
Peak emission wavelength	λρ	I <sub>F</sub> = 20mA	_	562	_	nm
Spectral line half width	Δλ	I <sub>F</sub> = 20mA	_	11	_	nm
Dominant wavelength	$\lambda_{d}$	I <sub>F</sub> = 20mA	_	558	_	nm

(Note): Lamps are classified into the following ranks according to their luminous intensity.

Measurement tolerance for each limit is ±15%.


R: 560-1120mcd, S: 1000-2000mcd, T: 1800-3600mcd


### **Precaution**


Please be careful of the followings


- Soldering temperature: 260°C max Soldering time: 3s max (Soldering portion of lead: Up to 2mm from the body of the device)
- If the lead is formed, the lead should be formed up to 5mm from the body of the device without forming stress to the resin. Soldering should be performed after lead forming.
- This visible LED lamp also emits some IR light. If a photodetector is located near the LED lamp, please ensure that it will not be affected by this IR light.

2











Radiation Pattern

Ta = 25 °C





3 2002-09-25

#### **RESTRICTIONS ON PRODUCT USE**

000707EAC

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes
  are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the
  products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with
  domestic garbage.
- The information contained herein is presented only as a guide for the applications of our products. No
  responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other
  rights of the third parties which may result from its use. No license is granted by implication or otherwise under
  any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.