

## ADSL Transformer

## P5341

### Features

- \* Lead-free (Pb-free)
- \* RoHS compliant
- \* Low Distortion
- \* IEC 60950 and UL 60950 certified
- \* Supplementary Insulation
- \* Industry Standard Footprint

### Applications

- \* TI chip set TNETD7300


---

### DESCRIPTION

P5341 is a low distortion transformer for TI chip set TNETD7300.

P5341 is certified to IEC 60950 and UL 60950 for supplementary insulation for a primary circuit, 250V working voltage. P5341 is a UL Recognized Component and is supported by an IEC CB Test Certificate. The part is completely lead-free, compliant with RoHS Directive 2002/95/EC, and suitable for lead-free and conventional processing.

The safety system yields very low transformer parasitics, ensuring that P5341 exhibits excellent frequency response and balance; in combination with its good harmonic distortion performance, P5341 is ideally suited to low cost yet demanding ADSL applications.



## SPECIFICATIONS

### Electrical



Typical values at T = 25°C, unless otherwise stated.

Parameter	Conditions	Min	Typ	Max	Units
Inductance	10kHz 100mV 1-4 (link 2-3)	1.42	1.5	1.58	mH
Leakage inductance	100kHz, 100mV, 1-4 (link 2-3; link 7, 8, 9, 10)	-	-	14	μH
Interwinding capacitance	100kHz 100mV 1-10 (link 2, 3; link 8, 9)	-	-	33	pF
Third Harmonic <sup>(1)</sup> Distortion	30kHz, 5.3Vrms (link 2-3; link 8-9)	-	-	-84	dB
DC resistance	1-4 (link 2-3) 10-7 (link 8-9)	-	-	2.55	Ω
		-	-	0.65	Ω
Turns ratio	1-4: 10-7 (link 3, 2; link 8,9)	1.96	2.00	2.04	-
Voltage isolation <sup>(2)</sup>	50Hz DC (1, 2, 3, 4 : 7, 8, 9, 10)	2.12	-	-	kVrms
		3.0	-	-	kV
Operating range: Functional Storage	Ambient temperature	-40	-	+85	°C
		-40	-	+85	°C

### Notes

1. 33Ω source, 130Ω load.
2. Components are 100% tested at 3.25kV DC.

**CONSTRUCTION**



Dimensions shown are in millimetres (inches).

**SAFETY**

Constructed in accordance with IEC 60950-1 and UL 60950-1, supplementary insulation for a primary circuit, 250V maximum working voltage, flammability class V-0.

**ABSOLUTE MAXIMUM RATINGS**

(Ratings of components independent of circuit).

Short term isolation voltage (1s)	2.12kVrms, 3.0kVDC
Storage temperature	-40°C to +85°C
Terminal temperature (10s)	260°C

## CERTIFICATION

Certified under the IEC CB scheme to IEC 60950:1999 (IEC CB Test Certificate No. GB637W) sub-sections 1.5, 2.9, 2.10.3.1, 2.10.3.2, 2.10.4, 2.10.5, 2.10.5.2, 2.10.5.4, 4.5, 4.7.3, 4.7.3.1, 4.7.3.4, (class V-0) and 5.2, for a maximum working voltage of 250Vrms, nominal mains supply voltage not exceeding 300Vrms and a maximum operating temperature of +85°C in Pollution Degree 2 environments, supplementary insulation for a primary circuit.

Recognized under the Component Recognition Program of Underwriters Laboratories Inc. to US and Canadian requirements CAN/CSA C22.2 No. 60950-1-3/UL60950-1, First Edition, maximum working voltage 250Vrms, Pollution Degree 2, supplementary insulation for a primary circuit.

UL File number E203175

Additionally, Profec Technologies certifies all transformers as providing voltage isolation of 2.12kVrms, 3kV DC minimum. All shipments are supported by a Certificate of Conformity to current applicable safety standards

## COPYRIGHT

ETAL and P5341 are Trade Marks of Profec Technologies Ltd.

The Trade Mark ETAL is registered at the UK Trade Marks Registry.

Profec Technologies Ltd. is the owner of the design right under the Copyright Designs and Patents Act 1988 and no rights or licences are hereby granted or implied to any third party.

© 2000-2005 Profec Technologies Ltd.  
Reproduction prohibited.



ETAL Group Oy, Kuormatie 14, FIN-03101, Nummela  
Telephone: +358 (0)20 7500 330 Fax: +358 (0)20 7500 333  
Website: [www.etalgroup.com](http://www.etalgroup.com) Email: [etalgroup@egruppen.com](mailto:etalgroup@egruppen.com)